

CLICK BOND, INC -- KA1-E1-CP-125-000-005A1A1 PATCH KIT, PART B -- 8040-01-107-3981

=====
Product Identification
=====

Product ID:KA1-E1-CP-125-000-005A1A1 PATCH KIT, PART B

MSDS Date:04/28/1992

FSC:8040

NIIN:01-107-3981

Kit Part:Y

MSDS Number: BNRSR

=== Responsible Party ===

Company Name:CLICK BOND, INC

Address:2151 LOCKHEED WAY

City:CARSON CITY

State:NV

ZIP:89706-0713

Country:US

Info Phone Num:7

02-885-8000/702-883-0191

Emergency Phone Num:702-885-8000

Preparer's Name:A B CARTER

CAGE:MO939

=== Contractor Identification ===

Company Name:CLICK BOND DIV OF PHYSICAL SYSTEMS INC

Address:2151 LOCKHEED WAY

Box:City:CARSON CITY

State:NV

ZIP:89701-0713

Country:US

Phone:775-885-8000

CAGE:66530

Company Name:CLICK BOND, INC

Address:2151 LOCKHEED WAY

City:CARSON CITY

State:NV

ZIP:89706

Country:US

Phone:702-885-8000/702-883-0191

CAGE:MO939

=====
Composition/Information on Ingredients
=====

=====

Ingred Name:TRADE SECRET POLYMER (RESIN CURE)
Other REC Limits:NONE SPECIFIED

Ingred Name:TRADE SECRET CURE AGENT (RESIN CURE)
Other REC Limits:NONE SPECIFIED

Ingred Name:TRADE SECRET INFORMATION AVAILABLE ON REQUEST TO QUALIFIED
MEDICAL PERSONNEL.
RTECS #:9999999ZZ
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MAY CAUSE MODERATE SKIN AND/OR
EYE IRRITATION. CHRONIC: NO LONG TERM EFFECTS HAVE BEEN NOTED DUE
TO EXPOSURE TO THIS MATERIAL.
Effects of Overexposure:SKIN OR EYE IRRITATION.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN CONDITIONS.

===== First Aid Measures =====

First Aid:SKIN: WASH SKIN OR EYES WITH WATER IF CONTACT OCCURS.
INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE AMOUNTS OF WATER OR
MIL
K IF AVAILABLE AND TRANSPORT TO MEDICAL FACILITY.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:495F,257C
Extinguishing Media:DRY CHEMICAL, FOAM, CO2.
Fire Fighting Procedures:COOL EXPOSED CONTAINERS TO PREVENT RUPTURE IN
FIRE CONDITIONS.
Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH VERMICULITE, CLAY OR COMMERCIAL
ABSORBENT. PLACE I

N COVERED CONTAINER FOR DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions: I P R Y RNI D FH PMMPERATURCS.

Other Precautions: WASH HANDS BEFORE EATING OR SMOKING.

ET IN EYES. AVOID CONTACT WITH SKIN OR CLOTHIN

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: G. AVOID BREATHING VAPOR, MIST, OR SPRAY.

KEEP AWAY FROM HEAT, SPARKS, OR FLAMES. E

ELECTRICALLY BOND AND

GROUND METAL CONTAINERS FOR TRANSFER TO ELIMINATE STATIC SPARKS.

STORE IN TIGHTLY CLOSED CON TAINERS IN COOL, DRY, WELL VENTILATED

AR

Ventilation: EA AWAY FROM SOURCE OF IGNITION. USE NIOSH

APPROVED RESPIRATOR SUITABLE FOR ORGANIC VAPORS, IF VAPORS, IF R

Protective Gloves: EQUIRED.

Other Protective Equipment: EXPLOSION PROOF GENERAL MECHANICAL

Work Hygienic Practices: VENTILATION AND LOCAL EXHAUST.

WEAR IMPERVIOUS GLOVES.

Supplemental Safety and

Health

=====
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: >212F, >100C

Vapor Pres: