

3M GENERAL OFFICES CO. -- SCOTCH-WELD (TM) 2216 PART A GRAY EPOXY ADH --
8040-00-145-0530

===== Product Identification =====

Product ID:SCOTCH-WELD (TM) 2216 PART A GRAY EPOXY ADH

MSDS Date:04/25/1992

FSC:8040

NIIN:00-145-0530

Kit Part:Y

MSDS Number: BNSZC

=== Responsible Party ===

Company Name:3M GENERAL OFFICES CO.

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Nu

m:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:04963

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

===== Composition/Information on Ingredients =====

Ingred Name:AMINE TERMINATED POLYMER - NJ REGISTRY NO 04499600-5569P

Fraction by Wt: 55-70%

Other REC Limits:NONE SPECIFIED

Ingred Name:KAOLIN

CAS

:1332-58-7
RTECS #:GF1670500
Fraction by Wt: 30-45%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: .01-.1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYE: EXTREMELY IRRITATING. DUST FROM
GRINDIN
G, SANDING, CUTTING CURED MAT'L: IRRITATION. SKIN:
IRRITATION ON PROLONGED CONTACT. ALLERGIC SKIN REACTION IN SOME.
INHALATION: VAPOR: RESPIRATORY IRRITATIO N. DUST FROM GRINDING,
SANDING, CUTTINGCURED MATERIAL: RESPIRATORY IRRITATION. INGESTION:
DIGESTIVE SYSTEM IRRITATION.

===== First Aid Measures =====

First Aid:EYE: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 10
MINUTES. CALL A PHYSICIAN. SKIN: THOROUGHLY WASH AFFECTED AREAS
WITH SOAP AND WATER. INHALATION: REMOVE PERSON TO UNCONTAMINATED
AIR. CALL A PHYSICIAN. IF SWALLOWED: DO NOT INDUCEVOMITING.
IMMEDIATELY CALL A PHYSICIAN OR POISON CONTROL CENTER.

===== Fire Fighting Measures =====

Extinguishing Media:CO2, FOAM, DRY CHEMICAL, WATER.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED
BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING THIS MATERIAL.
Unusual Fire/Explosion Hazard:NONE.

=====

===== Accidental Release Measures =====

Spill Release Procedures: VENTILATE THE AREA. OBSERVE THE PRECAUTIONS FROM OTHER SECTIONS. COLLECT SPILLED MATERIALS. PLACE IN A US DEPARTMENT OF TRANSPORTATION--APPROVED METAL CONTAINER, AND SEAL.

===== Handling and Storage =====

Handling and Storage Precautions: FOR INDUSTRIAL & PROFESSIONAL USE ONLY. MAT'L IS PART OF TWO COMPONENT SYSTEM. USE ONLY W/SUFF VENT TO REMOVE VAPORS/PREVENT VA
POR BLDUP.

Other Precautions: PRECAUTIONS FOR EACH COMPONENT SHOULD BE OBSERVED WHEN SEPARATE/MIXED. AVOID BREATHING VAPOR RELEASED DURING HEAT CURING. VENT CURING EQUIP TO OUTDOORS. AVOID EYE CONTACT. WEAR EYE PROTECTION (SAFETY GLASSES/GOGGLES). AVOID SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR DUST MASK TO AVOID DUST EXPOSURE.
Ventilation: VENT CURING EQUIPMENT TO OUTDOORS OR SUITABLE EMISSION CONTROL DEVICE.

Pr

otective Gloves: WEAR IMPERVIOUS GLOVES.

Eye Protection: SAFETY GLASSES OR CHEMICAL GOGGLES.

Other Protective Equipment: WEAR PROTECTIVE CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT.

Work Hygienic Practices: WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

AVOID EYE CONTACT W/BREATHING DUST FROM CUTTING, GRINDING OR SANDING OPERATIONS ON THE CURED PRODUCT. KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN.

===== Physical/Chemical Properties =====

HCC: N1

Spec Gravity: 1.260 (WATER=1)

Viscosity: 52.0 CPS

Solubility in Water: NIL

Appearance and Odor: PASTE, GRAY, PUNGENT ODOR.

Percent Volatiles by Volume: 0.00

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: CO, CO₂, N AND SMOKE PARTICLES WHEN SUBJECTED TO EXCESSIVE HEAT OR FLAME.

===== Disposal Considerations =====

Waste Dispo

sal Methods:MIX PART A W/PART B. COMPLETELY CURE & DISPOSE
OF FULLY CURED WASTE PRODUCT IN SANITARY LANDFILL. INCINERATE
UNCURED BULK PRODUCT AFTER MIXING W/FLAMMABLE MATERIAL IN
INDUSTRIAL/COMMERCIAL FACILITY. D ISPOSAL SHOULD BE IN ACCORDANCE
W/APPLIC REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or
implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.