

ACCUMETRIC INC -- BOSS 444-GREASE,MIL-L-15719 A -- 9150-01-080-9652

=====
Product Identification
=====

Product ID:BOSS 444-GREASE,MIL-L-15719 A

MSDS Date:12/10/1985

FSC:9150

NIIN:01-080-9652

MSDS Number: BNTQC

=== Responsible Party ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-769-3385

Emergency Phone Num:502-769-33

85

Preparer's Name:DEBBIE DUNN

CAGE:58149

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

=====
Composition/Information on Ingredients
=====

Ingred Name:MOLYKOTE 44 GREASE

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NOT ESTABLISHED.

ACGIH TLV:NOT ESTABLISHED.

=====
Hazards Identification
=====

LD50 LC50

Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE- EYES:MAY IRRITATE, SLIGHT PAIN, REDNESS & POSSIBLE MINOR CORNEAL INJURY. SKIN:SEVERAL REPEATED/PROLONGED CONTACT MAY CAUSE MILD IRRITATION. INHALED:VERY SLIGHT IRRITATION TO EYES OR RESPIRATORY TRACT POSSIBLE. ORAL:UNLIKELY. CHRONIC- MAY CAUSE SKIN IRRITATION.

Effects of Overexposure:MAY CAUSE

EYE IRRITATION, SLIGHT PAIN, REDNESS

& POSSIBLE MINOR CORNEAL INJURY. SEVERAL REPEATED/PROLONGED SKIN CONTACT MAY CAUSE MILD IRRITATION. INHALATION MAY CAUSE VERY SLIGHT IRRITATION TO EYES OR RESPIRATORY TRACT. INGESTION IS UNLIKELY.

Medical Cond Aggravated by Exposure:PREEXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:EYES:IMMEDIATELY FLUSH WITH WATER. SKIN:WIPE OFF EXCESS AND

WASH SKIN WITH SOAP AND WATER. INHALED/ORAL:NO FIRST AID SHOULD BE NEEDED. IF SYMPTOMS DEVELOP, SEE PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:OC

Flash Point:>250F,>121C

Extinguishing Media:USE WATER FOG, CO2, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:

None Known.

=====
Accidental Release Measures
=====

Spill Release Procedures:SCOOP UP EXCESS GREASE. CLEAN AREA WITH APPROPRIATE CLEANER OR USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORAGE- STORE AWAY FROM FLAMES, HIGH TEMPERATURES AND OXIDIZING AGENTS.

Other Precautions:MINIMIZE SKIN CONTACT. WASH WITH SOAP & WATER BEFORE

EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES ,INCLUDING SHOES, THAT CANNOT BE CLEANED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT ORDINARY REQUIRED. USE A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR IF NEEDED.

Ventilation:MECHANICAL (GENERAL)

Protective Gloves:WASH HANDS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EY

E WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:< 5

Spec Gravity:1.05

Evaporation Rate & Reference: