

FARWEST PAINT MANUFACTURING CO. -- EXTERIOR TRIM ENAMEL BROWN 10076 --
8010-01-333-9447

=====
Product Identification
=====

Product ID:EXTERIOR TRIM ENAMEL BROWN 10076
MSDS Date:09/19/1991
FSC:8010
NIIN:01-333-9447
MSDS Number: BNTVW
=== Responsible Party ===
Company Name:FARWEST PAINT MANUFACTURING CO.
Address:4522 S. 133RD ST.
City:TUKWILA
State:WA
ZIP:98168
Country:US
Info Phone Num:206-244-884
4
Emergency Phone Num:206-941-1619
CAGE:2F266

=== Contractor Identification ===
Company Name:FARWEST PAINT MANUFACTURING CO
Address:4522 S 133RD ST
City:TUKWILA
State:WA
ZIP:98168
Country:US
Phone:206-244-8844
CAGE:2F266

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 4.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:TEXANOL (ESTER A

LCOHOL)
CAS:25265-77-4
RTECS #:UF6000000
Fraction by Wt: 2.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:VOC: 62 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHAL: PROLONGED IN CONFINED
AREAS, MAY LEAD TO MUCUS MEMBRANCE IRRIT,
DIZZINESS, HEADACHE.
SKIN: IRRIT OF THE SKIN. EYE: IRRITATION OF THE EYES. INGESTION:
AMOUNTS INGESTED INCIDENTAL TO CONSUMER AND INDUSTRIAL HANDLING
ARE NOT LIKELY TO CAUSE INJURY, HOWEVER, INGESTION OF LARGER AMTS
COULD CAUSE SERIOUS INJURY
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIONS. (SEE SECTION VIII).

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. IF RESPI
RATORY SYMPTOMS DEVELOP,
SEEK MEDICAL ATTN AT ONCE. SKIN: WASH OFF QUICKLY WITH PLENTY OF
WATER, THEN SOAP & WATER. REMOVE AND WASH CONTAMINATED CLOTHING
BEFORE REUSE. EYE: FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER,
ESPECIALLY UNDER LIDS, FOR AT LEAST 15 MINUTES. OBTAIN EMERGENCY
MEDICAL TREATMENT. INGESTION: IF SWALLOWED, OBTAIN MEDICAL
TREATMENT IMMEDIATELY.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL,

WATER OR WATER FOG

Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS

Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

===== Handling and Storage ==
=====

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND APPROPRIATELY LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS IN SECTION II.

Ventilation:LOCAL EXHST PREFERABLE. GEN EXHST ACCEPTABLE IF THE EXPOS TO MATLS IN SECT II IS MAINTAINED BELOW APPLICABLE EXPOS LIMIT

Protective Gloves:RECOMMENDED BY GLOVE SUPPLIER

Eye Protection:SFTY SPECTACLES W/UNPERFORATED SIDESHLDs

Other Protective Equipment:EYE WASH, SAFETY SHOWERS, GOGGLES, SAFETY GLASSES, IMPERVIOUS GLOVES

Work Hygienic Practices:KEEP WORK AREA CLEAN/FREE FROM SPILLS/LEAKS. ALWAYS WASH HANDS THOROUGHLY W/SOAP & WATER BEFORE HNDLG FOOD/DRINK/SMOKING

Suppl
emental Safety and Health
USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:23.8 @ 25C

Vapor Density:> THAN AIR

Spec Gravity:9-11 LB/GL

pH:7-8

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR, COLOR OF TINT.

===== Stability

and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZERS AND/OR HYDROFLUORIC ACID

Stability Condition to Avoid: ELEVATED TEMPERATURES, CONTACT WITH
OXIDIZING AGENTS

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.