

BAKER SEALANTS AND COATINGS CO -- ADHESIVE, X-822 -- 8040-00-291-8625

=====
Product Identification
=====

Product ID:ADHESIVE, X-822
MSDS Date:01/30/1990
FSC:8040
NIIN:00-291-8625
MSDS Number: BNWKT
=== Responsible Party ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:B
City:JERSEY CITY
State:NJ
ZIP:07304
Country:US
Info Phone Num:201-333-6986
Emergency Phone Num:201-333-6986/800-424-9300 CHEMTREC
Preparer's Name:MARIO NAVARRO
CAGE:34094
=== Contractor Identification ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:City:JERSEY CITY
State:NJ
ZIP:07304-3306
Country:US
Phone:201-333-6986
CAGE:34094

=====
Composition/Information on Ingredients
=====

Ingred Name:VM&P NAPHTHA
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 80-85%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:300 PPM

Ingred Name:TOLUENE (SARA III)
CAS:108-88

RTECS #:XS5250000

Fraction by Wt: 3-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: CAN CAUSE SEVERE IRRITATION.

SKIN: CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS.

INHALATION: CAN CAU

SE NASAL & RESPIRATORY IRRITATION, CENTRAL

NERVOUS SYSTEM EFFECTS. INGESTION: CAN CAUSE GASTROINTESTINAL

IRRITATION. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE

CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL.

Effects of Overexposure:EYES: REDNESS, TEARING, BLURRED VISION.

INHALATION: CENTRAL NERVOUS SYSTEM EFFECTS: DIZZINESS, WEAKNESS,

FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONSCIOUSNESS, AND EVEN

DEATH. INGESTION: NAUSEA, VOMI TING AND DIARRHEA.

Medical Cond Aggravated

by Exposure:SKIN CONTACT MAY AGGRAVATE AN

EXISTING DERMATITIS.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH W/LRG AMT WATER, LIFTING EYELIDS. GET MED ATTN.

SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. IF

BREATHING DIFFICULT, ADMINISTER OXYGEN. IF BREATHING STOPPED, GIVE

ARTIFICIAL RESPIRATION. KEEP WARM, QUIET. GET MEDATTN. INGESTION:

DON'T INDUCE VOMIT, KEEP WARM, QUIET. GET MED AID. ASPIRATION OF

MAT'L INTO

LUNG DUE TO VOMITING CAN CAUSE CHEMICAL PNEUMONITIS, CAN

BE FATAL.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:72.0F,22.2C

Autoignition Temp:Autoignition Temp Text:480F

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE OR FOAM.

Fire Fighting Procedures:KEEP AWAY FROM SOURCES OF IGNITION. WEAR

SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:ALL LARGE METAL CONTAINERS SHOULD BE

GROUNDED AND/OR BONDED WHEN MATERIAL IS TRANSFERRED.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITE SOURCES. ABSORB LIQ W/ABSORB & SHOVEL TO CNTNRS. EXCLUDE PERSONS NOT WEARING PROTECT EQUIP FROM AREA. STOP SPILL AT SOURCE, DIKE AREA, PUMP LIQ TO SALVAGE TANK. PREVENT RUN-OFF TO WATER BODIES. IF RUN-OFF OCCURS, NOTIFY AUTHORITIES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF IGNITION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR SELF-CONTAINED BREATHING APPARATUS.
Ventilation:LOCAL EXHAUST OR MECHANICAL VENTILATION.
Protective Gloves:IMPERVIOUS GLOVES.
Eye Protection:SAFETY GLASSES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:240F,116C
Melt/Freeze Pt:M.P/F.P Text: