

DOLPH JOHN C CO -- DOLPH-SPRAY -- 5970-00-076-8988

=====  
Product Identification  
=====

Product ID:DOLPH-SPRAY

MSDS Date:01/17/1990

FSC:5970

NIIN:00-076-8988

MSDS Number: BPBHX

=== Responsible Party ===

Company Name:DOLPH JOHN C CO

Address:WEST NEW RD

Box:267

City:MONMOUTH JUNCTION

State:NJ

ZIP:08852-9513

Country:US

Info Phone Num:201-329-2333

Emergency Phone Num:201-329-2333

CAGE:72688

=== Contrac

tor Identification ===

Company Name:JOHN C. DOLPH COMPANY

Address:NEW ROAD

Box:267

City:MONMOUTH JUNCTION

State:NJ

ZIP:08852

Country:US

Phone:908-329-2333

CAGE:72688

Company Name:LAMINATED MATERIALS CORP.

Address:162 W LIPPINCOTT ST

Box:6710

City:PHILADELPHIA

State:PA

ZIP:19133-4221

Country:US

Phone:215-425-4100

CAGE:20200

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10-20%

OSHA PEL:200 PPM/15

0 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 1%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE (SARA III)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 20-30%  
OSHA PEL:1000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL CHLOROFORM (1,1,1-TRIC  
HLOOROEHANE) (SARA III)  
CAS:71-55-6  
RTECS #:KJ2975000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:350 PPM/450 STEL  
ACGIH TLV:350 PPM/450STEL;9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 25-30%  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTYL ACETATE (SARA III)  
CAS:110-19-0  
RTECS #:AI4025000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ACETATE (SARA III)  
CAS:141-78-6  
RTECS #:AH5425000  
Fraction by Wt: 15-25%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:400 PPM  
ACGIH TLV:400 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)  
CAS:117-81-7  
RTECS #:TI0350000  
Fraction by Wt: 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3/10 STEL  
ACGIH TLV:5 MG/M3; 9293  
EPA Rpt Qty  
:100 LBS  
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: MAY CAUSE SKIN AND EYE IRRITATION ON CONTACT. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. MAY CAUSE RESPIRATORY SYSTEM IRRITATION OR CENTRAL NERVOUS SYSTEM DEPRESSION IF VAPORS INHALED. MAY CAUSE IRRITATION OF GI TRACT OR CENTRAL NERVOUS SYSTEM DEPRESSION IF SWALLOWED.CHRONIC: DERMATITIS,LIVER/KIDNEY DAMAGE.  
Explanation of Carcinogenicity:DIOCTYL PHTHALATE IS LISTED AS A SUSPECTED CARCINOGEN (MANUFACTURER).  
Effects of Overexposure:BURNING OF EYES, REDNESS AND CRACKING OF THE SKIN, DROWSINESS, DIZZINESS, LOSS OF COORDINATION AND FATIGUE, VOMITING.  
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE

AT INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION: INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:40.0F,4.4C  
Lower Limits:1.8  
Upper Limits:12.0  
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE AEROSOL CANS TO RUPTURE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:STAY UPWIND AND AWAY FROM SPILL. KEEP ALL SOURCES OF IGNITION AND HOT METAL SURFACES AWAY FROM SPILL. USE SAND OR OTHER INERT MATERIAL TO CONTAIN SPILL. DO NOT FLUSH AREA WITH WATER, KEEP OUT OF DRAINS. USE ABSORBENT PADS.  
Neutralizing Agent:NOT APPLICABLE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM SOURCES OF IGNITION.  
Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, ETC. ON THE CONTAINER.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE AND DUST/MIST

PRE-FILTER RESPIRATORS AS PER CURRENT 29  
CFR 1910.134, INSTRUCTIONS/ WARNINGS AND NIOSH-RESPIRATOR  
SELECTION.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.  
LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:PLASTIC OR RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD P

PERSONAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR  
FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO  
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:40.0F,4.4C

Vapor Density:4.0(AIR=1)

Spec Gravity:0.8

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and O

lor:ORANGE; SOLVENT ODOR

Percent Volatiles by Volume:75-85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

THIS MATERIAL IS INCOMPATIBLE WITH STRONG ACIDS OR BASES, OXIDIZING  
AGENTS, AND SELECTED AMINES.

Stability Condition to Avoid:HIGH TEMPERATURE STORAGE.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOUL

D BE MADE IN ACCORDANCE WITH ALL  
APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify  
and  
assume responsibility for the suitability of this information to their  
particular situation.