

B P OIL COMPANY -- GASOLINE,BP SUPER NO LEAD -- 9130-00-148-7104

=====  
Product Identification  
=====

Product ID:GASOLINE,BP SUPER NO LEAD

MSDS Date:05/03/1988

FSC:9130

NIIN:00-148-7104

MSDS Number: BPBJF

=== Responsible Party ===

Company Name:B P OIL COMPANY

Address:200 PUBLIC SQUARE

Box:6989

City:CLEVELAND

State:OH

ZIP:44114-2375

Country:US

Info Phone Num:216-586-6499/800-424-9300(CHEMTREC)

Emerg

ency Phone Num:800-321-8642/800-362-8059(OH ONLY)

Preparer's Name:PATNESKY

CAGE:0MJ97

=== Contractor Identification ===

Company Name:B P OIL COMPANY

Address:200 PUBLIC SQUARE

Box:6989

City:CLEVELAND

State:OH

ZIP:44114-2375

Country:US

Phone:800-321-8642/800-362-8059(OH ONLY)

CAGE:0MJ97

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1PPM/5STEL;1910.102

8

ACGIH TLV:10 PPM; A2; 9293

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 12%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 11%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150 STEL;9293

EPA Rpt Qty:1000 LBS

DOT Rpt Q

ty:1000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III)

CAS:95-63-6

RTECS #:DC3325000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:25 PPM

ACGIH TLV:25 PPM; 9293

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125 STEL 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANE (SARA III)

CAS:110-82-7

RTECS #:GU6300000

Fraction by Wt: 1%

Other REC

Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM, 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: IRRITATION BY CONTACT. CENTRAL NERVOUS SYSTEM EFFECTS IF INHALED. IF SWALLOWED, MAY BE ASPIRATED INTO LUNGS, RESULTING IN PULMONARY EDEMA AND CHEMICAL PNEUMONITIS.

CHRONIC: REPEATED CONTACT MAY CAUSE DEFATTING. BENZENE IS A CONFIRMED CARCINOGEN AND MAY PRODUCE BLOOD CHANGES.

Explanation of Carcinogenicity:BENZENE IS A CONFIRMED CARCINOGEN BY NTP, IARC AND OSHA.

Effects of Overexposure:EYES/SKIN: SLIGHT IRRITATION, REDNESS.

INGESTION: NAUSEA, VOMITING, DIARRHEA, HEADACHE, DIZZINESS, BLURRED VISION, CONVULSION, UNCONSCIOUSNESS, DEATH. ASPIRATION INTO LUNG AFTER INGESTION MAY CAUSE PULMONARY EDEMA AND CHEMICAL PNEUMONITIS.

HALATION: SAME SYMPTOMS AS INGESTION PLUS ANEMIA AND IRREGULAR HEART RHYTHM.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH A HISTORY OF RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.SEE DOCTOR.

SKIN: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH WITH SOAP AND WATER.SEE DOCTOR. INHALATION: REMOVE VICTIM TO FRESH AIR.GIVE OXYGEN/

CPR IF NEEDED.SEE DOCTOR. INGESTION: DO NOT INDUCE

VOMITING.SEE DOCTOR IMMEDIATELY. \*\*\* NOTE TO PHYSICIAN: GASTRIC LAVAGE USING CUFFED ENDOTRACHEAL TUBE MAY BE PERFORMED AT YOUR DISCRETION \*\*\*

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:-35F,-37C

Autoignition Temp:Autoignition Temp Text:833F

Lower Limits:1.4

Upper Limits:7.6

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER STREAM MAY BE

INEFFECTIVE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:VAPORS FORM EXPLOSIVES MIXTURES WITH AIR. VAPORS MAY TRAVEL A LONG DISTANCE TO IGNITION SOURCE AND FLASHBACK. FIRE MAY FORM HAZARDOUS DECOMPOSTION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. REMOVE PERSONNEL.

STAY UPWIND. USE WATER SPRAY TO REDUCE VAPORS. WEAR PROPER PROTECTIVE EQUIPMENT. STOP LEAK. DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL. FOR SMALL SPILL, TAKE UP IN INERT MATERIAL, THEN FLUSH WITH WATER.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED PLACE, AWAY FROM HEAT, IGNITION SOURCES AND INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:AVOID BREATHING VAPORS, AND EYE AND SKIN CONTACT. USE ONLY WITH ADEQUATE VENTILATION. DO NOT SIPHON BY MOUTH. BOND AND GROUND CONTAINERS DURING TRANSFER. EMPTY CONTAINERS MAY CONTAIN TOXIC OR EXPLOSIVE RESIDUE OR VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE APPROPRIATE FOR EXPOSURE OF CONCERN OR SCBA IF TLV IS EXCEEDED.

Ventilation:SUFFICIENT MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST VENTILATION. USE EXPLOSION-PROOF EQUIPMENT.

Protective Gloves:VITON, NITRILE, PVA.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS.

Other Protective Equipment:FULL BODY LONG-SLEEVED GARMENTS TO PREVENT REPEATED OR PROLONGED SKIN CONTACT. EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN. DO NOT BREATHE VAPORS. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING.

Sup

plemental Safety and Health

THESE PRECAUTIONS ARE FOR NORMAL USES AND CONDITIONS. WHERE SPECIAL OR UNUSUAL CONDITIONS EXIST, CONSULT AN INDUSTRIAL HYGIENIST. RCRA CLASSIFICATION IGNITABLE (D001). EP TOXIC (D008).

===== Physical/Chemical Properties =====

HCC:F1

Boiling Pt:B.P. Text:55.0F,12.8C

Vapor Pres:760

Vapor Density:1.2

Spec Gravity:0.73

Evaporation Rate & Reference:>1 (WATER = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR LIQUID WITH A STRONG HYDROCARBON ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON OXIDES, AND VARIOUS HYDROCARBONS WHEN BURNED.

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT YOUR LOCAL ENVIRONMENTAL OFFICER.

MANUFACTURER RECOMMENDS INCINERATION OR TRANSFER TO RCRA PERMITTED WASTE MANAGEMENT FACILITY. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims

all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.