

TEXACO INC. -- 00351 UNLEADED REGULAR GASOLINE -- 9130-00-148-7102

=====
Product Identification
=====

Product ID:00351 UNLEADED REGULAR GASOLINE

MSDS Date:04/09/1987

FSC:9130

NIIN:00-148-7102

MSDS Number: BPBRN

=== Responsible Party ===

Company Name:TEXACO INC.

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Info Phone Num:914-831-3400 EXT 204

Emergency Phone Num:914-831-3400 EXT 204

Prepa

Preparer's Name:R. T. RICHARDS

CAGE:38431

=== Contractor Identification ===

Company Name:DIGITAL CONTROL SYSTEMS INC

Address:3160 GRAND MARAIS E

Box:City:WINDSOR, N8W 4W5

State:ON

Country:CN

Phone:NONE

CAGE:38431

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Phone:914-831-3400

CAGE:7B131

=====
Composition/Information on Ingredients
=====

Ingredient Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 1-3.99%

Other REC Limits:NONE SPECI

FIED
OSHA PEL:1PPM/5STEL;1910.1028
ACGIH TLV:10 PPM; A2; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 4-10.99%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 1-3.99%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9192
EPA Rpt
Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 4-10.99%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III)
CAS:95-63-6
RTECS #:DC3325000
Fraction by Wt: 1-3.99%
Other REC Limits:NONE SPECIFIED
OSHA PEL:25 PPM
ACGIH TLV:25 PPM; 9192

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)
CAS:16

34-04-4
RTECS #:KN5250000
Fraction by Wt: 0-10%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) = 18.75 ML/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE: EYES-CAUSES SLIGHT-MODERATE EYE IRRITATION. SKIN-MODERATELY IRRITATING. CHRONIC: RECENT STUDIES WITH LABORATORY ANIMALS HAVE SHOWN THAT GASOLINE VAPORS CAUSE KIDNEY DAMAGE & KIDNEY CANCER IN RATS & LIVER CANCER IN MICE.
Explanation of Carcinogenicity:PRODUCT CONTAINS BENZENE WHICH IS LISTED AS A CARCINOGEN BY NTP, IARC AND OSHA.
Effects of Overexposure:RESPIRATORY SYSTEM: MAY CAUSE DIZZINESS, IRRITATION OF EYES, NOSE AND THROAT, VOMITING, BLUISH COLOR OF THE SKIN AND CNS EFFECTS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH EXPOSED AREA WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. MAY CAUSE CHEMICAL PNEUMONITIS. CALL A PHYSICIAN. INHALATION: SHOULD REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. (REMOVE GASOLINE-SOAKED CLOTHING)

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:-
40F,-40C
Lower Limits:1.4 %
Upper Limits:7.6 %
Extinguishing Media:DRY CHEMICAL, FOAM, CARBON DIOXIDE.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FLAMES, BUT SHOULD BE USED TO COOL FIRE-EXPOSED CONTAINERS. IF A SPILL OR LEAK HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE VAPORS.
Unusual Fire/Explosion Hazard:FLOWING GASOLINE CAN BE IGNITED BY SELF-GENERATED STATIC ELECTRICITY; USE ADEQUATE GROUNDING. CARBON MONOXIDE & CARBON DIOXIDE MAY BE FORMED ON BURNING IN AIR.

=====

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES INCLUDING INTERNAL COMBUSTION ENGINES AND POWER TOOLS. VENTILATE AREA. AVOID BREATHING VAPORS. USE SCBA OR SUPPLIED-AIR MASK FOR LARGE SPILLS IN CONFINED AREAS. CONTAIN SPILL IF POSSIBLE. REMOVE WITH INERT ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Prec

autions:TRANSPORT, HANDLE AND STORE IN

ACCORDANCE WITH OSHA REGULATION 1910.106 AND APPLICABLE D.O.T. REGULATIONS.

Other Precautions:DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. MAY BE FATAL IF INHALED; MAY CAUSE IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. KEEP AWAY FROM HEAT, SPARKS AND FLAMES. AVOID BR EATHING VAPORS. FOR USE AS MOTOR FUEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SCBA OR SUPPLI
ED AIR RESPIRATORY PROTECTION

REQUIRED FOR ENTRY INTO TANKS, VESSELS, OR OTHER CONFINED SPACES CONTAINING GASOLINE.

Ventilation:ADEQUATE TO MEET PERMISSIBLE CONCENTRATIONS.

Protective Gloves:NITRILE, TEFLON, VITON

Eye Protection:CHEMICAL-TYPE GOGGLES, FACE SHIELD

Other Protective Equipment:PROTECTIVE CLOTHING SUCH AS UNIFORMS, COVERALLS OR LAB COATS SHOULD BE WORN.

Work Hygienic Practices:LAUNDER OR DRY CLEAN WHEN SOILED.

Supplemental Safety and Health

WARNING STATEMENT: DANGER! EXTR
EMELY FLAMMABLE. HARMFUL OR FATAL IF
SWALLOWED.

===== Physical/Chemical Properties =====

HCC:F1

Boiling Pt:B.P. Text:>90F,>32C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Decomp Temp:Decomp Text:N.A.

Vapor Pres:>-350 MMHG

Vapor Density:3 - 4.0

Spec Gravity:0.7 - .78

pH:N.A.

Evaporation Rate & Reference:N.D.

Solubility in Water:SLIGHT

Appearance and Odor:LIGHT STRAW TO LIGHT RED LIQUID

Percent Volatiles by Volume:100 %

Corrosion Rate:N.A.

===== Stabil

ity and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS

Stability Condition to Avoid: HEAT, SPARKS, FLAME AND OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products: TOXIC LEVELS OF CARBON MONOXIDE, CARBON DIOXIDE, IRRITATING ALDEHYDES AND KETONES.

===== Disposal Considerations =====

Waste Disposal Methods: PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume

responsibility for the suitability of this information to their particular situation.