

LUBRICATING SPECIALITIES CO -- A3000,MIL-H-83282C HYD FLUID -- 9150-00-180-6290

===== Product Identification =====

Product ID:A3000,MIL-H-83282C HYD FLUID

MSDS Date:08/22/1990

FSC:9150

NIIN:00-180-6290

MSDS Number: BPBSF

=== Responsible Party ===

Company Name:LUBRICATING SPECIALITIES CO

Address:8015 PARAMOUNT BLVD

City:PICO RIVERA

State:CA

ZIP:90660-4888

Country:US

Info Phone Num:213-928-3311

Eme

Agency Phone Num:213-928-3311

Preparer's Name:RICHARD J.EBERHARDT

CAGE:2X769

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

Company Name:TECHNOLUBE PRODUCT COMPANY

Address:8015 PARAMOUNT BLVD.

Box:City:PICO RIVERA

State:CA

ZIP:90660-4811

Country:US

Phone:562 776-4000 GEN: 562-776-4000

CAGE:2X769

===== Composit

ion/Information on Ingredients =====

Ingred Name:SYNTHETIC HYDROCARBON BASE

CAS:68649-12-7

Fraction by Wt: 200C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:SLIGHTLY COMBUSTIBLE. WHEN HEATED ABOVE FLASH POINT RELEASES FLAMMABLE VAPORS WHICH CAN BURN IN OPEN OR BE EXPLOSIVE IN CONFINED SPACES IF EXPOSED TO IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. WIPE OR MOP UP OR ABSORB WITH DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE IN APROPRIATE CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORGE NEAR OPEN FLAMME OR OTHER

SOURCES OF IGNITION. EXCESSIVE MISTING WAY CAUSE SLIPPERY FLOORS. PROPER FOOTWEAR REQUIRED.

Other Precautions:DISCARD CONTAMINATED LEATHER GLOVES AND SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED WITH ADEQUATE VEMTILATION.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipmen

t:EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>599F,>315C

Vapor Pres:1.

Spec Gravity:0.853

Evaporation Rate & Reference: