

APEX OIL CO -- NO.6 FUEL OIL -- 9140-00-247-4354

=====  
Product Identification  
=====

Product ID:NO.6 FUEL OIL  
MSDS Date:01/01/1987  
FSC:9140  
NIIN:00-247-4354  
MSDS Number: BPBSX  
=== Responsible Party ===  
Company Name:APEX OIL CO  
Address:8182 MARYLAND AVE  
City:ST. LOUIS  
State:MO  
ZIP:63105-3506  
Country:US  
Info Phone Num:314-889-9600  
Emergency Phone Num:314-889-9600 OR 800-424-9300  
CAGE:8P125  
=== Contr  
actor Identification ===  
Company Name:APEX OIL CO  
Address:8182 MARYLAND AVE  
Box:City:ST. LOUIS  
State:MO  
ZIP:63105-3506  
Country:US  
Phone:800-424-9300/314-889-9600  
CAGE:8P125

=====  
Composition/Information on Ingredients  
=====

Ingred Name:FUEL OIL  
Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 4700 MG/KG  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicit

y:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MIST OR VAPOR MAY CAUSE RESPIRATORY TRACT IRRITATION. CNS DEPRESSANT. INGESTION MAY CAUSE IRRITATION, CNS DEPRESSION, COMA AND DEATH. SKIN CONTACT MAY CAUSE DRYING, CRACKING, DEFATTING DERMATITIS, & IRRITATION WITH SEVERE ERYTHEMA & EDEMA.ABSORPTION OF LARGE AMOUNTS MAY RESULT IN NARCOSIS. MAY CAUSE EYE IRRITATION.

Explanation of Carcinogenicity:NONE OF THE INGREDIENTS ARE LISTED AS CARCINOGENS BY IARC, NTP, OR OSHA. AMES TESTS DID NOT INDICATE MUTAGENIC ACTIVITY.

Effects of Overexposure:GIDDINESS, NERVOUSNESS, HEADACHE, DIZZINESS, WEAKNESS, WEIGHT LOSS, ANEMIA, NUMBNESS, PARALYSIS, NAUSEA, VOMITING, INCOORDINATION, NARCOSIS, STUPOR, COMA, UNCONSCIOUSNESS, DEATH. PROLONGED OR REPEATED EXPOSURE TO HIGH CONCENTRATIONS MAY CAUSE DEGENERATIVE CHANGES TO LIVER AND KIDNEYS WITH POSSIBLE RENAL FAILURE.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASE IN O

R A HISTORY OF AILMENTS INVOLVING THE LIVER, KIDNEY, SKIN, CNS, OR REPRODUCTIVE SYSTEM ARE AT A GREATER THAN NORMAL RISK WHEN EXPOSED TO THIS MATERIAL.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MINUTES WHILE LIFTING EYELIDS. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS. GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:150F,66C

Autoignition Temp:Autoignition Temp Text:765F

Extinguishing Media:DRY CHEMICAL, FOAM, CARBON DIOXIDE. DO NOT USE WATER ON FIRE SINCE IT MAY CAUSE VIOLENT ERUPTION AND SPREAD OIL.

Fire Fighting Procedures:USE SUPPLIED-

AIR BREATHING EQUIPMENT FOR

ENCLOSED AREAS. COOL EXPOSED CONTAINERS WITH WATER SPRAY. CONTINUE WATER SPRAY UNTIL ENTIRE CONTAINER CONTENTS ARE COOL

Unusual Fire/Explosion Hazard:DO NOT STORE NEAR STRONG OXIDANTS. KEEP AWAY FROM SOURCES OF IGNITION. "EMPTY" CONTAINERS MAY CONTAIN FLAMMABLE OR EXPLOSIVE VAPORS WHICH ARE HEAVIER THAN AIR.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA

EA. STOP SPILL AT SOURCE. SMALL SPILL - REMOVE LIQUID BY OIL-ABSORBING MATERIALS. LARGE SPILL - EXCLUDE PERSONS NOT WEARING PROTECTIVE EQUIPMENT, DIKE AREA OF SPILL AND PUMP LIQUID INTO SALVAGE TANK.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE INHALATION OR SKIN CONTACT. ISOLATE FROM SOURCES OF IGNITION. PROHIBIT EATING, DRINKING AND SMOKING IN AREA OF ASPHALT USE.

Other Precau

tions:DO NOT PRESSURIZE, CUT, HEAT, WELD, OR EXPOSE "EMPTY" CONTAINERS TO SOURCES OF IGNITION. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE IS RECOMMENDED. USE POSITIVE PRESSURE AIR-SUPPLIED OR SCBA IN THE EVENT OF A LARGE SPILL.

Ventilation:INDOORS, USE LAB HOOD, OUTDOORS, WORK UPWIND. MECHANICAL VENTILATION IS RECOMMENDED FOR USE IN ENCLOSED WORK AREAS.

Protective Gloves:NEOPRENE OR PVC GLOVES

Eye Protection:SPLASH GOGGLES/SAFETY GLASSES W/SHIELDS

Other Protective Equipment:APPROPRIATE IMPERVIOUS CLOTHING AND EQUIPMENT TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WITH THIS SUBSTANCE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplementa

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:>400F,>204C

Spec Gravity:0.94-1.0

Viscosity:638 MAX @122F

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER TO BRONZE COLORED LIQUID, HEAVY AROMATIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:MAY BE IGNITED BY HEAT, SPARKS OR FLAME

VAPORS MAY TRAVEL TO SOURCE OF IGNITION AND FLASH BACK; VAPOR  
EXPLOSION HAZARD.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY RELEASE  
HYDROCARBONS & HYDROCARBON DERIVATIVES (CARBON DIOXIDE, ORGANIC  
ACIDS & ALDEHYDES).

===== Disposal Considerations =====

Waste Disposal Methods:UNDER EPA RCRA, IF THIS PRODUCT BECOMES A WASTE  
MATERIAL INTENDED FOR DISPOSAL AND HAS A FLASH POINT BELOW 140F, IT  
WOULD BE IGNITABLE HAZARDOUS WASTE  
(CODE D001). REFER TO LATEST EPA  
OR STATE REGULATIONS REGARDING PROPER DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
as  
sume responsibility for the suitability of this information to their  
particular situation.