

MONTANA REFINING CO -- FUEL OIL #1 -- 9140-00-286-5288

=====
Product Identification
=====

Product ID:FUEL OIL #1

MSDS Date:06/27/1991

FSC:9140

NIIN:00-286-5288

MSDS Number: BPBWH

=== Responsible Party ===

Company Name:MONTANA REFINING CO

Address:1900 10TH STREET

City:GREAT FALLS

State:MT

ZIP:59414-1099

Country:US

Info Phone Num:406-761-4100

Emergency Phone Num:406-761-4100/800-424-9300(CHEMTREC)

CAGE:6E335

=== Contractor Identification ===

Company Name:MONTANA REFINING CO

Address:1900 10TH ST

Box:City:GREAT FALLS

State:MT

ZIP:59414-1099

Country:US

Phone:406-761-4100/800-424-9300(CHEMTREC)

CAGE:6E335

=====
Composition/Information on Ingredients
=====

Ingred Name:KEROSENE (CONTAINING HYDROCARBON PETROLEUM DISTILLATES)

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: UNK

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM 9091

Ingred Name:BENZENE (SARA I

II); >100 PPM (TRACE LEVELS) BENZENE PER
API WASH AND MAJOR FORMULATORS. BUT NOT LISTED IN THE MSDS'S
CAS:71-43-2
RTECS #:CY1400000
Fraction by Wt: 0.01%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1PPM/5STEL;1910.1028
ACGIH TLV:10 PPM; A2; 9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:NAPHTHALENE (SARA III)
CAS:91-20-3
RTECS #:QJ0525000
Fraction by Wt: UNKNOW
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15 STEL; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LB
S

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: PRODUCT IS MILDLY IRRITATING TO
SKIN. ON INHALATION, IT MAY PRODUCE CENTRAL NERVOUS SYSTEM
DEPRESSION, NARCOSIS. GREATER EXPOSURE MAY CAUSE DIZZINESS, SLURRED
SPEECH, FLUSHED FACE, UNCONSCIOUSNESS OR CONVULSIONS.
CHRONIC:DERMATITIS,PNEUMONITIS, PULMONARY EDEMA
AND KIDNEY DAMAGE.
Explanation of Carcinogenicity:THE PRODUCT ITSELF HAS NOT SHOWN ANY
EVIDENCE OF BEING CARCINOGENIC. BUT SAMPLES ANALYSIS REVEALED
BENZENE >100PPM.
Effects of Overexposure:EYE:HIGH CONCENTRATION OF VAPORS CAUSE
IRRITATION; SKIN: MAY CAUSE MILD IRRITATION, POSSIBLE DERMATITIS
WITH PROLONGED AND/OR REPEATED CONTACT. INHALATION: RESPIRATORY
TRACT IRRITATION, NAUSEA, DIZZINESS, HEADACHE,CONFUSION,BLURRED
VISION. INGESTED: GASTROINTESTINAL IRRITATION, NA

USEA,
VOMITING.ASPIRATION HAZARD!
Medical Cond Aggravated by Exposure:PEOPLE WITH A SKIN DISORDER OR
IMPAIRED PULMONARY FUNCTION SHOULD USE EXTRA CAUTION WHEN HANDLING
OR USING THIS PRODUCT.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP
& WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE.
INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY.
INGESTED:DO NOT I
NDUCE VOMITING. GIVE 2 LARGE GLASSES OF MILK OR
WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY MOUTH IF
UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE, SEE A DOCTOR.

===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:>110F,>43C
Lower Limits:0.7%
Upper Limits:5.0%
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, HALON.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SCBA. EVACU
ATE AREA. USE WATER SPRAY TO COOL FIRE
EXPOSED CONTAINERS COOL, FLUSH SPILL/VAPORS AWAY.
Unusual Fire/Explosion Hazard:NONE GIVEN BY MANUFACTURER (SUPPLIER).
HMIS:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION
PRODUCTS AND VAPORS.VAPORS MAY FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. MINOR: ABSORB
MATERIAL WITH CLAY, VERMICULITE, OR SIMILAR ABSORBENT MATERIAL.
PLACE IN
DISPOSAL CONTAINERS. MAJOR: DIKE & CONTAIN SPILL. SHUT OFF
LEAKS. REMOVE LIQUID BY VACUUM OR ABSORBENT. AVOID WASHING TO
STORM SEWER

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, VENTILATED LOW FIRE
RISK AREA. DETACHED STORAGE IS PREFERABLE.
Other Precautions:'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR.
TREAT THEM WITH THE RESPECT DUE FULL ONES. DO NOT CUT,WELD,ETC. ON
THEM. GROUND CONTAINERS BEFO

RE TRANSFERRING LIQUID. AVOID HAVING
OPEN ELECTRICAL EQUIPMENT IN VAPOR AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE
NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR RESPIRATOR FOR
ORGANIC VAPOR IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134
FOR REGULATIONS PERTAINING TO RESPIRATOR USE.

Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED.

Protective Gloves:NEOPRENE, NITRI
LE, OR PVC

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER. WEAR
IMPERVIOUS CLOTHING WHEN SPLASHING IS LIKELY.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICES. AVOID
PROLONGED/REPEATED CONTACT. DO NOT EAT, DRINK OR SMOKE IN WORK
AREA.

Supplemental Safety and Health

PER API, WASHINGTON, DC AND FEW OF MAJOR FORMULATORS, DIESEL FUELS WERE
FOUND TO HAVE TRACE LEVELS OF BENZENE. TYPICAL SAMPLE ANALYSIS

SHOWED 100 TO 250 PPM OF BENZENE.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:5 MMHG @100

Vapor Density:4.5

Spec Gravity:0.8

Evaporation Rate & Reference:NIL

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR TO YELLOW LIQUID WITH CHARACTERISTIC
HYDROCARBON SMELL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stabil

ity Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
OTHER PETROLEUM COMBUSTION PRODUCTS. MAY EMIT SULFUR DIOXIDE
DEPENDING ON SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL
REGULATIONS. MANUFACTURER MAKES NO SUGGESTIONS AS TO METHOD OF
DISPOSAL. HMIS SUGGESTS INCINERATION MAY BE THE BEST D
ISPOSAL
METHOD. RCRA HAZ WASTE #S D001, D018 (BECAUSE OF BENZENE IN DIESEL
FUELS).RECYCLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to v
erify and
assume responsibility for the suitability of this information to their
particular situation.