

HARRIS J W CO INC -- BARE ROD OR WIRE 5356 -- 3439-00-803-9498

=====  
Product Identification  
=====

Product ID:BARE ROD OR WIRE 5356

MSDS Date:06/01/1990

FSC:3439

NIIN:00-803-9498

MSDS Number: BPBY

=== Responsible Party ===

Company Name:HARRIS J W CO INC

Address:10930 DEERFIELD RD.

City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Info Phone Num:513-891-2000

Emergency Phone Num:800-424-9300

CAGE:

JO820

=== Contractor Identification ===

Company Name:J. W. HARRIS CO., INC

Address:10930 DEERFIELD RD

Box:City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Phone:513-891-2000

CAGE:JO820

Company Name:J. W. HARRIS CO., INC.

Address:10930 DEERFIELD ROAD

Box:City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Phone:513-891-2000

CAGE:27911

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SILICON

CAS:7440-21-3

RTECS #:VW0400000

Fraction by Wt: 0.25%

Other REC Limits:N

ONE RECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:IRON  
CAS:7439-89-6  
RTECS #:NO7400000  
Fraction by Wt: 0.40%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 MG/M3 (FE)  
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:COPPER (SARA III)  
CAS:7440-50-8  
RTECS #:GL5325000  
Fraction by Wt: 0.10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.1MG/M3 FUME/1 DUST  
ACGIH TLV:0.2MG/M3 FUME; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:MANGANESE (SARA III)  
CAS:7439-96-  
5  
RTECS #:OO9275000  
Fraction by Wt: .05-.20%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:(C) 5 MG/M3 DUST  
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:MAGNESIUM  
CAS:7439-95-4  
RTECS #:OM3850000  
Fraction by Wt: 4.5-5.5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10MG/M3 RESPIRABLE  
ACGIH TLV:10 MG/M3; FUME; 9293

Ingred Name:CHROMIUM (SARA III)  
CAS:7440-47-3  
RTECS #:GB4200000  
Fraction by Wt: .05-.20%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:0.5 MG/M3; 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Q

ty:1 LB

Ingred Name:ZINC OXIDE (DUST) (SARA III)  
CAS:1314-13-2  
RTECS #:ZG8600000  
Fraction by Wt: 0.10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15MG/M3 TDUST/5 FUME  
ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:TITANIUM  
CAS:7440-32-6  
RTECS #:XR2275000  
Fraction by Wt: .06-.20%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ALUMINUM (SARA III)  
CAS:7429-90-5  
RTECS #:BD0330000  
Fraction by Wt: REM.  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15MG  
/M3 DUST/5 FUME  
ACGIH TLV:10MG/M3 DUST; 9293

===== Hazards Identification =====

LD50 LC50 Mixture:UNCLASSIFIED WELDING FUMES=5MG/M3 PEL  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:CHROMIUM: MAY CAUSE LUNG CHANGES. IT  
SHOULD BE CONSIDERED A POSSIBLE CARCINOGEN. COPPER FUME MAY CAUSE  
METAL FUME FEVER WHICH INCLUDE FEVER, BODY ACHE, CHILLS. IRON: MAY  
CAUSE X-RAY CHANGES OF THE LUN GS. MANGANESE: MAY CAUSE METAL FUME  
FEVER, AFFECT THE NERVOUS SYSTEM & RESPIRATORY SYSTEM DISEASE.  
Explanation of Carcinogenicity:CHROMIUM ALLOYS, AND CHROMIUM HAVE BEEN  
IDENTIFIED BY IARC AND/OR NTP AS POTENTIAL CANCER CAUSING AGENTS.  
Effects of Overexposure:EXPOSURE TO WELDING FUMES MAY CAUSE METAL FUME  
FEVER WITH SYMPTOMS OF CHILLS, FEVER, NAUSEA, COUGH, DRY THROAT,  
WEAKNESS, MUSCLE ACHES, AND A SWEET OR METALLIC TASTE IN THE MOUTH.  
PROLONGED

OR REPEATED EXPOSURE MAY CAUSE DIFFICULTY IN WALKING, WEAKNESS OR CRAMPS IN THE LEGS, HOARSENESS, MEMORY LOSS, SKIN SENSITIZATION.

Medical Condition Aggravated by Exposure: INDIVIDUALS WITH IMPAIRED PULMONARY FUNCTIONS OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY FUME IRRITANTS.

=====  
===== First Aid Measures =====

First Aid: INHALATION: REMOVE TO FRESH AIR. CONSULT A PHYSICIAN. EYE: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET

MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INGESTION: WHILE INGESTION OF LARGE ENOUGH QUANTITIES TO CAUSE HEALTH EFFECTS IS UNLIKELY, CONSULT A PHYSICIAN IF IT OCCURS.

=====  
===== Fire Fighting Measures =====

Flash Point: NON-FLAMMABLE

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL AS NEEDED FOR SURROUNDING FIRE. THIS PRODUCT IS NON-FLAMMABLE.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A

FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. WELDING ARC, OPEN FLAME AND SPARKS CAN IGNITE COMBUSTIBLES.

=====  
===== Accidental Release Measures =====

Spill Release Procedures: CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN

ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSURE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Other Precautions: PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED

GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATORS FOR PROTECTION AGAINST AIRBORNE DUST OR FUMES. RESPIRATORS SHOULD BE USED IN ACCORDANCE WITH 29CFR 1910.134.

Ventilation:USE LOCAL AND GENERAL VENTILATION TO KEEP AIRBORNE CONCENTRATIONS OF DUST OR FUMES BELOW THE TLV DURING USE.

Protective Gloves:WELDERS LEATHER GLOVES

Eye Protection:OSHA APPROVED GOGGLES/FACE SHIELD W/LENS

Other Protective Equipment:BARRIER CREAMS MAY BE NECESSARY TO PREVENT SKIN SENSITIZATION AND DERMATITIS.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THE PRESENCE OF CONTAMINANTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:NONE STATED

Appearance and Odor:SOLID WIRE OR ROD

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:WELDING AND BRAZING FUMES MAY INCLUDE OXIDES OF THE METALS, CHROMATES, FLUORIDES, COMPLEX METALLICS, AND OZONE.

===== Disposal Considerations =====

Waste Disposal Methods:RECYCLE OR DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.