View NSN Online: https://aerobasegroup.com/nsn/6850-00-963-5402

GENERAL ELECTRIC CO SILICONE PRODUCT DIV. -- G635 SILICONE GREASE COMPOUND --

6850-00-963-5402

============= Product Identification =================

Product ID:G635 SILICONE GREASE COMPOUND

MSDS Date: 10/22/1992

FSC:6850

NIIN:00-963-5402

MSDS Number: BPBZY === Responsible Party ===

Company Name: GENERAL ELECTRIC CO SILICONE PRODUCT DIV.

Address: HUDSON RIVER ROAD

City:WATERFORD

State:NY ZIP:12188 Country:US Info Phone

Num:518-237-3330

Emergency Phone Num:518-237-3330 Preparer's Name:DA POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name: GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address: 260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY ZIP:12188 Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

Company Name: THE SMITH GROUP INC.

Address:811 E. CAYUGA STREET

Box:City:PHILADELPHIA

State:PA

ZIP:19124-3893 Country:US

Phone:215-743-8200

CAGE:2B613

====== Composition/Informatio

n on Ingredients ========
Ingred Name:POLYDIMETHYLPHENYLSILOXANE CAS:63148-62-9 Fraction by Wt: 80-99%
Other REC Limits:NONE RECOMMENDED
Ingred Name:FUMED SILICA CAS:112945-52-5
Fraction by Wt: 10-30% Other REC Limits:NONE RECOMMENDED OSHA PEL:6MG/M3 ACGIH TLV:10MG/M3
======================================
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-INGESTION:NO ILL EFFECTS EXPECTED. EYE:IRRITATION. SKIN: NOT NORMALLY EXPECTED TO CAUSE ILL EFFECTS. CHRONIC-PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION, DERMATITIS. Effects of Overexposure:MILD EYE IRRITATION Medical Cond Aggravated by Exposure:NONE KNOWN.
======================================
First Aid:EYE:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MIN.GET MEDICAL ATTENTION IF IRRITATION PERSISTS;SKIN:WASH WITH SOAP & WATER;INHALATION:REMOVE TO FRESH AIR;INGESTION:DO NOT INDUCE VOMIT.
GIVE LARGE Q UANTITIES OF WATER & GET MEDICAL ATTENTION.NOTHING BY MOUTH IF UNCONSCIOUS.
======================================
Flash Point Method:COC Flash Point:>500F,>260C Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA,CO2. Fire Fighting Procedures:NONE NOTED.USE NIOSH/MSHA APPROVED SCBA WITH FULL PROTECTION Unusual Fire/Explosion Hazard:NONE NOTED
=========== Accidental Release Measures ===========
Spill Release Procedures:USE PR

OPER PERSONAL PROTECTION; USE INERT ABSORBANT MATERIAL AND PUT IN A CONTAINER FOR PROPER DISPOSAL.
=========== Handling and Storage ==============
Handling and Storage Precautions:STORE IN COOLD DRY AND VENTILATED AREA. KEEP CONTAINER AWAY FROM HEAT AND OPEN FLAMES. Other Precautions:AVOID CONTACT WITH SKIN AND EYES:WASH THOROUGHLY AFTER EACH USE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NO SPECIAL REQMNTS UNDE R ORDINARY CONDITIONS/ ADEQUATE VENT. Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION Work Hygienic Practices:STANDARD HYGIENIC PRACTICES. Supplemental Safety and Health
======== Physical/Chemical Properties ==========
HCC:V7 Vapor Pres:NEG Vapor Density:NEG Spec Gravity:1.045 Evaporation Rate & amp ; Reference: