

EVEREADY BATTERY CO INC -- EVEREADY BATTERY (ENERGIZER, ALKALINE) -- 6135-00-990-1822

=====
Product Identification
=====

Product ID:EVEREADY BATTERY (ENERGIZER, ALKALINE)

MSDS Date:01/03/1989

FSC:6135

NIIN:00-990-1822

MSDS Number: BPCBG

=== Responsible Party ===

Company Name:EVEREADY BATTERY CO INC

Address:CHECKERBOARD SQ

City:ST LOUIS

State:MO

ZIP:63164

Country:US

Info Phone Num:216-835-7368

Eme

Agency Phone Num:417-625-3333, 1-800-526-4727

CAGE:83740

=== Contractor Identification ===

Company Name:EVEREADY BATTERY CO INC

Address:CHECKERBOARD SQ

Box:City:ST LOUIS

State:MO

ZIP:63164

Country:US

Phone:216-835-7368

CAGE:83740

=====
Composition/Information on Ingredients
=====

Ingred Name:POTASSIUM HYDROXIDE

CAS:1310-58-3

RTECS #:TT2100000

Fraction by Wt: 3-10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:C, 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9091

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:10

00 LBS

Ingred Name:MERCURY

CAS:7439-97-6

RTECS #:OV4550000

Fraction by Wt: 0.1-0.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, C, 0.1 MG/M3

ACGIH TLV:S, 0.05 MG/M3; 9091

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ZINC (SARA III)

CAS:7440-66-6

RTECS #:ZG8600000

Fraction by Wt: 5-22%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG ZNO/M3

ACGIH TLV:10 MG ZNO/M3; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:MANGANESE DIOXIDE

CAS:1313-13-9

RTECS #:OP0350000

Fraction by Wt: 18050%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG MN/M3 CEILING

ACGIH TLV:5 MG MN/M3

Ingred Name:GRAPHITE, NATURAL

CAS:7782-42-5

RTECS #:MD9659600

Fraction by Wt: 1-8%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MPPCF RDUST

ACGIH TLV:2 MG/M3 RDUST; 9293

==== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPOSURE TO

MERCURY-ACUTE-SKIN:I

IRRITATION, ANURIA. EYE:IRRITATION, CORNEAL INJURY OR BURNS. INGESTION:IMMEDIATE NECROSIS IN MOUTH, THROAT, ESOPHAGUS & STOMACH. DEATH MAY OCCURE. INHALATION:DYSPNEA, COUGH, FEVER, NAUSEA & VOMITING, DIARRHEA, STOMATITIS, SALIVATION & METALLIC TASTE. CHRONIC: CNS DISTURBANCES.

Explanation of Carcinogenicity:MERCURY, ZINC AND MANGANESE ARE NOT LISTED BY IARC, NTP, OR OSHA AS CARCINOGENS.

Effects of Overexposure:TREMORS, CONVULSIONS & OTHER CNS DISTURBANCES, PNEUMONITIS, CH

EST PAINS, DYSPNEA, COUGHING, STOMATITIS, GINGIVITIS AND LOOSENING OF TEETH, SALIVATION, LOSS OF MEMORY, METALLIC TASTE, DIZZINESS, CLUMSI NESS, SLURRED SPEECH, DIARRHEA, PAIN & NUMBNESS IN EXTREMITIES, NEPHRITIS, ANXIETY, HEADACHE, WEIGHT LOSS, AND INSOMNIA.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF ALCOHOLISM, CHRONIC KIDNEY DISEASE OR KNOWN ALLERGY TO MERCURY MAY BE AT INCREASED RISK FROM EXPOSURE TO MERCURY IF THE BATTERY IS RUPTURED.

=====

===== First Aid Measures =====

First Aid:IF EXPOSED TO RUPTURED BATTERY-INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING GIVE CPR/OXYGEN. GET MEDICAL ATTENTION. EYE:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN:WASH SKIN WITH PLENTY OF SOAP & WATER. INGESTION:GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE , FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS OF MERCURY. CELL MAY EXPLODE IN FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:PICK UP ALL BATTERIES. FOR A

SMALL SPILL OF A

RUPTURED BATTERY: COLLECT THE DUST WITH A VACUUM CLEANER AND SAVE FOR DISPOSAL. WASH THE AREA.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM HEAT. STACK CARTONS NO MORE THAN 4 LAYERS HIGH ON A PALLET AND NO MORE THAN 3 PALLETS HIGH.

Other Precautions:DO NOT SEAL BATTERIES IN AIR TIGHT OR WATERTIGHT CONTAINERS OR COMPARTMENTS. DO NOT RUPTURE OR THROW BATTERIES IN FIRE. DO NOT RECHARGE BATTERIES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED. WEAR MASK WHEN HANDLING DUST FROM RUPTURED BATTERY.

Ventilation:GENERAL/LOCAL EXHAUST VENTILATION WHEN HANDLING RUPTURED BATTERIES.

Protective Gloves:RUBBER, IF HANDLING RUPTURED BATTERY.

Eye Protection:NONE

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES.

Supplemental Safety and Health

THIS PRODUCT IS AN "ARTICLE". THERE ARE NO HEALTH HAZARDS IN HANDLING BATTERIES UNLESS THE BATTERIES ARE RUPTURED. WHEN HANDLING RUPTURED BATTERY DO NOT GET ON SKIN, IN EYES OR ON CLOTHING. DO NOT BREATHE THE VAPORS.

===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:CYLINDRICAL BATTERY

===== Stability and Reactivity Data =====

Stability Ind

icator/Materials to Avoid: YES

STRONG ACIDS AND BASES

Stability Condition to Avoid: HIGH TEMPERATURES

Hazardous Decomposition Products: THERMAL DECOMPOSITION PRODUCTS INCLUDE TOXIC MERCURY VAPORS, MOLTEN AND BURNING FUMES.

===== Disposal Considerations =====

Waste Disposal Methods: DO NOT INCINERATE, BURY IN LANDFILL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):

This informat

ion is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.