

ANITEC IMAGE CORP -- REPROLITH 220 DEV/REP, PART B -- 6750-01-197-7895

=====  
Product Identification  
=====

Product ID:REPROLITH 220 DEV/REP, PART B

MSDS Date:01/01/1991

FSC:6750

NIIN:01-197-7895

MSDS Number: BPCCY

=== Responsible Party ===

Company Name:ANITEC IMAGE CORP

Address:40 CHARLES ST

Box:4444

City:BINGHAMTON

State:NY

ZIP:13902

Country:US

Info Phone Num:800-234-7707

Emergency Phone Num:800-424-9300(CHEMTREC)/800-424-9300

CAGE:61263

=== Contractor Identification ===

Company Name:ANITEC IMAGE CORP

Address:40 CHARLES ST

Box:4444

City:BINGHAMTON

State:NY

ZIP:13902

Country:US

Phone:607-774-3333

CAGE:61263

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POTASSIUM CARBONATE

CAS:584-08-7

RTECS #:TS7750000

Fraction by Wt: 10-20%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM CARBONATE

CAS:497-19-8

RTECS #:VZ4050000

Fraction by Wt: 1-5%

Other REC Li

imits:NONE RECOMMENDED

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT2100000

Fraction by Wt: 0.1-1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C, 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM SULFITE

CAS:7757-83-7

RTECS #:WE2150000

Fraction by Wt: >5%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carci

nogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CAUSTIC SOLUTION MAY BE CORROSIVE TO SKIN OR EYES.

Effects of Overexposure:SKIN WILL FEEL SLIPPERY OR SOAPY TO TOUCH.

Medical Cond Aggravated by Exposure:SKIN RASHES OE ALLERGIES, OPEN WOUNDS.

===== First Aid Measures =====

First Aid:WASH EXPOSED SKIN OR EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CALL APHYSICIAN IF IRRITATION PERSISTS.

===== Fire Fi  
ghting Measures =====

Flash Point:NA

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:WATER, MIST, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:AVOID BREATHING COMBUSTION FUMES.

Unusual Fire/Explosion Hazard:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL AND NEUTRALIZE WITH DILUTE ACID. ABSORB INTO INERT MATERIALS SUCH AS VERMICULITE, OR FLUSH TO CHEMICAL SEWER OR WA



Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.