

ANSUL FIRE PROTECTION,WORMALD U.S.INC. -- HALON 1301, FREON FE 1301 -- 8120-01-257-4591
===== Product Identification =====

Product ID:HALON 1301, FREON FE 1301
MSDS Date:01/15/1991
FSC:8120
NIIN:01-257-4591
MSDS Number: BPCDY
=== Responsible Party ===
Company Name:ANSUL FIRE PROTECTION,WORMALD U.S.INC.
Address:ONE STANTON STREET
City:MARINETTE
State:WI
ZIP:54143-2542
Country:US
Info Phone Num:715
-735-7411
Emergency Phone Num:715-735-7411 800-424-9300 CHEMTRA
CAGE:03670
=== Contractor Identification ===
Company Name:ANSUL INC
Address:ONE STANTON STREET
Box:City:MARINETTE
State:WI
ZIP:54143-2542
Country:US
Phone:715-735-7411
CAGE:03670

===== Composition/Information on Ingredients =====

Ingred Name:TRIFLUOROBROMOMETHANE (HALON 1301) (SARA III)
CAS:75-63-8
RTECS #:PA5425000
Fraction by Wt: 99.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM;

9293

Ozone Depleting Chemical:1

Ingred Name:OTHER INGREDIENTS

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LC50 INH RAT >800,000 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: VAPOR IS HEAVIER THAN AIR
AND CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE FOR
BREATHING. BREATHING HIGH CONCENTRATIONS

OF VAPOR MAY CAUSE

LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, AND MAY LEAD TO
NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR DEATH.

SKIN/EYE: LIQUID CAN DEFAT TISSUE.

Explanation of Carcinogenicity:THIS COMPOUND IS NOT LISTED AS A
CARCINOGEN BY IARC, NTP OR OSHA.

Effects of Overexposure:BREATHING HIGH CONCENTRATIONS OF VAPOR MAY
CAUSE LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, AND MAY
LEAD TO NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR DEATH

Medical Cond Aggravated by Exposure:IN SUSCEPTIBLE INDIVIDUALS, CARDIAC
SENSITIZATION TO CIRCULATING EPINEPHRINE COMPOUNDS CAN RESULT IN
POTENTIALLY FATAL HEART ARRHYTHMIAS.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR, CALL A PHYSICIAN. IF NOT
BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT,
GIVE OXYGEN. DO NOT GIVE EPINEPHRINE OR SIMILAR DRUGS. EYE: FLUSH
WITH WATER . SKIN: FLUSH WITH WATER

IF IRRITATION PERSISTS, GET
MEDICAL ATTENTION. ORAL: GET MEDICAL ATTENTION IMMEDIATELY. DO NOT
INDUCE VOMITING AS THE HAZARD OF ASPIRATING INTO THE LUNGS IS TOO
GREAT.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE WATER TO COOL FIRE EXPOSED CYLINDERS.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER

PRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE ENCLOSED AREAS IN CASE OF
INADVERTENT OR DELIBERATE DISCHARGE OF HALON

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN, COOL, DRY AND
WELL-VENTILATED AREA OF LOW FIRE
RISK. PROTECT CONTAINERS FROM
PHYSICAL DAMAGE AND KEEP CLOSED.

Other Precautions:AVOID BREATHING VAPOR, LIQUID CONTACT WITH EYES, SKIN
OR CLOTHING. TANK-CLEANING PERSONNEL SHOULD USE ONLY FORMAL TANK
ENTRY PROCEDURE BASED ON RECOGNIZED SAFETY PRINCIPLES. EMPTY
CONTAINERS MAY CONTAIN PRODUCT RESIDUES/VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED FOR ADEQUATELY VENTED WORK
SITUATIONS. FOR ACCIDENTAL OR NON-VE
NTILATED SITUATIONS, USE A
SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR RESPIRATOR,
APPROVED BY NIOSH.

Ventilation:PROVIDE LOCAL EXHAUST AT FILLING ZONES AND OTHER OPERATING
SPACES WHERE LEAKAGE IS PROBABLE. MECHANICAL FOR OTHER.

Protective Gloves:PLASTIC

Eye Protection:CHEMICAL GOGGLES; EYE WASH AND SHOWER

Other Protective Equipment:USE IMPERVIOUS CLOTHING IF THERE IS REPEATED
OR PROLONGED CONTACT WITH LIQUID.

Work Hygienic Practices:REMOVE AND WASH CLOTHING PROMPTLY UPON
CONTAMINATION. USE ORDINARY GOOD HYGIENE AND GOOD HOUSEKEEPING.

Supplemental Safety and Health
AVOID DIRECT CONTACT.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-72F,-58C

Vapor Pres:199.0 PSI

Vapor Density:5.2

Spec Gravity:1.57

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLOR GAS, SWEET ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid

:YES

ACTIVE METALS AND FIRES INVOLVING METAL HYDRIDES

Stability Condition to Avoid:HIGH HEAT, DO NOT HEAT ABOVE 900 F

Hazardous Decomposition Products:DECOMPOSED BY HIGH TEMPERATURES (OPEN FLAMES, GLOWING METAL SURFACES, ETC.) FORMING HYDROBROMIC AND HYDROFLUORIC ACIDS

===== Disposal Considerations =====

Waste Disposal Methods:COMPLY WITH FEDERAL, STATE AND LOCAL REGULATIONS. REMOVE TO A PERMITTED WASTE DISPOSAL FACILITY. MATERIAL USUALLY DISPERSES IN THE ATMOSPHERE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.