View NSN Online: https://aerobasegroup.com/nsn/9140-00-242-6749

CHEVRON ENVIRONMENTAL HEALTH CENTER INC. -- HEATING FUEL NO 1 -- 9140-00-242-6749

Product ID:HEATING FUEL NO 1 MSDS Date:01/03/1992 FSC:9140 NIIN:00-242-6749 **MSDS Number: BPFRZ** === Responsible Party === Company Name: CHEVRON ENVIRONMENTAL HEALTH CENTER INC. Address:15299 SAN PABLO AVE. Box:4054 City:RICHMOND State:CA ZIP:94804 Country:US Info Phone Num:415-233-37 37 OR 800-582-3835 Emergency Phone Num:415-233-3737 OR 800-457-2022 CAGE:0AHD1 === Contractor Identification === Company Name: CHEVRON ENVIRONMENTAL HEALTH CENTER INC Address:15299 SAN PABLO AVE Box:4054 City:RICHMOND State:CA ZIP:94804 Country:US Phone:800-582-3835 CAGE:0AHD1

Ingred Name:ALIPHATIC PETROLEUM SOLVENT/KEROSENE CAS:8008-20-6 RTECS #:OA5500000 Other REC Limits:NONE RECOMMENDED

Ingred Name:KEROSENE/KEROSENE HYDROD

ESULFURIZED CAS:64742-81-0 Other REC Limits:NONE RECOMMENDED

Ingred Name:DISTILLATES, HYDROSULFURIZED MIDDLE CAS:64742-80-9 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:DISTILLATES,STREIGHT RUN MIDDLE CAS:64741-44-2 RTECS #:LX3296000 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

LD50 LC50 Mixture:ORAL LD50 (RAT) IS > 5ML/KG Routes

of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-INHALED:IRRITATES RESPIRATORY TRACT,HEADACHE,NAUSEA,DIZZINESS,LOSS OF APPETITE,WEAKNESS,LOSS OF COORDINATION.EYES:IRRITATION.SKIN:PROLONGED/REPEATED CONTACT CAN CAUSE PAIN,SWELLING,BLISTERING.IN GESTION:MAY IRRITATE DIGESTIVE TRACT.ASPIRATION INTO THE LUNG MAY CAUSE LUNG DAMAGE.CHRONIC-SKIN DISCOLORATION,BLISTERS.

Explanation of Carcino

genicity: THE NIOSH HAS RECOMMENDED THAT WHOLE

DIESEL EXHAUST BE REGARDED AS POTENTIALLY CAUSING CANCER. Effects of Overexposure:INHALATION CAUSES IRRITATION OF RESPIRATORY TRACT, HEADACHE, NAUSEA, DIZZINESS, LOSS OF APPETITE, WEAKNESS, AND LOSS OF COORDINATION. IRRITATES EYE. PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE PAIN, SWELLING, BLISTERING. INGESTION MAY IRRITATE DIGESTIVE TRACT. ASPIRATION INTO THE LUNG MAY CAUSE LUNG DAMAGE.

Medical Cond Aggravated by Exposure:P

RE-EXISTING SKIN DISORDERS MAY BE

MORE SUSCEPTIBLE TO THIS MATERIAL.

First Aid:GET MEDICAL CARE IN ALL CASES.INHALATION:REMOVE TO FRESH AIR.PROVIDE CPR/OXYGEN IF NEEDED.EYE:FLUSH WITH WATER FOR 15 MINUTES KEEPING EYELID OPEN.SKIN:WASH WITH SOAP & WATER.INGESTION:DO NOT INDUCE VO MITING.ASPIRATION HAZARD.IF CONSCIOUS,DRINK MILK/WATER.CALL PHYSICIAN.IF SPONTANEOUS VOMITING OCCURS,KEEP HEAD LOWER THAN HIP S TO PREVENT PULMONARY ASPIRATION.

Flash Point Method:TCC Flash Point:100F,38C MIN Lower Limits:0.6 Upper Limits:4.7 Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. A FORCED STREAM OF WATER COULD SCATTER FLAMES OF FIRE. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusu al Fire/Explosion Hazard:MAY FORM WATER VAPOR, CARBON MONOXIDE AND CARBON DIOXIDE. WATER RUNOFF TO SEWER MAY CARRY COMBUSTIBLE FUELS & CREATE A FIRE/EXPLOSION. MORE FIRE HAZARD IF >85F. Spill Release Procedures: REMOVE SOURCE OF HEAT, SPARKS, FLAME, FRICTION & ELECTRICITY, INCLUDING INTERNAL COMBUSTION ENGINE. USE EXPLOSION-PROOF EQUIPMENT TO CLEAN UP.DIKE SPILL.PREVENT LIQUID FROM ENTERING SEWERS, WATERWAYS/LOW A R EAS.SOAK UP WITH SAWDUST, SAND, OIL DRY. SHOVEL/SWEEP Handling and Storage Precautions:STORAGE-STORE IN COOL,DRY WELL-VENTILATED AREA IN CLOSED CONTAINER AWAY FROM HEAT, IGNITION SOURCES & OXIDIZERS. Other Precautions: COMBUSTIBLE LIQUID. USE WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. GROUND AND BOUND CONTAINERS TO PREVENT STATIC SPARK

S. USE EXP LOSION-PROOF ELECTRICAL SERVICES.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection: IN SITUATION WHERE VAPOR CONCENTRATIONS MAY EXCEED THE RECOMMENDED EXPOSURE LIMITS, A NIOSH-APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR SHOULD BE WORN. USE SELF-CONTAINED SUPPLIED-AIR RESPIRATOR FOR E MERGENCIES.

Ventilation: GENERAL DILUTION OR MECHANICAL VENTILATION/EXPLOSION-PROOF LOCAL EXHAUST TO KEEP VAPOR BELOW RECOMMENDED EXPOSURE LIMITS Protective Gloves: NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL Eve Protection: USE CHEMICAL SAFETY GOGGLES & FACESHIELD Other Protective Equipment: EYE WASH STATION. BARRIER CREAMS SPECIFIC FOR PETROLEUM-BASED MATERIALS MAY BE USED WHEN GLOVES ARE IMPRACTICAL. Work Hygienic Practices: DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT. WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA. Supplemental Safety and Health FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PIN A SAME NSN. E MPTY CONTAINERS MAY CONTAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE TO HEAT, F LAME; THEY MAY EXPLODE. DO NOT USE PRESSURE TO EMPTY DRUM OR DRUM MAY RUPTURE WITH EXPLOSIVE FORCE. HCC:F4 Boiling Pt:B.P. Text:400F,204C Spec Gravity:0.85 Solubility in Water: INSOLUBLE Appearance and Odor: PALE YELLOW LIQUID WITH MILD PETROLEUM ODOR ====== Stabil Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS SUCH AS CHLORATES, NITRATES, PEROXIDES, ETC. Stability Condition to Avoid: HIGH HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE Waste Disposal Methods: WASTE MAY BE BURNED IN AN APPROVED INCINERATOR. TREATMENT, STORAGE, TRANSPORTATION AND D **ISPOSAL MUST BE IN** ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND **REGULATIONS.** Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.