

LHB INDUSTRIES -- SO SURE GLOSS BLACK 17038 (14-190)

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 00-290-6984  
MSDS Date: 04/16/1992  
MSDS Num: BPFVV  
Product ID: SO SURE GLOSS BLACK 17038 (14-190)  
MFN: 02  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS M  
O 63134  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 314-522-3141 800-424-9300(CHEMTREC)  
Preparer's Name: RUDOLF OPPENHEIM  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: ENAMEL  
Specification Number: A-A-665D  
Unit of Issue: PT  
UI Container Qty: 0

=====  
Ingredients  
=====

=====

Cas: 8030-30-6  
RTECS #: DE3030000  
Name: VM & P NAPHTHA  
% Wt: 8.46  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 300 PPM  
ACGIH TLV: 300 PPM

-----

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE (SARA 313)  
% Wt: 24.68  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 200 PPM/150 STEL  
ACGIH TLV: 50 PPM; 9293  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----

Cas: 67-64-1  
RTECS #: AL3150000  
Name: ACETONE (SARA 313)  
% Wt: 25.25  
Other  
REC Limits: NONE SPECIFIED  
OSHA PEL: 1000PPM  
ACGIH TLV: 750PPM/1000STEL;9293  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS

-----

Cas: 74-98-6  
RTECS #: TX2275000  
Name: PROPANE  
% Wt: 16.72  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 1000 PPM  
ACGIH TLV: 1000 PPM

-----

Cas: 75-28-5  
RTECS #: TZ4300000  
Name: ISOBUTANE  
% Wt: 4.11  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 800 PPM

-----

Cas: 106-97-8  
RTECS

#: EJ4200000

Name: N-BUTANE

% Wt: 6.58

Other REC Limits: NONE SPECIFIED

OSHA PEL: 800 PPM

ACGIH TLV: 800 PPM

RTECS #: 9999999VO

Name: VOC: 628 G/L

Other REC Limits: NONE SPECIFIED

Health Hazards Data

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENTRATE/INHALE CON

TENTS HARMFUL/FATAL. REPORTS

ASSOCIATE OCCUPATIONAL OVEREXPOSURE W/PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE.

CONFINED AREAS/HIGH CONCENTRATION OF VAPORS ARE ANESTHETIC. IRRITATION T O SKIN/RESPIRATORY TRACT. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.

Signs And Symptions Of Overexposure: IRRITATION TO EYES, THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGER, GIDDINESS, AND POSSIBLE NAUSEA.

Medical Cond Aggravated

By Exposure: RESPIRATORY AILMENTS.

First Aid: SKIN/CLOTHES: WASH WITH SOAP/WATER; WASH CLOTHES BEFORE REUSE. EYES: FLUSH W/WATER 15 MIN/CONTACT PHYSICIAN/ OPHTHALMOLOGIST IMMEDIATELY. INGEST: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL AID. INH ALE: MOVE TO FRESH AIR/ARTIFICIAL RESPIRATION IF NEEDED. GET MEDICAL AID. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Handling and Disposal

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: IN ACCORDANCE W/APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT PUNCTURE/INCINERATE/STORE ABOVE 120F. EXPOSURE TO HEAT/PROLONGED EXPOSURE TO SUN: CONTAINER MAY BURST. DISCARD EMPTY IN TRASH PI CK-UP. DO NOT PLACE IN HOME TRASH COMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CAUT

ION-

CONTENTS UNDER PRESSURE. DO NOT STORE WHERE TEMPS EXCEED 120F. AVOID BREATHING SPRAY/MIST/VAPOR.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USE. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING OR SWALLOWING MAY BE HARMFUL OR FATAL.

=====  
Fire and Explosion Hazard Information  
=====

==  
Flash Point Text: NR

Autoignition Temp Text: 874 F

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.

Fire Fighting Procedures: WATER INEFFECTIVE/USED TO COOL CONTAINERS. WEAR SELF-CONTAINED BREATHING APPARATUS. USE SHIELDING TO PROTECT PERSONNEL FROM BURST/RUPTURE/VENT CONTAINERS.

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPERATURE (OVER 120F) CONTAINERS MAY VENT/RUPTURE/BURST. AEROSOL CONTAINER;  
DO NOT EXPOSE TO TEMPS ABOVE 120F.

=====  
Control Measures  
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL: ACCEPTABLE AT POINT OF SPRAY OR MIST RELEASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH

STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE WHILE USING PRODUCT.

=====  
Physical/Chemical Properties  
=====

HCC: V3

Vapor Pres: 60 @ 68 F

Vapor Density: >1.5

Spec Gravity: .867 (WATER=1)

Solubility in Water: INSOLUBLE

Appearance and Odor: GLOSS BLACK/PAINT

Percent Volatiles by Volume: 85  
=====

Reacti

Stability Data

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT.

Hazardous Decomposition Products: CARBON MONOXIDE, AND POSSIBLE HYDROGEN CHLORIDE.

Hazardous Polymerization Indicator: NO

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Code: 0FTT5

Trans ID NO: 67799

Product ID: SO SURE GLOSS BLACK 17038 (14-190

MSDS Prepared Date: 04/16/1992

Review Date: 09/08/1992

MFN: 2

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: PT

Container QTY: 0

Detail DOT Information

DOT PSN Code: DTJ

Symbols: D

DOT Proper Shipping Name

: CONSUMER COMMODITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 156,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A

=====  
Detail IMO Information  
=====

IMO PSN Code: AKH  
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?  
IMDG Page Number: SEE 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidiary Risk Label: -  
EMS Number: 2-13

=====  
Detail IATA Information  
=====

IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass: 75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo: 203

=====  
Detail AFI Information  
=====

AFI PSN Code: ALS  
AFI Proper Shipping Name: AEROSOLS, NONFLAMMABLE, N.O.S.  
AFI PSN Modifier: CONTAINING SUBSTANCES IN CLASS 8, PACKING GROUP I OR II  
AFI Hazard Class: FORB  
Back Pack Reference: FORBIDDEN

=====  
HAZCOM Label  
=====

Product ID: SO SURE GLOSS BLACK 17038 (14-190)  
Cage: 0FTT5  
Company Name: LHB INDUSTRIES  
Street: 8833 FLEISCHER PLACE  
City

: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 314-522-3141 800-424-9300(CHEMTREC)

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATE/INHALE CONTENTS HARMFUL/FATAL. REPORTS ASSOCIATE OCCUPATIONAL OVEREXPOSURE W/PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE.

CONFINED AREAS/HIGH CONCENTRATION OF VAPORS ARE ANESTHETIC. IRRITATION TO SKIN/RESPIRATORY TRACT. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.

IRRITATION TO EYES, THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGER, GIDDINESS, AND POSSIBLE NAUSEA.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrant

s, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.