View NSN Online: https://aerobasegroup.com/nsn/9140-01-292-4460

CHEVRON ENVIRONMENTAL HEALTH CENTER INC. -- HEATING FUEL NO 1 -- 9140-01-292-4460

Product ID:HEATING FUEL NO 1

MSDS Date:01/03/1992

FSC:9140

NIIN:01-292-4460

MSDS Number: BPGKB === Responsible Party ===

Company Name: CHEVRON ENVIRONMENTAL HEALTH CENTER INC.

Address:15299 SAN PABLO AVE.

Box:4054

City:RICHMOND

State:CA ZIP:94804 Country:US

Info Phone Num:415-233-37

37 OR 800-582-3835

Emergency Phone Num:415-233-3737 OR 800-457-2022

CAGE:0AHD1

=== Contractor Identification ===

Company Name: CHEVRON ENVIRONMENTAL HEALTH CENTER INC

Address:15299 SAN PABLO AVE

Box:4054

City:RICHMOND

State:CA ZIP:94804 Country:US

Phone:800-582-3835

CAGE:0AHD1

======= Composition/Information on Ingredients ========

Ingred Name: ALIPHATIC PETROLEUM SOLVENT/KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Other REC Limits: NONE RECOMMENDED

Ingred Name: KEROSENE/KEROSENE HYDROD

ESULFURIZED
CAS:64742-81-0
Other REC Limits:NONE RECOMMENDED

Ingred Name: DISTILLATES, HYDROSULFURIZED MIDDLE

CAS:64742-80-9

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name: DISTILLATES, STREIGHT RUN MIDDLE

CAS:64741-44-2 RTECS #:LX3296000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

=========== Hazards Identification =================

LD50 LC50 Mixture:ORAL LD50 (RAT) IS > 5ML/KG

Routes

of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-INHALED:IRRITATES RESPIRATORY TRACT,HEADACHE,NAUSEA,DIZZINESS,LOSS OF APPETITE,WEAKNESS,LOSS OF COORDINATION.EYES:IRRITATION.SKIN:PROLONGED/REPEATED CONTACT CAN CAUSE PAIN,SWELLING,BLISTERING.IN GESTION:MAY IRRITATE DIGESTIVE TRACT.ASPIRATION INTO THE LUNG MAY CAUSE LUNG DAMAGE.CHRONIC-SKIN DISCOLORATION.BLISTERS.

Explanation of Carcino

genicity:THE NIOSH HAS RECOMMENDED THAT WHOLE

DIESEL EXHAUST BE REGARDED AS POTENTIALLY CAUSING CANCER.

Effects of Overexposure:INHALATION CAUSES IRRITATION OF RESPIRATORY TRACT, HEADACHE, NAUSEA, DIZZINESS, LOSS OF APPETITE, WEAKNESS, AND LOSS OF COORDINATION. IRRITATES EYE. PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE PAIN, SWELLING, BLISTERING. INGESTION MAY IRRITATE DIGESTIVE TRACT. ASPIRATION INTO THE LUNG MAY CAUSE LUNG DAMAGE.

Medical Cond Aggravated by Exposure:P RE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL.

First Aid:GET MEDICAL CARE IN ALL CASES.INHALATION:REMOVE TO FRESH AIR.PROVIDE CPR/OXYGEN IF NEEDED.EYE:FLUSH WITH WATER FOR 15 MINUTES KEEPING EYELID OPEN.SKIN:WASH WITH SOAP & WATER.INGESTION:DO NOT INDUCE VO MITING.ASPIRATION HAZARD.IF CONSCIOUS,DRINK MILK/WATER.CALL PHYSICIAN.IF SPONTANEOUS VOMITING OCCURS,KEEP HEAD LOWER THAN HIP

S TO PREVENT PULMONARY ASPIRATION. Flash Point Method:TCC Flash Point:100F,38C MIN Lower Limits:0.6 Upper Limits:4.7 Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. A FORCED STREAM OF WATER COULD SCATTER FLAMES OF FIRE. Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusua I Fire/Explosion Hazard: MAY FORM WATER VAPOR, CARBON MONOXIDE AND CARBON DIOXIDE. WATER RUNOFF TO SEWER MAY CARRY COMBUSTIBLE FUELS & CREATE A FIRE/EXPLOSION. MORE FIRE HAZARD IF >85F. ======== Accidental Release Measures =========== Spill Release Procedures: REMOVE SOURCE OF HEAT, SPARKS, FLAME, FRICTION & ELECTRICITY, INCLUDING INTERNAL COMBUSTION ENGINE. USE EXPLOSION-PROOF EQUIPMENT TO CLEAN UP.DIKE SPILL.PREVENT LIQUID FROM ENTERING SEWERS, WATERWAYS/LOW AR EAS.SOAK UP WITH SAWDUST, SAND, OIL DRY. SHOVEL/SWEEP ============== Handling and Storage ========================= Handling and Storage Precautions: STORAGE-STORE IN COOL, DRY WELL-VENTILATED AREA IN CLOSED CONTAINER AWAY FROM HEAT, IGNITION SOURCES & OXIDIZERS. Other Precautions: COMBUSTIBLE LIQUID. USE WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. GROUND AND BOUND CONTAINERS TO PREVENT STATIC SPARKS . USE EXP LOSION-PROOF ELECTRICAL SERVICES. ===== Exposure Controls/Personal Protection ========

Respiratory Protection: IN SITUATION WHERE VAPOR CONCENTRATIONS MAY EXCEED THE RECOMMENDED EXPOSURE LIMITS, A NIOSH-APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR SHOULD BE WORN. USE SELF-CONTAINED SUPPLIED-AIR RESPIRATOR FOR E MERGENCIES.

Ventilation:GENERAL DILUTION OR MECHANICAL VENTILATION/EXPLOSION-PROOF LOCAL EXHAUST TO KEEP VAPOR BELOW RECOMMENDED EXPOSURE LIMITS

rotective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL
Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD
Other Protective Equipment:EYE WASH STATION.BARRIER CREAMS SPECIFIC FOR
PETROLEUM-BASED MATERIALS MAY BE USED WHEN GLOVES ARE IMPRACTICAL.
Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.
WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK
AREA.

Supplemental Safety and Health

EMPTY CONTAINERS MAY CONTAIN RESIDUE AND CAN BE DANGEROUS. DO NOT

PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE TO HEAT, FLAME; THEY MAY EXPLODE. DO NOT USE PRESSURE TO EMPTY DRUM OR DR UM MAY RUPTURE WITH EXPLOSIVE FORCE.

========= Physical/Chemical Properties =========
HCC:F4 Boiling Pt:B.P. Text:400F,204C Spec Gravity:0.85 Solubility in Water:INSOLUBLE Appearance and Odor:PALE YELLOW LIQUID WITH MILD PETROLEUM ODOR
========= Stability and Reactivity Data =========
Stability Indicator/Mate rials to Avoid:YES STRONG OXIDIZING AGENTS SUCH AS CHLORATES, NITRATES, PEROXIDES, ETC Stability Condition to Avoid:HIGH HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Waste Disposal Methods:WASTE MAY BE BURNED IN AN APPROVED INCINERATOR. TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL MUST BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE A ND FEDERAL LAWS AND

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

======= Disposal Considerations =============================

ND FEDERAL LAWS REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this in

formation to their particular situation.