View NSN Online: https://aerobasegroup.com/nsn/9130-00-148-7103

U S OIL AND REFINING CO -- REGULAR UNLEADED GASOLINE -- 9130-00-148-7103

Product ID:REGULAR UNLEADED GASOLINE MSDS Date:10/01/1985 FSC:9130 NIIN:00-148-7103 MSDS Number: BPHGM === Responsible Party === Company Name: U S OIL AND REFINING CO Address:3001 MARSHALL AVE E City:TACOMA State:WA ZIP:98421-3118 Country:US Emergency Phone Num:253-383-1651 CAGE:6E780 === Contractor Identification === Company Name: TRUE NORTH ENERGY CO Address:180 E OCEAN BLVD NO 906 Box:City:LONG BEACH State:CA ZIP:90802-4760 Country:US CAGE:0NFP0 Company Name: U S OIL AND REFINING CO Address:3001 E MARSHALL AVE Box:2255 City:TACOMA State:WA ZIP:98401-2255 Country:US Phone:253-383-1651/FAX: 253-383-9970 CAGE:6E780

Ingred Name:GASOLINE CAS:8006-61-9 RTECS #:LX3300000 Fraction by Wt: 100% Other REC Limits:NONE RECO MMENDED OSHA PEL:300 PPM/500 STEL ACGIH TLV:300 PPM/500STEL;9293

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic: ACUTE-INHALATION: PROLONGED EXPOSURE MAY CAUSE SYMPTOMS OF CENTRAL NERVOUS SYSTEM DEPRESSION. EYE: EYE IRRITATION MAY RESULT FROM CONTACT WITH LIQUID. SKIN: SKIN IRRITATION. CHRONIC\_EXPOSURE TO HIGH L EVELS OF GASOLINE VAPORS MAY CAUSE ASPHYXIATION, SKIN IRR ITATION, CENTRAL NERVOUS SYSTEM **DEPRESSION, & CHEMICAL PNEUMONI** Explanation of Carcinogenicity: A LAB STUDY DONE BT API HAS SHOWN THAT RATS & MICE DEVELOPED CANCER AFTER CHRONIC INHALATION TO VAPORS OF UNLEADED GAS. Effects of Overexposure: INHALATION: DIZZINESS, INCOORDINATION, DROWSINESS, COMA AND DEATH. SKIN: DERMATITIS MAY OCCUR UPON PROLONGED CONTACT DUE TO SKIN DEFATTING.INGESTION: NAUSEA, VOMITING, DIARRJEA AND RESTLESSNESS. Medical Cond Aggravated by Exposure:NONE S PECIFIED BY MANUFACTURER.

First Aid:INHALATION-REMOVE FROM ARE TO FRESH AIR. GIVE OXYGEN OR ADMINISTER CPR, IF NEEDED. OBTAIN PROMPT MEDICAL ATTENTION. EYE-FLUSH WITH CLEAN WATER FOR AT LEST 15 MIN. IF IRRITATION PERSISTS, OBTAIN MEDICA L ATTENTION. SKIN-QUICKLY REMOVE SOILEDCLOTHES. WASH AREA WITH SOAP & WATER. IF IRRITATION PERSISTS, OBTAIN MEDICAL ATTENTION. INGESTUION-DO NOT INDUCE VOMITING. MUST O

BTAIN MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:-45F,-43C Autoignition Temp:Autoignition Temp Text:>600F Lower Limits:1.3% Upper Limits:8.2% Extinguishing Media:DRY CHEMICAL, FOAM, CARBON DIOXIDE, HALON. WATER FOG OR WATER SPRAY ARE OF VALUE FOR COOLING, BUT MAY NOT EXTINGUISH. Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED FIRE SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BR

EATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER. Unusual Fire/Explosion Hazard: EXTREMELY FLAMMABLE! THIS MATERIAL RELEASES VAPORS AT OR BELOW AMBIENT TEMPERATURE. WHEN MIXED WITH AIR & EXPOSED TO IGNITION SOURCES VAPORS CAN BURN OR EXPLODE Spill Release Procedures: CONTAIN SPILL, REMOVE ALL IGNITION SOURCES & SAFELY STOP FLOW. IN URBAN AREAS, CLEANUP ASAP; IN NATURAL ENVIRONMENT, SEEK ADVICE FROM ECOLOGIST. EVACUATE ALL PERSONNEL. USE PROPER PROTECTIVE EQUIPMENT . \*\*\*CONTINUES IN OTHER PRECAUTIONS\*\*\* Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS & OPEN FLAMES. KEEP CONTAINERS CLOSED! GROUND ALL DRUMS & TRANSFER VESSELS WHEN HANDLING. KEEP OUT OF REACH OF CHILDREN. Other Precautions: BALNKET WITH FOAM OR USE WATER FOG TO DISPERSE VAPORS. PADS/ABSORBENT MATERIAL CAN BE USED. GASOLINE WIL L FLOAT ON WTAER AND RESULTING RUNOFF MAY CREATE AN EXPLOSION OR FIRE HAZARD. NOTIFY NATIONAL RE SPONSE CENTER (800/424-8802). Respiratory Protection: AN APPROVED ORGANIC VAPOR RESPIRATOR, SUPPLIED AIR, OR SELF-CONTAINED BREATHING APPARATUS MUST BE USED WHEN VAPOR CONCENTRATIONS EXCEED THE OCCUPATIONAL EXPOSURE LIMITS. Ventilation: USE ADEQUATE VENTILATION TO KEEP VAPOR CONCENTRATIONS OF THIS MATERIAL BELOW T HE OCCUPATIONAL EXPOSURE LIMITS. Protective Gloves: CLEAN & IMPERVIOUS GLOVES. Eve Protection: CHEMICAL TYPE GOGGLES &/OR FACE SHIELD Other Protective Equipment: WEAR CLEAN & IMPERVIOUS PROTECTIVE CLOTHING SUCH AS GLOVES, APRON, BOOTS AND FACIAL PROTECTION SHOULD BE WORN. Work Hygienic Practices: USE GOOD PERSONAL HYGIENE PRACTICES. IMMEDIATELY REMOVE SOILED CLOTHING & WASH THOROUGHLY BEFORE REUSE. **DISCARD SHOES.** Supplemental Safety and Health NOTE TO PHYSICIAN: TOXIC SIGNS AND SYMPTOMS

MAY FOLLOW CONTACT WITH SKIN OVER LARGE AREAS OF THE BODY, INHALATION OF VAPORS OR INGESTION. PRIMARY HAZARD: INHALATION OF VAPORS. INGESTION, OF LIQUID & A SPIRATION INTO THE LUNGS MAY RESULT IN CHEMICAL PNEUMONIA.

HCC:F1 Boiling Pt:=21.1C, 70.F B.P. Text:70 TO 440F Melt/Freeze Pt:M.P/F.P Text:N/AP Decomp Temp:Decomp Text:N/AP Vapor Pres:8-15 PSIA Vapor Density:N/AP Spec Gravity:0.72 TO 0.77 pH:N/AP Viscosity :N/AP Evaporation Rate & amp; Reference: SLOWER THAN BUTYL ACETATE Solubility in Water:SLIGHT. Appearance and Odor: COLORLESS TO STRAW-COLORED LIQUID; PETROLEUM NAPHTHA ODOR. Percent Volatiles by Volume: APPREC Corrosion Rate:N/AP

Stability Indicator/Materials to Avoid:YES REACTS WITH STRONG ACIDS AND STRONG OXIDIZING MATERIALS. Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES. Hazardous Decomposition Products:BURNIN G OR EXCESSIVE HEATING MAY PRODUCE CARBON MONOXIDE AND OTHER HARMFUL GASES AND VAPORS.

Waste Disposal Methods:MAXAMIZE PRODUCT RECOVERY FOR REUSE PRIOR TO DISPOSAL. DISPOSE OF PRODUCT, CONTAMINATED MATERIAL, & STORAGE TANK WATER BOTTOMS AS AN EPA "IGNITABLE HAZARDOUS WASTE" (D001), UNLESS PROVEN OTHERWISE. CO MPLY WITH ALL LAWS.

Disclaimer (provided with this information by the compiling agencies): This info

rmation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.