

HULS AMERICA INC -- MIL-H-5606 F -- 9150-00-265-9408

=====
===== Product Identification =====

Product ID:MIL-H-5606 F
MSDS Date:03/30/1992
FSC:9150
NIIN:00-265-9408
MSDS Number: BPHZQ
=== Responsible Party ===
Company Name:HULS AMERICA INC
Address:80 CENTENNIAL AVE
Box:456
City:PISCATAWAY
State:NJ
ZIP:08855-0456
Country:US
Info Phone Num:201-980-6800
Emergency Phone Num:201-763-7173
Preparer's Name:P.A
. PARKER
CAGE:63182
=== Contractor Identification ===
Company Name:HULS AMERICA INC
Address:TURNER PLACE
Box:365
City:PISCATAWAY
State:NJ
ZIP:08855
Country:US
Phone:201-763-7173
CAGE:63182

=====
===== Composition/Information on Ingredients =====

Ingred Name:PROPRIETARY PETROLEUM HYDROCARNON
Other REC Limits:NONE RECOMMENDED

Ingred Name:OTHER INGREDIENTS
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalat

ion:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MISTS/VAPORS/FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. INHALATION MAY CAUSE VOMITING, NAUSEA AND DIZZINESS.

Explanation of Carcinogenicity:NONE NOTED

Effects of Overexposure:OVEREXPOSURE MAY LEAD TO RESPIRATORY IRRITATION, DERMATITIS AND EYE IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH A SKIN DISORDER SHOULD

USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:220F,104C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR H

EAT OF FIRE MAY PRODUCE

HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. RECOVER FREE LIQUID. WIPE OR MOP UP OR ABSORB WITH DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE IN APPROPRIATE CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE NEAR OPEN FLAME OR OTHER SOURCES OF IGNITION. EXCESS

IVE MISTING MAY CAUSE SLIPPERY FLOORS.

PROPER FOOTWEAR REQUIRED.

Other Precautions:WASH HANDS WITH SOAP AND WATER BEFORE EATING,
DRINKING, OR SMOKING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED
RESPIRATORS FOR OIL OR MIST.

Ventilation:SUFFICIENT TO MAINTAIN ATMOSPHERE BELOW TLV LIMIT.

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES

Oth

er Protective Equipment:EYE WASH STATION & SAFETY SHOWER. CHEMICALLY
RESISTANT BOOTS AND APRONS RECOMMENDED.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.

WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK
AREA.

Supplemental Safety and Health

WASH OR TAKE SHOWER IF GENERAL CONTACT OCCURS. REMOVE OIL-SOAKED
CLOTHING AND LAUNDER BEFORE REUSE. DISCARD CONTAMINATED LEATHER
GLOVES AND SHOES.

=====
===== Physical/Chemical Properties ==

=====

HCC:V6

Vapor Pres:0.07 MM HG

Spec Gravity: