

DAVLIN PAINT CO. -- 221 INTERIOR SEMIGLOSS -- 8010-00-754-2610

===== Product Identification =====

Product ID:221 INTERIOR SEMIGLOSS

MSDS Date:03/20/1992

FSC:8010

NIIN:00-754-2610

MSDS Number: BPJFD

=== Responsible Party ===

Company Name:DAVLIN PAINT CO.

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:(510) 889-7098

Emergency Phone Num:(510)848-2863,CHEMTREC 800-424-9300

Prepar

er's Name:PATRICIA SHAW

CAGE:DO185

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

Company Name:DAVLIN PAINT CO.

Address:P.O. BOX 2308

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Phone:415-889-7098

CAGE:DO185

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL

CAS:57-55-6

RTECS #:TY2000000

Fraction by Wt: 5.0%

Other REC Limits

:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYLPENTANEDIOL-1,3-MONOISOBUTYRATE

CAS:25265-77-4

Fraction by Wt: 5.0%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION:IRRITATION OF EYES, NOSE,  
THROAT/LUNGS. SKIN:IRRITATION, RASH. INGESTION:GASTROINTESTINAL  
IRRITATION, VOMITING, NAUSEA,  
DIARRHEA.  
Effects of Overexposure:INHALATION: IRRITATION OF EYES, NOSE,  
THROAT/LUNG. SKIN:IRRITATION, DRYING, & RASH. INGESTION:VOMITING,  
DIARRHEA & NAUSEA.  
Medical Cond Aggravated by Exposure:SKIN DISEASES.

=====  
===== First Aid Measures =====  
=====

First Aid:INHALATION: MOVE PERSON TO FRESH AIR. EYE: FLUSH W/LARGE  
QUANTITIES OF WATER FOR 15 MINS & CALL PHYSICIAN. SKIN: WASH  
THOROUGHLY W/SOAP & WATER. INGESTION: DRINK 1-2 GLASSES OF WATER TO  
DILUTE. DON'T INDUCE VOMITING. CONSULT PHYSICIAN.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:TCC  
Flash Point:241F,116C  
Lower Limits:0.6  
Upper Limits:12.5  
Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures:IF THIS MATERIAL IS INVOLVED IN A FIRE,NIOSH  
APPROVED SELF-CONTAINED RESPIRATORY EQUIPMENT SHOULD BE WORN.  
Unusual Fire/Explosion Hazard:ALTHOUGH THIS MATERIAL IS  
NON-FLAMMABLE,VAPORS CAN COLLECT ABOVE LIQUID IN CLOSE  
D  
CONTAINERS/STORAGE VESSELS.CLOSED CONTAINERS MAY EXPLODE IN THE  
HEAT OF FIRE.

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:KEEP PERSONNEL AWAY. FLOORS MAY BE SLIPPERY,  
USE CARE TO AVOID FALLING. DIKE/CONTAIN SPILL W/INERT MATERIAL.  
TRANSFER LIQUID & DIKING MATERIAL TO CONTAINERS FOR RECOVERY OR  
DISPOSAL. KEEP SPILLS OUT OF SEWERS & OPEN WATER.

=====  
===== Handling and Storage =====  
=====

Handling an

d Storage Precautions: DON'T STORE >100F. AVOID FREEZING.  
DON'T TAKE INTERNALLY. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR NIOSH APPROVED RESPIRATOR TO MAINTAIN MISTS  
& VAPORS BELOW TLV. HIGH AIRBORNE CONCENTRATIONS MAY REQUIRE THE  
USE OF A SUPPLIED-AIR RESPIRATOR OR A SELF-CONTAINED BREATHING  
APPARATUS.

Ventilation: PROVIDE MECHANICAL/LOCAL EXHAUST VENTILATION TO KEEP