

AKZO COATINGS INC -- X-422, CATALYST FOR 463-07-0027 -- 8010-01-050-4082

=====
Product Identification
=====

Product ID:X-422, CATALYST FOR 463-07-0027

MSDS Date:10/26/1992

FSC:8010

NIIN:01-050-4082

Kit Part:Y

MSDS Number: BPJHH

=== Responsible Party ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

City:ORANGE

State:CA

ZIP:92661

Country:US

Info Phone Num:714-637-1750

Emergency Phone

Num:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 35-45%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:NAPHTHA, LIGHT ALIPHATIC
CAS:64742-89-8
Fraction by Wt: 35-45%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYAMIDE
CAS:68082-29-1
Fraction by Wt: 15-25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TRIETHYLENE TETRAMINE
CAS:112-24-3
RTECS #:YE6650000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPYLENE GLYCOL METHYL ETHER (GLYCOL ETHER PM) (VAPOR
PRESSURE 12.5 MM HG)
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 5-20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/360 MG/M3
ACGIH TLV:100 PPM/369 MG/M3

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 9.5 MM HG)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5-20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/435 MG/M3
ACGIH TLV:100 PPM/434 MG/M3
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acut

e and Chronic:ACUTE-EYES/SKIN:IRRITATION.

INHALATION:IRRITATION TO THE RESPIRATORY TRACT, DIZZINESS, HEADACHE, UNCONSCIOUSNESS. INGESTION: INTESTINAL DISORDERS, NAUSEA, VOMITING, ASPIRATION INTO LUNGS MAY CAUSE CHE MICAL PNEUMONITIS WHICH CAN BE FATAL. CHRONIC-DERMATITS, LIVER AND KIDNEY DAMAGE.

Effects of Overexposure:COUGHING, HEADACHE, VOMITING, WEAKNESS, GASTROINTESTINAL IRRITATION. OVEREXPOSURE MAY RESULT IN DAMAGE TO BLOOD, KIDNEYS, LIVER, BONE MARROW &/OR EYES. IRRITANT & DEPRESSANT FOR CENTRAL NERVOUS SYSTEM .

Medical Cond Aggravated by Exposure:LUNGS, LIVER AND KIDNEY.

===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY. SKIN: WASH WITH SOAP AND WATER. EYE: FLUSH WITH WATER FOR AT LEAST 15 MIN, CONSULT A PHYSICIAN. INGESTION: DRINK ONE OR TWO GLA SSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENT ER IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:20.0F,-6.7C

Lower Limits:1.1

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE. FIRE FIGHTING PERSONNEL SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. MAY EMIT TOXIC VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENTS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINER AWAY FROM SUN/HEAT/IGNITE SOURCES. KEEP CONTAINER CLOSED. USE APPROVED BONDING & GROUNDING PROCEDURES.

Other Precautions:UPRIGHT. DO

NOT USE PRESSURE TO EMPTY CONTAINERS.
AVOID BREATHING SANDING DUST. DO NOT WELD OR FLAME CUT AN EMPTY
DRUM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ADEQUATE VENTILATION IS REQUIRED. USE NIOSH
APPROVED RESPIRATOR DEVICE. SEE YOUR SAFETY EQUIPMENT SUPPLIER FOR
EVALUATION AND RECOMMENDATION. IN CONFINED AREAS USE NIOSH APPROVED
AIRLINE RESPIRATOR OR HOOD.

Ventilation:PROVIDE VENTILATION TO KEEP VAPOR CONCENTRATION BELOW TLV &
LEL.

Protective Gloves:REQUIRED FOR PROLONGED/REPEATED CONTACT.

Eye Protection:SAFETY EYEWEAR TO PROTECT FROM SPLASHES.

Other Protective Equipment:EYE BATH & SHOWER. USE CHEMICAL RESISTANT
APRON, BOOTS OR OTHER CLOTHES IF NEEDED.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING
WASHROOM. AVOID CONTACT WITH SKIN.

Supplemental Safety and Health

LIQUID MAY PENETRATE SHOES AND LEATHER CAUSING DELAYED IRRITATION. DRY
PIGMENT MAY CAUSE A NUISANCE DUST WHICH CAN BE IRRITATING TO

RESPIRATORY SYSTEM. OVEREXPOSURE TO DUST MAY CAUSE LUNG DAMAGE.

===== Physical/Chemical Properties =====

HCC:B2

Boiling Pt:B.P. Text:177F,81C

Vapor Density:>AIR

Spec Gravity:0.80

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:84

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS.

Stability Condition to Avoid:HIGH TEMP, OPEN FLAMES.

Hazardous

Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
SMOKE, OXIDES OF NITROGEN AND METAL OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL POLLUTION CONTROL REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.