View NSN Online: https://aerobasegroup.com/nsn/9150-00-664-0111 INLAND PACKAGING -- INNERBOND 2010 FLUID 10 CST -- 9150-00-664-0111 Product ID: INNERBOND 2010 FLUID 10 CST MSDS Date:11/02/1992 FSC:9150 NIIN:00-664-0111 MSDS Number: BPKWQ === Responsible Party === Company Name: INLAND PACKAGING Box:644 City:ELIZABETHTOWN State:KY ZIP:42701-9804 Country:US Info Phone Num:502-737-6757 Emergency Phone Num:502-737-6758 CAGE:66172 = == Contractor Identification === Company Name: INLAND PACKAGING INC Address: 209 PETERSON DR Box:644 City:ELIZABETHTOWN State:KY ZIP:42701-9804 Country:US Phone:502-737-6757 CAGE:66172 ======= Composition/Information on Ingredients ========

Ingred Name:HEXAMETHYLDISILOXANE
Other REC Limits:NONE SPECIFIED

Ingred Name: TETRADECAMETHYLHEXASILIXONE

Other REC Limits: NONE SPECIFIED

========= Hazards Identification ===============

LD50 LC50 Mixture: DERMAL LD50 (RAT) I

| S 2000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: DROWSINESS, DIZZINESS, AND HEADACHES. EYES: TEARING, REDNESS, MILD BURNING SENSATION. SKIN: MILD IRRITATION. INGESTION: MILD NAUSEA. Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN CONDITIONS MAY BE AGGRAVATED BY OVEREXPOSURE. |
|---|
| ====================================== |
| First Aid:INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, SEE DOCTOR. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER FOR AT LEAST 15 MINUTES. IF SYMPTOMS PERSIST, SEE DOCTOR. INGESTION: INDUCE VOMITING. SEE DOCTOR IMMEDIATELY. IF ANY SYMPTOMS LAST LONGER THAN 24 HOURS, SEE DOCTOR. |
| ====================================== |
| Flash Point:55.4F,13.0C Extinguishin g Media:FOAM, CARBON DIOXIDE, OR DRY CHEMICAL. Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID. COOL CONTAINERS WITH WATER FOG. MATERIAL MAY REIGNITE WHEN FLOATING ON TOP OF WATER. |
| =========== Accidental Release Measures =========== |
| Spill Release Procedures:ISOLATE AREA. ELIMINATE ALL SOURCES OF IGNITION. ABSORB WITH VERMICULITE AND SWEEP INTO STEEL DRUM FOR LATER DISPOSAL. CONTACT LOCAL ENVIRONMENTAL MANAGER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. |
| ============ Handling and Storage ============ |
| Handling and Storage Precautions:STORE IN COOL(|