View NSN Online: https://aerobasegroup.com/nsn/9140-00-286-5297

Product ID:DIESEL FUELS MSDS Date:09/12/1990 FSC:9140 NIIN:00-286-5297 MSDS Number: BPMGP === Responsible Party === Company Name: MOBIL CORP Address:150 E 42ND ST **City:NEW YORK** State:NY ZIP:10017-5612 Country:US Info Phone Num:800-662-4525 Emergency Phone Num:609-737-4411 / 800-424-9300CHEMTREC Preparer's Name: ENVIRO NMENTAL HEALTH & SA CAGE:57635 === Contractor Identification === Company Name: MOBIL CORP Address:150 E 42ND ST Box:City:NEW YORK State:NY ZIP:10017-5612 Country:US Phone:212-883-4242 CAGE:57635 Company Name: MOBIL OIL CORP Address:3225 GALLONS ROAD City:FAIRFAX State:VA ZIP:22037-0001 Country:US Phone:609-737-4411/CHEMTREC 800-424-9300 CAGE:3V728

Ingred Name:DIESEL FUEL (NO. 2 DIESEL FUEL) CAS:68334-30-5 RTECS #:HZ1800000 Frac

tion by Wt: 100% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: HARMFUL IF IN CONTACT WITH OR

ABSORBED THROUGH THE SKIN. CONTACT MAY CAUSE SKIN AND EYE IRRITATION. INHALATION IS MODERATLEY TOXIC. INGESTION IS SLIGHTLY TOXIC. CHRONIC: PROLONGED OR REPEATED E XPOSURE MAY CAUSE LIVE R OR

BLOOD-FORMING ORGAN DAMAGE, EFFECT THE UNBORN. MAY CAUSE SKIN IRRITATION OR DERMATITIS.

Explanation of Carcinogenicity:PER MANUFACTURER'S MSDS-ANIMAL STUDIES SHOW DIESEL EXHAUST HAS THE POTENTIAL FOR LUNG CANCER.

Effects of Overexposure:SKIN/EYE-DRY SKIN, IRRITATION. INHALED: RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS. INGESTION-NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES-FLUSH WITH WATER. GET MEDICAL ASSISTANCE. SKIN-DRY WIPE. WASH WITH WATERLESS CLEANER, FOLLOWED BY SOAP & WATER. REMOVE CONTAMINATED CLOTHES & SHOES. INHALED-REMOVE FROM EXPOSURE. IF UNCONSCIOUSNE SS OCCURS, SEEK IMMEDIATE MEDICAL ASSISTANCE. IF BREATHING STOPPED, GIVE ARTIFICIAL RESPIRATION. INGESTED-DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE 1-2 GLASSES OF WATER. GET IMMEDIATE MEDICAL HELP.

Flash Point Method:PMCC Flash Point:>125F,>52C Extinguishing Media:WATER FOG, CARBON DIXOIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING SELF-CONTAINED BREATHING APPARATUS. USE WATER TO COOL FIRE EXPOSED CONTAINERS. CONTAIN RUNOFF. Unusual Fire/Explosion Hazard:MATERIAL IS COMBUSTIBLE.

Spill Release Proce

dures: ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVEL UP AND DISPOSE OF IN ACCORDANCE WITH CURRENT LOCAL, STATE AND FEDERAL REGULATIONS. REPORT SPILLS AS REQUIRED TO PROPER AUTHORI TIES. IF AFFECTS WATERWAYS-CALL 800-424-8802.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY FROM SOURCES OF IGNITION AND INCOMPATIBLE

MATERIALS. AVOID ALL PERSONAL

CONTACT AND BREATHING MISTS/VAPORS.

Other Precautions: FLAMMABLE ATMOSPHERE CAN BE PRODUCED IN TANKS. GROUND & BOND ALL TRANSFER EQUIPMENT. STORED MATERIAL MUST BE LABELED AS COMBUSTIBLE.

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER NORMAL CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Ventilation: VENTILATION DESIRABLE AND EQUIPMENT MUST BE

EXPLOSION-PROOF. USE IN WEL

L-VENTILATED AREA.

Protective Gloves: IMPERVIOUS-NITRILE, PVA.

Eye Protection: CHEMICAL GOGGLES FOR SPLASH PROTECTION.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. DLA-HMIS:

EYE WASH STATION & SAFETY SHOWER AVAILABLE FOR EMERGENCIES.

Work Hygienic Practices: WASH HANDS AFTER USE AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health

ENVIRONMENTAL DATA: SARA 311/312-FIRE, CHRONIC, ACUTE; SARA 313: NONE. TSCA-ALL. N

OTE: THIS PRODUCT CONTAINS AROMATIC OILS WHICH CONTAIN POLYCYCLIC AROMATIC HYDROCARBONS (PCAH). UNDER CONDITIONS OF PO OR PERSONAL HYGIENE SOME PCAH MAY CAUSEHUMAN SKIN CANCER. MD'S NOTE: ASPIRATED PRODUCT MAY CAUSE CHEMICAL PNEUMONITIS.

HCC:F4 Boiling Pt:B.P. Text:350F,177C Vapor Pres:0.5 MM HG Spec Gravity:0.82-0.87 Viscosity:1.3-4.1 CST Appearance and Odor:CLEAR TO AMBER LIQUID; HYDROCARBON ODOR.

Stability Indicator/Materials to Avoid:YES HALOGENS, STRONG ACIDS, ALKALIS AND OXIDIZERS.

Stability Condition to Avoid:HEAT, SPRAKS, FLAME, AND BUILD-UP OF STATIC ELECTRICITY. DLA-HMIS: AVOID CONTACT WITH INCOMPATIBLE MATERIALS.

Hazardous Decomposition Products:CARBON MONOXIDE FROM INCOMPLETE COMBUSTION.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

Waste

Disposal Methods:PRODUCT IS SUITABLE FOR BURNING AS FUEL VALUE IN COMPLIANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. EPA/RCRA HAZARDOUS WASTE NUMBER D001 (IGNITABLE) (FLASHPOINT