View NSN Online: https://aerobasegroup.com/nsn/5330-00-658-8086

GARLOCK INC -- 7021, COMPRESSED ASBESTOS SHEETS -- 5330-00-658-8086

Product ID:7021, COMPRESSED ASBESTOS SHEETS MSDS Date:04/13/1987 FSC:5330 NIIN:00-658-8086 **MSDS Number: BPMHF** === Responsible Party === Company Name: GARLOCK INC Address:1666 DIVISION ST City:PALMYRA State:NY ZIP:14522-9343 Country:US Info Phone Num:315-597-4811;315-597-3061 **Emergency Phone Num:3** 15-597-4811 Preparer's Name:H.R. HUGHES CAGE:76380 === Contractor Identification === **Company Name: GARLOCK INC** Address:1666 DIVISION ST Box:City:PALMYRA State:NY ZIP:14522 Country:US Phone:315-597-4811 CAGE:76380 Company Name: GARLOCK INC MECHANICAL PACKING DIV Address:1666 DIVISION ST City:PALMYRA State:NY ZIP:14522-9343 Country:US Phone:315-597-4811 CAGE:73680

======= Composition/Information on Ingredients ==========

Ingred Name:ASBESTOS, CHRYSOTILE-, (CHRYSOTILE (WHITE) ASBESTOS) C

AS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 80-90% OSHA PEL:0.2 FIBERS/CC ACGIH TLV:0.2 FIBERS/CC

Ingred Name:OTHER PREC: PREC, NIOSH/MSHA APPRVD HALF FACE RESP W/HEPA FILTERS SHOULD BE WORN BY INDIVIDUALS WHEN ENGAGED IN (ING 3) RTECS #:9999999ZZ

Ingred Name: ING 2: REMOVAL OF USED GASKETS. RTECS #:99999992Z

Ingred Name:VENT: FIBERS, SUFFICIENT VENTILATION SHOULD BE PROVIDED TO KEEP FIBER LEVEL BELOW 0.2 FIBERS PER CC. RTECS #:9999999ZZ

======= Hazards Identificati

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: PROD DOES NOT POSE HLTH HAZ UNDER ORDINARY CNDNTS OF USE. HAZ WOULD ARISE ONLY IF PROD WERE SUBJECTED TO MECH ACTIONS THAT WOULD CAUSE ASBESTOS FIBERS TO BE RELEASED FROM ELASTOMER COMPOUND MATRIX. IN HAL OF SUCH AIRBORNE FIBERS CAN CAUSE WELL-KNOWN LONG TERM EFTS OF ASBESTOSIS, LUNG CANCER & (EFTS OF OVEREXP) Explanation of Carcinogenicity: CHRYSOTILE: GROUP 1(NTP, IARC) OSHA REGULATED. Effects of Overexposure: HLTH HAZ: MESOTHELIOMA. INGEST: FREE ASBESTOS FIBERS MAY BE A FACTOR IN CANCERS OF GI TRACT & LARYNX. SUCH CANCERS ARE BELIEVED TO BE SMOKING RELATED. SKIN/EYE CONT: SIMPLE **IRRITATION IN SENSITIVE IND IVIDUALS.** Medical Cond Aggravated by Exposure: INHALING FREE ASBESTOS FIBERS MAY AGGRAVATE ANY LUNG CONDITIONS AND RESPIRAT ORY TRACT IRRITATIONS.

First Aid:INHAL: REMOVE FROM CONTAMD AREA. REPORT EXPOSURE TO MED PERSONNEL. INGEST: NO SPECIFIC ACTION. REPORT EXPOSURE TO MED PERSONNEL. SKIN: WASH AREA OF CONT THORO WITH SOAP AND WATER. CONTACT PHYS IF IRRI TATION PERSISTS. EYE: IRRIGATE WELL WITH WATER FOR AT LEAST 15 MIN. CONTACT PHYS AS A PRECAUTION.

Extinguish

ing Media:WATER, FOAM, CO\*2, DRY CHEMICAL. Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard: PRODUCES SMOKE, SOME FUMES AND POSSIBLY SOME FREE ASBESTOS FIBERS WHEN BURNED. Spill Release Procedures:WET WASTE, VACUUM UP ANY WASTE WITH HEPA FILTERED VACUUM CLEANER. WEAR PROTECTIVE EQUIPMENT AND NIOSH/MSHA APPROVED HALF FACE RESPIRATOR WITH HEPA FIL TERS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: STORE IN CLEAN, DRY PLACE AWAY FROM STRONG OXIDIZING AGENTS. NORMAL WASH UP AFTER HANDLING IS RECOMMENDED. Other Precautions: ASBESTOS BONDED BY AN ELASTOMER CMPD, HOWEVER, DO NOT MISUSE BY IMPROPER CUTTING/HNDLG. SEE OSHA REGS 29CFR1910. WHEN **REMOVING USED GASKETS, AVOID EXCESSIVE MECH ACTIONS & PLACE** ASBESTOS CNTNG RE SIDUE S IN PLASTIC BAG FOR DISP. AS (ING 2) Respiratory Protection: NOT REQD UNDER NORM CNDTNS OF USE. IF ANY OPERATIONS ARE PERFORMED ON PRODUCT THAT MAY RELEASE ASBESTOS FIBERS, USE A NIOSH/MSHA APPRVD HALF FACE RESPIRATOR WITH HEPA FILTERS. Ventilation: NO SPECIAL REQUIREMENTS UNDER NORM CNDNTS OF USE. IF ANY OPERATIONS ARE PERFORMED ON PROD THAT MAY REL ASBESTOS (ING 4) Protective Gloves: IMPERVIOUS GLOVES. Е ve Protection: CHEMICAL WORKERS GOGGLES . Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: NORMAL WASH UP AFTER HANDLING IS RECOMMENDED. Supplemental Safety and Health HAZ DECOMP: THERE MAY BE OTHER PROD UNKNOWN TO MFR. WASTE DISP METH: DUST SHOULD BE WETTED & VACUUMED UP W/HEPA FILTERED VACUUM CLEANER, SEALED IN PLASTIC BAG & DISPOSED OF I/A/W INSTRUCTION FROM DISP COMPANY. USER IS RESPONSIBLE FOR COMPLYING W/ANY LOCAL, STATE **OR FEDERAL REGULATIO** 

NS.

Solubility in Water:NEGLIGIBLE Appearance and Odor:GREY-BLACK TO BLACK SHEET OR GASKET-SLIGHT ODOR.

Stability Indicator/Materials to Avoid:YES

AVOID STORAGE WITH STRONG OXIDIZING AGENTS. DIRECT FLAME WILL IGNITE BINDER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:IN FIRE: SMOKE, POSS CO UNDER CERTAIN

CIRCUMSTANCES. SOME ASBESTOS FIBERS MAY BE REL ONCE BINDER HAS BURNED. (SUPP DATA)

Waste Disposal Methods:SINCE ASBESTOS IN PROD IS SECURED W/BINDER & IS NOT FRIABLE/LOOSE, PROD CAN BE DISPOSED OF W/OTHER INERT MATL IN NORM LANDFILL. GRIND/MACHINING OF PROD SHOULD BE AVOIDED SINCE THESE/SIMILAR OPERATIONS MAY GENERATE ASBESTOS DUST. ANY SUCH (SUPP DATA)

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.