View NSN Online: https://aerobasegroup.com/nsn/4910-01-210-1978

Product ID:NA1270, MAN845 HONING OIL MSDS Date:08/15/1987 FSC:4910 NIIN:01-210-1978 **MSDS Number: BPMLP** === Responsible Party === Company Name: SUNNEN PRODUCTS CO Address:7910 MANCHESTER AVE **City:ST LOUIS** State:MO ZIP:63143-2712 Country:US Info Phone Num:312-781-2105 Emergency Phone Num:314-781-21 05 Preparer's Name: TERRY HELLER CAGE:58436 === Contractor Identification === Company Name: SUNNEN PRODUCTS CO Address:7910 MANCHESTER AVE Box:City:SAINT LOUIS State:MO ZIP:63143-2712 Country:US Phone:314-781-2100 CAGE:58436

Ingred Name:GAS OIL, BLEND; (REFINED MINERAL OIL) CAS:64741-44-2 RTECS #:LX3296000 Fraction by Wt: >99% Other REC Limits:5 MG/M3 MIST (MFR)

Ingred Name:SUPDAT:FOR USE IN/AROUND HOUSEHOLD/DWELLING. ALL

PRECAUTIONS DETAILED ON CONTR LBL APPLY TO PARTIALLY FULL/EMPTY (ING 3) RTECS #:9999999ZZ

Ingred Name:ING 2:CONTRS. DO NOT ATTEMPT TO CLEAN AS RESIDUE IS DFCLT TO REMOVE. EMPTY DRUMS SHOULD BE COMPLETLY DRAINED, (ING 4) RTECS #:9999999ZZ

Ingred Name:ING 3:PROPERLY CLSD & RETURNED TO A DRUM CONDITIONER TO BE COMMERCIALLY CLEANED. OTHERWISE, CONTRS SHOULD BE (ING 5) RTECS #:9999999ZZ

Ingred Name:ING 4:DISPOSED OF IN ENVIRONMENTALLY SAFE MANNER AND IN ACCORDANCE WITH APPLICABLE G OVERNMENTAL REGULATIONS. RTECS #:9999999ZZ

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:SKIN:PROLONGED OR REPEATED CONTACT WITH MATERIAL MAY LEAD TO IRRITATION CAUSED BY DISSOLVING OF NATURAL OILS FROM SKIN CAUSING SLIGHT SKIN IRRITATION. INGEST:SLIGHTLY TOXIC - B ASED ON TESTING OF SIMILAR PRODUCTS (EFTS OF OVEREXPOS) Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:HLTH HAZ:AND/OR COMPONENTS. EYE:EXPECTED TO BE NON-IRRITATING - BASED ON TESTING OF SIMILAR PRODUCT AND/OR COMPONENTS. INHAL:NOT ESTABLISHED. CHRONIC:NO APPLICABLE

INFORMATION FOUND.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:INHAL:REMOVE FROM FURTHER E XPOS. IF UNCONSCIOUSNESS OCCURS.

SEEK IMMED MED ASSIST & CALL MD. IF BRTHG HAS STOPPED, BEGIN MOUTH TO MOUTH RESUSCITATION. EYE:REMOVE CONTACT LENSES (IF WEARING) & FLUSH EY ES W/WATER FOR AT LEAST 15 MIN. SEEK MDATTN TO CHECK FOR POSS IRRIT. SKIN:WASH CONT AREAS W/ MILD NON-ABRASIVE SOAP & WATER. INGEST:DO NOT INDUCE VOMIT. ADMIN VEGETABLE OIL. GET MD ASSIST. (SUPDAT)

Flash Point Method:COC Flash Poin t:245F,118C Lower Limits:0.6% Upper Limits:7% Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG. Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard: SEALED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT. Spill Release Procedures: ABSORB ON FIRE RETARDANT ABSORBANT. GATHER AND DISPOSE IN ACCORDANCE WITH APPLICABLE REGULATIONS. NOTIF Y COAST GUARD IF SPILL COULD REACH ANY WATERWAY (1-800-424-8802) Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: STORE AWAY FROM HEAT/FLAME. IF STORED OUTDOORS, STORE SO AS TO SHED WATER. Other Precautions:NORMAL USE:MAY CAUSE SKIN IRRIT AND/OR DEFAT SKIN ON PRLNG/RPTD CONT. AVOID WEARING CLTHG SOAKED W/FLUID. AVOID PRLNGD INHAL OF MIST/VAP. DO NOT TRANSFER TO UNLBL CONTRS. D **O NOT REUSE** CONTRS FOR OTHER MATL/PURPOSES. DO NOT CUT, (SUPDAT) Respiratory Protection: IF USE CONDITIONS GIVE RISE TO EXCESSIVE MIST (>5 MG/M3) USE NIOSH/MSHA APPROVED RESPIRATOR RATED FOR MINERAL OIL MIST OR FORCED VENTILATION TO REDUCE MIST EXPOSURE TO WELL BELOW TLV LEVELS. Ventilation:LOCAL:NORMAL. MECHANICAL:REQUIRED IF USE CONDITIONS GIVE RISE TO LEV >5 MG/M3. Protective Gloves: IMPERVIOUS GLOVES . Eye Protection: CHEMICAL WORKERS GOGGLES . Other Protective Equipment:OIL IMPERVIOUS APRON IF DESIRED. Work Hygienic Practices: PRACTIVE GOOD PERSONAL HYGIENE BY WASHING HANDS SEVERAL TIMES EACH DAY. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health MATL TO AVOID:SOAP AND/OR EMULSIONS. FIRST AID PROC:NOTE TO MD:MATERIAL IF ASPIRED INTO LUNGS MAY CAUSE CHEMICAL PNEUMONITIS. TREAT APPROPRIATELY. OTHER PREC:BRAZE, WELD, SOLDER/PRESS CONTR AS DOING S O MAY CAUS

E CONTR TO EXPLODE, POTENTIALLY CAUSING SERIOUS INJURY/DEATH. FOR INDUSTRIAL USE ONLY. NOT SUITABLE (ING 2)

Boiling Pt:B.P. Text:>600F,>316C Vapor Pres: