View NSN Online: https://aerobasegroup.com/nsn/9150-00-292-9657

TEXACO REFINING AND MARKETING INC. -- 01562, CAPELLA WF 68 -- 9150-00-292-9657

Product ID:01562, CAPELLA WF 68

MSDS Date:11/12/1997

FSC:9150

NIIN:00-292-9657

MSDS Number: BPMRY === Responsible Party ===

Company Name: TEXACO REFINING AND MARKETING INC.

Address:1111 RUSK STREET

Box:4427

City:HOUSTON

State:TX

ZIP:77210-4427

Country:US

Info Phone Num:713-650-5206/800

-782-7852

Emergency Phone Num:713-650-5206, CHEMTREC 800-424-9300

CAGE:2R503

=== Contractor Identification ===

Company Name: B&M ENTERPRISES

Address:17350 TEMPLE AVE

Box:City:LA PUENTE

State:CA ZIP:91744 Country:US

Phone:818-912-1275

CAGE:097K0

Company Name: EMULTEC INDUSTRIAL PRODUCTS INC

Address:1150 HAYDEN DR SUITE 100

Box:City:CHARROLLTON

State:TX ZIP:75006 Country:US

Phone:972-417-1288

CAGE:0WA27

Company Name: SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA ZIP:70058 Country :US

Phone:504-366-4542

CAGE:0T5C6

Company Name: TEXACO LUBRICANTS

CAGE:TEXLU

Company Name: TEXACO REFINING AND MARKETING INC

Address:1111 RUSK ST Box:City:HOUSTON

State:TX

ZIP:77002-3310 Country:US

Phone:713-650-5206

CAGE:2R503

======= Composition/Information on Ingredients ========

Ingred Name: DISTILLATES, ACID-TREATED HEAVY NAPHTHENIC

CAS:64742-18-3 RTECS #:PY8032000 Fraction by Wt: 80-94.9%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name:MINERAL

OIL

CAS:64742-53-6

RTECS #:PY8036000 Fraction by Wt: 10-19.9%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

========== Hazards Identification ===========================

LD50 LC50 Mixture:LD50 (ORAL RAT) IS >5G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:MAY CAUSE MINIMAL IRRITATION,

EXPERIENCED AS TEMPORARY DISCOMFORT. SKIN:NO ADVERS

E EFFECTS

EXPECTED. BRIEF CONTACT IS NOT IRRITATING. INGESTION:NO ADVERSE EFFECTS EXPECTED.

Explanation of Carcinogenicity: NOT A CARCINOGEN.

Effects of Overexposure:SKIN-MAY CAUSE DEEFATTING OF SKIN OR IRRITATION, SEEN AS REDNESS WITH POSSIBLE MILD DISCOMFORT. INHALATION-MAY CAUSE IRRITATION OF THE NOSE AND THROAT, HEADACHE, NAUSEA AND DROWSINESS. INGESTION-IF MO RE THAN SEVERAL MOUTHFULS ARE SWALLOWED, ABDOMINAL DISCOMFORT, NAUSEA AND DIARRHEA MAY OCCUR.

Medical Cond Agg

ravated by Exposure:BECAUSE OF ITS DEFATTING PROPERTIES, PROLONGED & REPEATED SKIN CONTACT MAY AGGRAVATE AN EXISTING DERMATITIS (SKIN CONDITION).

First Aid:EYES-FLUSH EYES WITH PLENTY OF WATER FOR SEVERAL MINUTES. GET MEDICAL ATTENTION. SKIN-WASH SKIN WITH PLENTY OF SOAP & WATER FOR SEVERAL MIN. GET MEDICAL ATTENTION. INGESTION-IF MORE THAN SEVERAL MOUTH FULS HAVE BEEN SWALLOWED, GIVE 2 GLASSES OF WATER. G

MEDICAL ATTENTION. INHALATION-IF IRRITATION, HEADACHE, NAUSEA OR DROWSINESS OCCURS, REMOVE TO FRESH AIR. GET MEDICAL ATTENTION.

========== Fire Fighting Measures ============

Flash Point Method:COC

Flash Point:355F,179C

Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures: USE WATER TO COOL FIRE EXPOSED CONTAINERS. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISP ERSE THE

VAPORS AND TO PROVIDE PROTECTION.

Unusual Fire/Explosion Hazard:NONE.

========= Accidental Release Measures ===========

Spill Release Procedures: VENTILATE AREA. AVOID BREATHING VAPOR. USE SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED AIR FOR LARGE SPILLS OR CONFINED AREAS. CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL & SH OVEL UP. PREVENR ENTRY INTO SEWERS.

Han

dling and Storage Precautions:MINIMUM FEASIBLE HANDLING TEMPERATURES SHOULD BE MAINTAINED. WATER CONTAMINATION SHOULD BE AVOIDED.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: AIRBORNE CONCENTRATIONS SHOULD BE KEPT TO LOWEST LEVEL POSSIBL

E. IF VAPOR, MIST OR DUST IS GENERATED, USE RESPIRATOR
APPROVED BY MSHA OR NIOSH AS APPROPIATE. SUPPLIED AIR RESPIRATORY
PROTECTION SHOULD BE USED FOR CLEANING LARGE SPILLS.

Ventilation: ADEQUATE TO MEET OCCUPATIONAL EXPOSURE LIMITS.

Protective Gloves: WASH SKIN SEVERAL TIMES DAILY.

Eye Protection: CHEMICAL-TYPE GOGGLES OR FACE SHIELD.

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices: SOILED CLOTHING SHOULD BE LAUNDERED OR DRY-CLEANED AT LEAST ONCE

A WEEK.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

=========== Physical/Chemical Properties ==========

HCC:V6

Spec Gravity:0.895 Viscosity:64.6 CST

Appearance and Odor:CLEAR, LIGHT PALE OIL; BLAND ODOR.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: NONE SPECIFIED BY

MANUFACTURER.

Hazardous Decomposition Products:TOXIC LEVELS OF CARBON MONOXIDE, CARBON DIOXIDE, IRRITATING ALDEHYDES AND KETONES.

======= Disposal Considerations ===========

Waste Disposal Methods:THIS PRODUCT HAS BEEN EVALUATED FOR RCRA CHARACTERISTICS & DOES NOT MEET THE CRITERIA OF A HAZARDOUS WASTE IF DISCARDED IN ITS PURCHASED FORM. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE AT THE TIME OF DISPOSAL IF MATERIAL IS HAZARDOUS.

Disclaimer

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.