

DETROIT DIESEL CORP -- 5124796 -- 5330-00-758-2883

===== Product Identification =====

Product ID:5124796

MSDS Date:12/09/1992

FSC:5330

NIIN:00-758-2883

MSDS Number: BPMTJ

=== Responsible Party ===

Company Name:DETROIT DIESEL CORP

Address:13400 W OUTER DR /SPEED CODE N-53/

City:DETROIT

State:MI

ZIP:48239-4001

Country:US

Info Phone Num:313-592-5100

Emergency Phone Num:313-592-5100

Preparer's Name:H

MIS TECHNICIAN

CAGE:72582

=== Contractor Identification ===

Company Name:DETROIT DIESEL CORP, CORPORATE HQ

Address:13400 W OUTER DR /SPEED CODE N-53/

Box:City:DETROIT

State:MI

ZIP:48239-4001

Country:US

Phone:313-592-5100/5665

CAGE:72582

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

===== Hazards Identi

fication =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &
MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE
LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER
OF THE BOWEL.

Expl
anation of Carcinogenicity:ASBESTOS IS A KNOWN HUMAN CARCINOGEN.
Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH
THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.
DIARRHEA, VOMITING, AND NA USEA.
Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA, AND TUBERCULOSIS
ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

===== First Aid Measures =====
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE
THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH
THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.
INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCTOR.

===== Fire Fighting Measures =====

Flash Point:NOT REQUIRED
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FIRE F
IGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED
VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE
RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE
MATERIAL WITH WATER

& SURFACTANT AND THEN SHOVEL OR MOP UP
CONTAMINATION.

=====
Handling and Storage
=====

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED
FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED
BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE
INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED
ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL
LOCAL, STATE AND FEDERAL REGULATIONS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF
REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR
HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE
EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves:COTTON OR LEATHER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS
AFTER HANDLING ITEM. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN. WHEN HMIS IS ABLE TO OBTAIN AN MSDS
FROM MANUFACTURER, THIS RECORD WILL BE UPDATED. MANUFACTURER SAYS
NO ASBESTOS IN GASKETS SINCE APRIL 1988; PRIOR TO THAT YES.

=====
Physical/Chemical Properties
=====

HCC:T6

Solubility in Water:INSOLUBLE

Appearance and Odor:GASKET

Percent Volatiles by Volume:0

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid:ACCUMULATIONS OF DUST

Hazardous Decomposition Products:ASBESTOS DUST

=====
Disposal Considerations
=====

Waste Disposal Methods:WET THE MATERIAL WITH WATER

ATER AND SURFACTANT.

PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information t

o be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.