

UNITED RESIN CORPORATION -- HIGH HEAT SURFACE COAT, 2X21C -- 8040-00-944-7292

===== Product Identification =====

Product ID:HIGH HEAT SURFACE COAT, 2X21C

MSDS Date:04/29/1991

FSC:8040

NIIN:00-944-7292

Kit Part:Y

MSDS Number: BPPDJ

=== Responsible Party ===

Company Name:UNITED RESIN CORPORATION

Address:4359 NORMANDY COURT

City:ROYAL OAK

State:MI

ZIP:48073

Country:US

Info Phone Num:313-549-8200

Eme

rgency Phone Num:313-549-8200

CAGE:1FD35

=== Contractor Identification ===

Company Name:UNITED RESIN CORPORATION

Address:4359 NORMANDY COURT

City:ROYAL OAK

State:MI

ZIP:48073

Country:US

Phone:248-549-8200/

CAGE:1FD35

===== Composition/Information on Ingredients =====

Ingred Name:BISPHENOL A/EPICHLOROHYDRIN

CAS:25068-38-6

Other REC Limits:NONE SPECIFIED

Ingred Name:DIGLYCIDYL ETHER (SARA III)

CAS:17557-23-2

RTECS #:TX3760000

Other REC Limits:NONE SPECIFIED

ACGIH TLV:10 MG/M3

Ingred Name:ALUMINUM OXIDE (SARA III)
CAS:1344-28-1
RTECS #:BD1200000
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:FIBERGLASS FIBERS
CAS:65997-17-3
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3
ACGIH TLV:10 MG/M3

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN CONTACT: MAY RESULT IN IRRITATION
OR CHEMICAL BURN. EYE CONTACT
T: PRODUCT CAN CAUSE SEVERE EYE
IRRITATION, SWELLING AND/OR CHEMICAL BURN. CONTACT LENSES SHOULD
NOT BE WORN WHEN WORKING WITH THIS MATERIAL. INHALATION:
IRRITATING TO UPPER RESP SYSTEM. INGESTION LOW ORAL TOXICITY.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/GENEROUS
AMOUNTS OF WATER 15 MINUTES. GET MEDICAL ATTENTION IF IT APPEARS
NECESSARY. SKIN: IMMEDIATELY WASH SKIN W/SOAP & WATER. WASH

CONTAMINATED CLOTHING BEFORE REUSE. INGESTION: IF SWALLOWED DO NOT
INDUCE VOMITING. GIVE LARGE AMOUNTS OF WATER OR MILK IF AVAILABLE.
CALL DR. TREATMENT BASED ON JUDGEMENT OF DR IN RESPONSE TO
REACTIONS OF PATIENT.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:>200F,>93C
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL, CO2.
Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL
PROTECTIVE GEAR INCLU

DING POSITIVE PRESSURE NIOSH APPROVED SCBA.

COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:CONTAINER AREAS EXPOSED TO INTENSE HEAT OR FLAME SHOULD BE COOLED WITH H2O TO PREVENT PRESSURE BUILDUP AND/OR WEAKENING OF CONTAINER STRUCTURE.

===== Accidental Release Measures =====

Spill Release Procedures:USE CAUTIOUS JUDGEMENT WHEN CLEANING SPILLS.

SMALL: COLLECT WITH ABSORBENT (CLAY/SAND). LARGE: DIKE, CONTAIN W/ABSORBENT. FLUS

H W/WATER SPRAY TO REMOVE RESIDUE. DISPOSE OF FLUSH LEGALLY.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT AMBIENT TEMPERATURES IN VENTED AREA. AVOID IGNIT SOURCE/HEAT. STORE SEPARATELY FROM AMINE CURING AGENTS. PROTECT CNTNR FROM PHYSICAL DAMAGE.

Other Precautions:CNTNRS, EVEN EMPTIED, CAN CONTAIN HZD RESIDUES.

HANDLE IN ACCORD W/GOOD INDUSTRIAL PRACTICES. AVOID PROLONGED OR REPEATED CONTACT W/SKIN. WASH WITH SOAP/WATER BEFORE EATING, DRINKING, SMOKING, APPLYIN G COSMETICS, OR USING TOILET FACILITES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATORY PROTECTION WHERE EXPOSURE LIMITS ARE EXCEEDED OR IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL.

Ventilation:USE ONLY W/VENT. LOCAL EXHAUST IS RECOMMENDED. MECHANICAL EXHAUST CAN BE USED AS A BACK-UP SYSTEM.

Protective Gloves:CHEMICAL RESISTANT GLOVES (RUBBER/PVA)

E

Eye Protection:SAFETY GLASSES OR GOGGLES W/SIDE SHIELDS

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS REQUIRED TO MINIMIZE SKIN CONTACT.

Work Hygienic Practices:LAUNDER CONTAMINATED CLOTHING BEFORE USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres: