

HULS AMERICA INC. -- MIL-H-46170B TYPE 2

=====  
MSDS Safety Information  
=====

FSC: 9150  
NIIN: 01-131-3325  
MSDS Date: 02/21/1991  
MSDS Num: BPPFJ  
Product ID: MIL-H-46170B TYPE 2  
MFN: 02  
Responsible Party  
Cage: 0DH22  
Name: HULS AMERICA INC.  
Address: TURNER PLACE,  
Box: 365  
City: PISCATAWAY NJ 08854  
Info Phone Number: 201-763-7173  
Emergency Phone Number: 201-763-7173  
Proprietary Ind: Y  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 0DHB8  
Name: HUL AMERICA INC  
Address: TURNER PLACE  
Box: 365  
City: PISCATAWAY NJ 08854-0365  
Phone: 201-763-7173  
Cage: 0DH22  
Name: HULS AMERICA INC  
Address: TURNER PLACE  
Box: 365  
City: PISCATAWAY NJ 08854-0365  
Phone: 908-981-5016  
Cage: 63182  
Name: HU

LS AMERICA INC  
Address: TURNER PLACE  
Box: 365  
City: PISCATAWAY NJ 08855  
Phone: 201-763-7173

=====  
Item Description Information  
=====

Item Manager: S9G  
Item Name: HYDRAULIC FLUID,FIRE RESISTANT  
Specification Number: MIL-H-46170B  
Type/Grade/Class: TYPE II  
Unit of Issue: CN  
Quantitative Expression: 00000000005GL  
UI Container Qty: 0  
Type of Container: CAN  
=====

=====  
Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----  
=====

=====  
Health Hazards Data  
=====

LD50 LC50 Mixture: UNKNOWN  
Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Ingestion: NO  
Carcinogenicity Inds - NTP: NO  
IARC: NO  
OSHA: NO  
Effects of Exposure: ACUTE- LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION, NAUSEA, VOMITING. BARIUM COMPOUND IS A MODERATE SKIN IRRITANT AND IS CORROSIVE TO EYES. CHRONIC- NONE KNOWN.  
Signs And Symptoms Of Overexposure: LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION, NAUSEA, VOMITING. BARIUM COMPOUND IS A MODERATE SKIN IRRITANT AND IS CORROSIVE TO EYES.  
Medical Cond Aggravated By Exposure: PRE-EXISTING SKIN DISORDERS MAY BE M

ORE

SUSCEPTIBLE TO THIS MATERIAL.

First Aid: CONSULT PHYSICIAN IF SYMPTOMS PERSIST. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER.

INHALATION:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. INGESTION:DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

=====  
Handling and Disposal  
=====

Spill Release Procedures: WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF

IGNITION. VENTILATE THE AREA. CONTAIN THE SPILL. PICK UP LARGE SPILL WITH NON-SPARKING TOOLS; SMALL SPILLS/RESIDUE WITH INERT ABSORBENT MATERIAL. PLACE IN CONTAINERS. PREVENT ENTERING WATERWAYS/SEWERS.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: STORAGE- STORE IN COOL, VENTILATED AREA. DO NOT USE OIL ABOVE THE MAXIMUM RECOMMENDED TEMPERATURE OF 430F.

Other Precautions: KEEP CONTAINER CLOSED.

WASH THOROUGHLY AFTER HANDLING. AVOID

CONTACT WITH EYES, SKIN AND CLOTHING. KEEP OUT OF REACH OF CHILDREN. MAY SOFTEN SOME PLASTIC AND PAINT SURFACES. WIPE UP SPILLS IMMEDIATELY .

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Method: COC

Flash Point Text: 430F,221C

Extinguishing Media: WATER FOG, CARBON DIOXIDE, FOAM OR DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard: CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

=====  
Control Measures  
=====

Respiratory Protection: WEAR NIOSH-APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES

R SELF CONTAINED BREATHING APPARATUS IF MATERIAL IS HEATED.  
Ventilation: MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)  
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).  
Protective Gloves: NATURAL RUBBER, NITRILE  
Eye Protection: SAFETY GOGGLES  
Other Protective Equipment: EYE WASH STATION, QUICK DRENCH SHOWER AND  
IMPERVIOUS CLOTHING  
Work Hygienic Practices: PRACTICE GOOD HYGIENIC PROCEDURE. WASH THOROUGHLY  
BEFORE EATING OR DRINKING. USE WITH ADEQUATE VENTILATION.  
Supplemental Safety and Health: FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE  
PNI A UNDER THE SAME NSN.

=====  
Physical/Chemical Properties  
=====

HCC: V6  
Decomp Text: UNKNOWN  
Spec Gravity: 0.842  
Solubility in Water: NEGLIGIBLE  
Appearance and Odor: RED LIQUID  
Corrosion Rate: UNKNOWN

=====  
Reactivity Data  
=====

Stability Indicator: YES  
Stability Condition To Avoid: EXCESSIVE HEAT  
Materials To Avoid: STRONG OXIDIZERS  
Hazardous Decomposition Products: TOXIC FUMES  
Hazardous Polymerization Indicator: NO  
Conditions To Avoid Polymerization: NOT RELEVANT

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====  
Transportation Information

on

=====  
Responsible Party Cage: 0DH22  
Trans ID NO: 109667  
Product ID: MIL-H-46170B TYPE 2  
MSDS Prepared Date: 02/21/1991  
Review Date: 12/22/1992  
MFN: 2  
Net Unit Weight: 35.1 LBS  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: CN  
Container QTY: 0  
Type Of Container: CAN  
=====

=====  
Detail DOT Information  
=====

DOT PSN Code: ZZZ  
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IMO Information  
=====

IMO PSN Code: ZZZ  
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ZZZ  
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail AFI Information  
=====

AFI PSN Code: ZZZ  
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
HAZCOM Label  
=====

Product ID: MIL-H-46170B TYPE 2  
Cage: 0DH22  
Company Name: HULS AMERICA INC  
Street: TURNER PLACE  
PO Box: 365  
City: PISCATAWAY NJ  
Zipcode: 08854-03

65

Health Emergency Phone: 201-763-7173

Label Required IND: Y

Date Of Label Review: 12/22/1992

Status Code: C

MFG Label NO: UNKNOWN

Label Date: 12/22/1992

Year Procured: 1993

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: ACUTE- LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION,

NAUSEA, VOMITING. BARIUM COMPOUND IS A MODERATE SKIN IRRITANT AND IS CORROSIVE TO EYES. CHRONIC- NONE KNOWN. STORAGE- STORE IN COOL, VENTILATED AREA. DO NOT USE OIL ABOVE THE MAXIMUM RECOMMENDED TEMPERATURE OF 430F. FIRST AID- CONSULT PHYSICIAN IF SYMPTOMS PERSIST. EYE: FUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN: WASH WITH SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

==

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.