

STANDARD OIL CO OF OHIO -- #2 DIESEL FUEL, UNBRADED; PRODUCT CODE P 14 --
9140-00-286-5294

=====
Product Identification
=====

Product ID:#2 DIESEL FUEL, UNBRADED; PRODUCT CODE P 14

MSDS Date:10/03/1985

FSC:9140

NIIN:00-286-5294

MSDS Number: BPQST

=== Responsible Party ===

Company Name:STANDARD OIL CO OF OHIO

Address:200 PUBLIC SQ

City:CLEVELAND

State:OH

ZIP:44114

Country:US

Info Phone Num:800-362

-8059

Emergency Phone Num:800-362-8059/800-424-9300(CHEMTREC)

CAGE:82250

=== Contractor Identification ===

Company Name:BP OIL COMPANY

Address:200 PUBLIC SQ

Box:City:CLEVELAND

State:OH

ZIP:44114-2375

Country:US

Phone:216-586-8023

CAGE:82250

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES

CAS:68476-30-2

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
Fire Fighting Measures
=====

Fla

sh Point:130F,54C

Autoignition Temp:Autoignition Temp Text:ND

Lower Limits:0.7

Upper Limits:5.0

Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, FOAM OR CARBON DIOXIDE TO EXTINGUISH FIRE. COOL FIRE EXPOSED CONTAINER WITH WATER SPRAY.

Fire Fighting Procedures:IF LEAK OR SPILL HAS NOT IGNITED, VENT AREA & USE WATER TO DISPERSE GAS OR VAPOR & TO PROTECT PERSONNEL. USE WATER TO FLUSH SPILL AWAY FROM IGNITION SOURCE.

Unusual Fire/Explosion Hazard:DANGEROUS WHEN EXPOSED TO HEAT/FLAME.

RUNOFF TO SEWER MAY CAUSE FIRE/EXPLOSION HAZARD. FIREFIGHTERS SHOULD WEAR MSHA/NIOSH APPROVED SCBA, WITH FULL FACE MASK.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:320F,160C

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:0.4 MMHG

Vapor Density:4.7 AIR=1

Spec Gravity:0.84-0.89

pH:7

Viscosity:2-3.6 CST

Evaporation Rate & Reference:SLOW

ER (WATER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:STRAW COLORED LIQUID WITH HYDROCARBON ODOR.

Percent Volatiles by Volume:0%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZERS.

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements

of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.