

FISKE BROTHERS REFINING CO -- LUBRIPLATE NO. 107 -- 9150-01-088-7114

=====
Product Identification
=====

Product ID:LUBRIPLATE NO. 107

MSDS Date:05/01/1987

FSC:9150

NIIN:01-088-7114

MSDS Number: BPQWX

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

P

reparer's Name:ROBERT J. SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENTS. ACGIH TLV: 5 MG/M3, OIL MIST

(MFR)
ACGIH TLV:ING NAME

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRIT. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PREC, EXPOS TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED.
THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MIN AMTS (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ:ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH W/CLEAR WATER FOR AT LEAST 15 MIN/UNTIL IRRIT SUBSIDES. IF IRRIT PERSISTS CONSULT MD. SKIN:REMOVE ANY CONTAM CLTHG & WASH W/SOAP & WARM WATER. IF INJECTED BY HIGH PRESS UNDER SKIN, REGARDLES S OF APPEARANCE OR ITS SIZE CNTCT MD IMMED. DELAY MAY CAUSE LOSS OF AFFECTED PART OF BODY. INHAL:VAP PRESS IS VERY LOW & INHAL AT ROOM TEMP IS NOT PROBLEM. IF OVERCOME BY VAP FROM HOT (SUPP DATA)

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:>360F,>182C
Lower Limits:0.
9%
Upper Limits:7%
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, OR WATER SPRAY (FOG)
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . COOL EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

=====
Accidental Release Measures
=====

Spill Release Procedures:SCRAPE UP

GREASE, WASH REMAINDER WITH SUITABLE
PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF
SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED
OR MAY ENTER SEWER S AND WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG
OXIDANTS.

Othe
r Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRER BEFORE REUSE.
CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. WEAR NIOSH/MSHA APPROVED
RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:USE TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES, IF NEEDED.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:USE OIL-RESISTANT APRON, IF N
EEDED.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:SUPP DATA

Evaporation Rate & Reference: