

HULS AMERICA INC -- MIL-L-6085B/PQ RUST PREVENTIVE 160 -- 9150-00-753-4667
===== Product Identification =====

Product ID:MIL-L-6085B/PQ RUST PREVENTIVE 160

MSDS Date:01/16/1989

FSC:9150

NIIN:00-753-4667

MSDS Number: BPRJY

=== Responsible Party ===

Company Name:HULS AMERICA INC

Address:80 CENTENNIAL AVE

Box:456

City:PISCATAWAY

State:NJ

ZIP:08855-0456

Country:US

Info Phone Num:201-980-6800

Emergenc

y Phone Num:201-980-6800

Preparer's Name:P.A. PARKER

CAGE:63182

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

===== Composition/Information on Ingredients =====

Ingred Name:SULFONIC ACIDS,PETROLEUM,SODIUM SALTS

CAS:68608-24-4

Fraction by Wt: 100.0%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Route

s of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:LOW ORAL AND DERMAL
TOXICITY;MIST OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE AND
SKIN IRRITATION,NAUSEA, VOMITING,RESPIRATORY TRACT IRRITATION.
Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS
CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.
Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, NAUSEA,
VOMITI
NG, RESPIRATORY TRACT IRRITATION.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

=====
===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH PLENTY OF
WATER FOR ABOUT 15-20 MINUTES; SEEK MEDICAL HELP. INHALATION:
REMOVE TO FRESH AIR; SEEK MEDICAL HELP. INGESTION: DO NOT INDUCE
VOMITING, CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Po
int Method:COC
Flash Point:440F/227C
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM OR CARBON DIOXIDE
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN
CLOSED CONTAINERS;COOL WITH WATER SPRAY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL
IGNITION SOURCE
S;CONTAIN FREE MATERIAL;USE SUITABLE INERT ABSORBENT
MATERIAL AND RECOVER FOR PROPER DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AND WELL VENTILATED
AREA. OPERATING TEMPERATURES BELOW 440F; DO NOT USE ABOVE THIS
TEMPERATURE.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
===== Exposure Controls/Personal Protection =====

Resp

iratory Protection:NORMALLY NOT NEEDED;IF OVER HEATED;USE
NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE
PEL/TLV.

Ventilation:USE LOCAL/GENERAL TO MAINTAIN ADEQUATE CFM.

Protective Gloves:IMPERVIOUS.

Eye Protection:CHEMICAL GOGGLES/FACESHIELD.

Other Protective Equipment:EYE-WASH FOUNTAIN, SAFETY SHOWER.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT
AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health

AVOID EYE/SKIN CONTACT.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>450F/232C

Vapor Pres:1.0

Spec Gravity: