View NSN Online: https://aerobasegroup.com/nsn/8010-00-807-7497

Product ID:Q-MAX A27 MSDS Date:01/01/1991 FSC:8010 NIIN:00-807-7497 MSDS Number: BPRKD === Responsible Party === **Company Name: MAVIDON CORPORATION** Address:3953 SW BRUNER TERRACE City:PALM CITY State:FL ZIP:34990 Country:US Info Phone Num:407-286-8951 Emergency Phone Num:407-286-8951 OR 800-535-5053 CAGE:MO005 = == Contractor Identification === Company Name: MAVIDON CORP Address:3953 BRUNER TERRACE Box:City:PALM CITY State:FL ZIP:34990 Country:US Phone:407-286-8951 CAGE:0EUM3 Company Name: MAVIDON CORPORATION Address:3953 SW BRUNER TERRACE Box:City:PALM CITY State:FL ZIP:34990 Country:US Phone:407-286-8951 CAGE:MO005

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Other REC Limits:NONE SPECIFIED OSHA P EL:100 PPM ACGIH TLV:100 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

LD50 LC50 Mixture:NOT KNOWN

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED CONTACT WITH SKIN WILL DRY AND DEFAT THE SKIN,LEADING TO DERMATITIS.REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANE

NT BRAIN AND NERVOUS SYST EM DAMAGE.INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENT MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN:CONTACT MAY CAUSE

IRRITATION.INHALATION:EFFECTS OF HIGH VAPOR CONCENTRATIONS MAY RANGE FROM DIZZINESS AND HEADACHES TO UNCONSCIOUSNESS. Medical Cond Aggravated by Exposure:NOT KNOWN

First Aid:EYES:FLUSH WITH LARGE AMO UNTS OF WATER FOR AT LEAST 15 MINUTES . SKIN:REMOVE CONTAMINATED CLOTHING,WASH SKIN WITH SOAP AND WARM WATER. INGESTION:DO NOT INDUCE VOMITING.CALL PHYSICIAN. INHALATION :REMOVE FROM EXPOSURE IMMEDIATELY.CALL PHYSICIAN.IF BREATHING IS IRREGULAR OR STOPPED,START RESUSCITATION,ADMINISTER OXYGEN.

Flash Point Method:TCC Flash Point:75F,23C Lower Limits:1% Upper Limits:7% Extinguishing Media:CARBON DIOXIDE,DRY

CHEMICAL,OR REGULAR FOAM. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA) AND FULL TURNOUT GEAR .COOL EXPOSED CONTAINERS WITH WATER SPRAY,AVOID BREATHING VAPOR OR FUMES. Unusual Fire/Explosion Hazard:DO NOT MIX WITH STRONG OXIDANTS LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN.
======================================
Spill Release Procedures: ELIMINATE IGNITION SOURCES, KEEP PEOPLE AWAY, RECOVER FREE LIQUID, ADD ABSORBENT (SAND, EART H, SAWDUST). AVOID BREATHING VAPORS. VENTILATE CONFINED SPACES. ALERT AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTE R SEWERS, WATERCOURSES OR EXTENSIVE LANDAREAS. Neutralizing Agent: NOT KNOWN
======================================
Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.DO NOT HANDLE OR STORE NEAR HEAT,SPARKS,FLAME OR STRONG OXIDANTS.ADEQUATE VENTILATION IS REQUIRED. Other Precautions:NOT KNOWN
Exposure Controls/Personal Protection ====================================
Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED. Ventilation:LOCAL EXHAUST:FACE VELOCITY >60 FPM. Protective Gloves:CHEMICAL RESISTANT GLOVES. Eye Protection:CHEMICAL SPLASH GOGGLES. Other Protective Equipment:SUFFICIENT CLOTHING TO PREVENT CONTACT WITH SKIN (CHEMICAL RESISTANT APRON).WASH CONTAMINATED SKIN WITH SOAP AND WATER. Work Hygienic Prac tices:AVOID BREATHING VAPORS,PROLONGED OR REPEATED CONTACT.REMOVE CONTAMINATED CLOTHING & SHOES,DRY SHOES BEFORE REUSE. Supplemental Safety and Health
VAPOR PRESSURE:25 MMHG AT 77F,25C.
======================================
Boiling Pt:B.P. Text:290F,143C Melt/Freeze Pt:M.P/F.P Text:90F,32C Decomp Temp:Decomp Text:NOT KNOWN Vapor Pres:SUP DATA Vapor Density:3.7(AIR=1) Spec Gravity:0.87 (WATER=1) Evaporation Rate & amp; Reference:0.7 (BUTYL ACETATE=1) Solubi

lity in Water:NEGLIGIBLE Appearance and Odor:WATER WHITE TO AMBER LIQUID WITH AROMATIC HYDROCARBON ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:NONE ESTABLISHED Hazardous Decomposition Products:FUMES,SMOKE AND CARBON MONOXIDE. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISPO SAL MUST BE IN ACCORDANCE WITH FEDERAL,STATE,AND LOCAL REGULATIONS.COORDINATE WITH SUPPORTING INSTALLATION AND/OR MACOM ENVIRONMENTAL OFFICE PRIOR TO DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person ut ilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.