

AMERON INC,PROTECTIVE LINING PRODUCT -- AMERCOAT 3203 WHITE F/S 27875 --
8010-01-344-5321

=====
===== Product Identification =====

Product ID:AMERCOAT 3203 WHITE F/S 27875

MSDS Date:01/30/1992

FSC:8010

NIIN:01-344-5321

MSDS Number: BPRRR

=== Responsible Party ===

Company Name:AMERON INC,PROTECTIVE LINING PRODUCT

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-
1951

Emergency Phone Num:800-424-9300

CAGE:55851

=== Contractor Identification ===

Company Name:AMERON INC,PROTECTIVE LINING PRODUCT

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:800-424-9300

CAGE:55851

=====
===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50: 1.6 G/KG. LC50: 510 PPM.

Health Hazards A

acute and Chronic:VAPOR OR SPRAY MIST CAN BE HARMFUL.

IRRITATING TO EYES, SKIN, NOSE & THROAT. EXCESSIVE INHALATION CAN CAUSE HEADACHE, NAUSEA, OR DIZZINESS. REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENT IS ASSOCIATED W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. CAN BE HARMFUL IF SWALLOWED. CAN BE HARMFUL IN INHALED. CAN BE *

Effects of Overexposure:* HARMFUL IF INHALED OR ABSORBED THROUGH THE SKIN. OVEREXPOSURE CAN DAMAGE LUNGS, CENTRAL NERVOUS SYSTEM.

OVERE

XPOSURE CAN CAUSE DELAYED LUNG INJURY.

Medical Cond Aggravated by Exposure:RESPIRATORY. SKIN.

===== First Aid Measures =====

First Aid:OVEREXPOSURE TO VAPOR/SPRAY MIST: PROVIDE FRESH AIR. IF BREATHING LABORED, GIVE OXYGEN/ARTIFICIAL RESPIRATION. SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SWALLOWED: DRINK 1-2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOM

ITING.

CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:95.0F,35.0C

Lower Limits:1.00

Upper Limits:8.00

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WEAR FULL PROTECTIVE EQUIPMENT, SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. KEEP FROM HEAT/IG

NIT SOURCE. VAPOR MAY

SPREAD LONG DISTANCES CAUSE FLASH FIRE/IGNITE EXPLOSIVELY.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING OF VAPORS. USE ABSORBENT CLEANUP MATERIALS. PLACE IN SEPARATE CONTAINER. KEEP OUT OF SEWERS AND WATERWAYS. IF ENTRY IS THREATENED OR OCCURS, NOTIFY LOCAL AUTHORITIES. ELIMINATE ALL SOURCES OF IGNITION.

===== Handling and Storage =====

Handling and Storage

e Precautions:KEEP CONTAINER CLOSED, UPRIGHT WHEN NOT IN USE. STORE IN COOL, DRY, WELL-VENTILATED AREA. AVOID STORAGE TEMPERATURES ABOVE 100 F.

Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED BREATHING OF VAPORS OR SPRAY MIST OR CONTACT WITH SKIN & EYES. DO NOT WELD OR FLAME CUT ON EMPTY CONTAINER. GROUND CONTAINERS WHEN POURING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA RESPIRATOR. FOR SPECIFIC CONDITIONS,

REFER TO NIOSH POCKET GUIDE TO CHEM HZDS. USE AIR-LINE RESPIRATORS IN CONFINED OR RESTRICTED VENTILATION AREAS. REFER TO 29 CFR, OSHA PARTS 1910 & 1915 FOR COATING OPERATIONS.

Ventilation:PROVIDE VENT TO KEEP AIR CONTAM CONC BELOW TLV. REMOVE WELDING/FLAME CUT DECOMP PROD. SEE 29CFR 1910/1915 COATING OPERTN

Protective Gloves:NEOPRENE, OR OTHER SUITABLE IMPERVIOUS

Eye Protection:SPLASH PROOF GOGGLES OR FACE SHIELD

Other Protective Equipment:FULL PROTECTIVE CLOTHING. SPARK-PROOF

EQUIPMENT.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING, SMOKING OR USING WASHROOM. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:252 TO 300F

Vapor Density:> AIR

Spec Gravity:11.2 LBS/GAL

Evaporation Rate & Reference:LOW.12 HIGH 1 (BU AC=1)

Appearance and Odor:LIQUID, SOLVENT ODOR.

Percent Volatiles by Volume:40

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, ACIDS, ALKALIES.

Stability Condition to Avoid:HEAT, OPEN FLAME, ARC OR SPARKS.

Hazardous Decomposition Products:CO AND CO2

===== Disposal Considerations =====

Waste Disposal Methods:IN SEPARATE, CLOSED METAL CONTAINER IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. EPA WASTE NO: D001.

Disclaimer (provided with this information by the compiling agencies):
This inform

ation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.