View NSN Online: https://aerobasegroup.com/nsn/9340-01-323-0527

Product ID:SCOTCHPLY SP377CU1 LOW ENERGY CURE COMPOSITE PREPREG MSDS Date:01/01/1990 FSC:9340 NIIN:01-323-0527 MSDS Number: BPSZG === Responsible Party === Company Name: MINNESOTA MINING/ADH COATINGS/SEALERS Address:3M CTR City:ST PAUL State:MN ZIP:55 144-1000 Country:US Emergency Phone Num:612-733-1110 CAGE:76381 === Contractor Identification === Company Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV Address:3M CTR Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:800-364-3577/651-737-6501(24 HOURS) CAGE:04963 Company Name: MINNESOTA MINING AND MFG CO, DBA 3M Address: 3M CENTER BLDG 224-5S-04 Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:866-556 5712 / 612-733-1110 CAGE:76381

======= Composition/In

formation on Ingredients ==========

Ingred Name:GLASS FABRIC Fraction by Wt: 55-70%

Ingred Name:2,2-BIS(4-(2,3-EPOXYPROPYLOXY)PHENYL)PROPANE, BISPHENOL A DIGLYCIDYL ETHER, EPON 828, EPOXIDE A CAS:1675-54-3 RTECS #:TX3800000 Fraction by Wt: 15-25%

Ingred Name:CURATIVES FOR EPOXY RESIN - TRADE SECRET Fraction by Wt: 10-20%

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IAR C:NO OSHA:NO Health Hazards Acute and Chronic:EYES: DUST FROM CUTTING/GRINDING/SANDING OF CURED PRODUCT MAY CAUSE IRRITATION. SKIN: ALLERGIES. INHALATION: IRRITATION OF RESPIRATORY SYSTEM. Explanation of Carcinogenicity:NONE Effects of Overexposure:SKIN: DUST FROM CUTTING, GRINDING, OR SANDING OF CURED PRODUCT MAY CAUSE IRRITATION.

First Aid:EYES: IMMEDATELY FLUSH W/PLENTY OF WATER. SKIN: THOROUGHLY WASH AFFEC

TED AREA W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Extinguishing Media:CO2, FOAM, DRY CHEMICAL Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.

Spill Release Procedures: OBSERVE PRECAUTIONS. COLLECT SPILLED MATERIAL. PLACE IN A CLOSED CONTAINERS.

====== Handlin

Handling and Storage Precautions: FOR INDUSTRIAL/PROFESSIONAL USE. AVOID CONTACT W/EYES, SKIN, INHALATION OF VAPORS. USE SUFFICIENT VENTILATION. KEEP FROM CHILDREN. Other Precautions: USE WATER AS LUBRICANT ON MACHINING TOOLS TO ELIMINATE DUST/IMPROVE MACHINABILITY OF CURED PARTS. STORE AT 72F OR BELOW TO MAINTAIN SHELF LIFE. ALLOW TO THOROUGHLY WARM TO ROOM TEMP. DON'T OPEN PROTEC TIVE CONTAINER BEFORE AMBIENT CONDITION. ======= E xposure Controls/Personal Protection ============ Respiratory Protection: WEAR DUST MASK TO AVOID DUST EXPOSURE. Ventilation:SUFFICIENT TO REMOVE VAPORS/PREVENT VAPOR BUILDUP. VENT CURING EQUIPMENT TO OUTDOORS/SUITABLE EMISSION CONTROL DEVICE. Eye Protection: SAFETY GLASSES OR GOGGLES Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health Spec Gravity:1.5-2 Solubilit y in Water: INSOLUBLE Appearance and Odor:BLACK TAPE, NO ODOR. Percent Volatiles by Volume:0.5-2% Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:CO, CO2 Waste Disposal Methods: UNCURED: INCINERATE AFTER MIXING W/FLAMMABLE MATERIAL IN INDUSTRIAL/COMMERCIAL FACILITY. CURED: DISPOSE OF IN SANITARY LANDFILL ACCORDING TO STATE, LOCAL, OR FEDERAL **REGULATIONS.** 

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this info rmation to their particular situation.