View NSN Online: https://aerobasegroup.com/nsn/3439-00-153-4280

Product ID:SOLDER ALLOYS OF LEAD, TIN, SILVER, BIMUTH,

MSDS Date:03/13/1990

FSC:3439

NIIN:00-153-4280

MSDS Number: BPTWC
=== Responsible Party ===
Company Name:ALPHA METALS

Address:600 ROUTE 440

City: JERSEY CITY

State:NJ ZIP:07304 Country:US

Info Phone Num:201-434-6778

Emergency Phon e Num:201-434-6778

CAGE:96613

=== Contractor Identification === Company Name:DEANCO INC Address:7933 QUEENAIR DR Box:City:GAITHERSBURG

State:MD

ZIP:20879-4137

Country:US

Phone:301-948-5444

CAGE:9K946

Company Name: FRYS METALS INC (FORMER ALPHA METALS)

Address:600 ROUTE 440 Box:City:JERSEY CITY

State:NJ ZIP:07304 Country:US

Phone:201-434-6778

CAGE:96613

======= Composition/Information on Ingredients ========

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Other REC Limi

ts:NONE RECOMMENDED OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9293

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:TIN CAS:7440-31-5

RTECS #:XP7320000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9293

Ingred Name: SILVER (SARA III)

CAS:7440-22-4

RTECS #:VW3500000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9293

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:BISMUTH

CAS:7440-69-9

RTECS #:EB2600000

Other REC Limits: NONE RECOMMEN

DED

Ingred Name: ANTIMONY (SARA III)

CAS:7440-36-0

RTECS #:CC4025000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG SB/M3; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: INDIUM

CAS:7440-74-6

RTECS #:NL1050000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.1 MG/M3

ACGIH TLV:0.1 MG/M3; 9293

========== Hazards Identification ===========================

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA

	N	\cap	
-	ıvı		

Health Hazards Acute and Chronic:ACUTE: INHALATION OF FUMES MAY CAUSE NERVOUS SYSTEM AND MUSCLE IRREGULARITIES, IRRITATION OF EYES, NOSE, THROAT, AND RESPIRATORY SYSTEM, METAL FUME FEVER. CHRONIC: INHALATION OF FUMES MAY CAUSE CANCER, SIDEROSIS, AND AFFECT LUNG FUNCTION.

Explanation of Carcinogenicity: IARC CLASSES LEAD AND SOME LEAD COMPOUNDS AS 2B CARCINOGENS (POSSIBLE CARCINOGENS).

Effects of Overexposure:INHALATION: NAUSEA, DIZZINESS, DRYNESS OF NOSE AND THROAT, C

OUGHING, WHEEZING AND SHORTNESS OF BREATH. EYES: REDNESS, TEARING, BLURRED VISION.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

FIRST AID: INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NEEDED. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. FOR BURNS, COOL AREA AND SEE DOCTOR. INGESTION: DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER

IMMEDIATELY.
======================================
Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:WHEN HEATED TO HIGH TEMPERATURES, LEAD EMITS HIGHLY TOXIC FUMES.

======== Accidental Release Measures ============

Spill Release Procedures: SWEEP UP OR MOP. PLACE RESIDUE IN A CONTAINER FOR DISPOSAL

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:REMOVE ANY COMBUSTIBLES FROM WORK AREA: SPARKS OR WELDING ARC COULD IGNITE NEARBY COMBUSTIBLES.

Other Precautions:FOOD AND DRINK SHOULD NOT BE CONSUMED OR TOBACCO PRODUCTS USED NOR COSMETICS APPLIED IN AREAS WHERE SOLDER MAY BE USED.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: USE N

IOSH/MSHA APPROVED RESPIRATOR FOR WELDING

FUMES OR SUPPLIED AIR RESPIRATOR IN CONFINED SPACES OR WHERE FUME CONCENTRATION EXCEEDS REGULATORY LIMITS.

Ventilation: USE MECHANICAL OR LOCAL EXHAUST OR BOTH TO MAINTAIN LEVELS OF FUMES BELOW REGULATORY LIMITS.

Protective Gloves: WORK GLOVES

Eye Protection: SAFETY GLASSES

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH HANDS AFTER USE AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOT

HING BEFORE REUSE.

Supplemental Safety and Health

========= Physical/Chemical Properties ===========

HCC:N1

Solubility in Water: NEGLIGIBLE

Appearance and Odor:OPAGUE, CHARCOAL COLORED SOLID

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, HYDROGEN PEROXIDE >52% Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:LEAD OXIDE AN

D ANTIMONY OXIDE MAY BE

VOLVED AT TEMPERATURES GREATER THAN 1000F.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.