View NSN Online: https://aerobasegroup.com/nsn/8030-00-598-5915

SANCHEM INC SUB OF SANTELL CHEMICAL CO -- NO-OX-ID A SPECIAL -- 8030-00-598-5915

Product ID:NO-OX-ID A SPECIAL

MSDS Date:07/03/1991

FSC:8030

NIIN:00-598-5915

MSDS Number: BPVBT === Responsible Party ===

Company Name: SANCHEM INC SUB OF SANTELL CHEMICAL CO

Address:1600 S CANAL ST

City:CHICAGO

State:IL

ZIP:60616-1106

Country:US

Info Phone Num:312-733-6100

Emergency

Phone Num:312-733-6100

Preparer's Name: JOHN W RIBBER

CAGE:LO672

=== Contractor Identification === Company Name:SANCHEM INC Address:1600 S. CANAL ST

Box:City:CHICAGO

State:IL ZIP:60616 Country:US

Phone:312-733-6100

CAGE:56086

Company Name: SANCHEM INC SUB OF SANTELL CHEMICAL CO

Address:1600 S CANAL ST

City:CHICAGO

State:IL

ZIP:60616-1106 Country:US

Phone:312-733-6100

CAGE:LO672

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS, RULE-66 (NIOSH RECOM

MENDATIONS FOR AN 8 HR EXPOSURE TO 100% MINERAL SPIRITS-RULE 66: 350 MG/M3) CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 8% Other REC Limits:NIOSH LIMIT ABOVE OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293 Ingred Name:PETROLEUM WAX CAS:64742-51-4 Fraction by Wt: 38% Other REC Limits: NONE SPECIFIED Ingred Name:MICROCRYSTALLINE WAX CAS:63231-60-7 Fraction by Wt: 38% Other REC Limits: NONE SPECIFIED Ingred Name: REFINED PETROLEUM OIL CAS:64742-63-8 Fraction by Wt: 15% Other REC Limits: NONE SPECIF **IED** Ingred Name: FATTY ACID ESTER CAS:68937-84-8 Fraction by Wt: 1.0% Other REC Limits: NONE SPECIFIED =========== Hazards Identification ========================== Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure: MAY CAUSE MINOR SKIN IRRITATION

Medical Cond Aggravated by Exposure: NONE KNOWN

First Aid:WASH WITH SOAP AND WATER. IF

INGESTED INDUCE VOMITING.
======================================
Flash Point Method:COC Flash Point:250F,121C Lower Limits:0.9 Upper Limits:6.0 Extinguishing Media:DRY CHEMICAL, FOAM, SAND Fire Fighting Procedures:RECOMMEND SUPPLIED AIR RESPIRATOR Unusual Fire/Explosion Hazard:WATER MAY CAUSE FROTHING WHICH MAY CAUSE SPLATTERING OF HOT MATERIAL.
======== Accidental Release Measures ==========
Spill Release Procedures:SCOOP UP AND WASH ARE
A DOWN WITH SOAP AND WATER. STORE IN SEALED DRUMS FOR DISPOSAL.
======================================
Handling and Storage Precautions:STORE IN COOL DRY AREA AWAY FROM OPEN FLAMES, HEAT OR SPARKS. Other Precautions:NONE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT REQUIRED Protective Gloves:OPTIONAL Eye Protection:GOGGLES Other Protective Equipment:NOT REQUIRED Work Hygienic Practices:WASH HANDS BEFORE EA TING. Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:N1 Boiling Pt:B.P. Text:450F,232C Melt/Freeze Pt:M.P/F.P Text:140 TO 150F Spec Gravity:0.90 (WATER=1) Solubility in Water:NOT SOLUBLE Appearance and Odor:LIGHT TO DARK BROWN GREASE
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OR

HYDR

OCARBONS

======= Disposal Considerations ===========

Waste Disposal Methods: NORMAL SCAVENGER

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profe ssional advice to verify and assume responsibility for the suitability of this information to their particular situation.