

ROCKWELL INTERNATIONAL CORP GOVERNMENT PRODUCTS -- A1-3222-V-1088 --
2530-01-128-4219

=====
Product Identification
=====

Product ID:A1-3222-V-1088

MSDS Date:01/28/1993

FSC:2530

NIIN:01-128-4219

MSDS Number: BPVRC

=== Responsible Party ===

Company Name:ROCKWELL INTERNATIONAL CORP GOVERNMENT PRODUCTS

Address:2135 W MAPLE RD

City:TROY

State:MI

ZIP:48084-7121

Country:US

Preparer's Name:HMIS TECHNICIA

N

CAGE:78500

=== Contractor Identification ===

Company Name:MERITOR HEAVY VEHICLE SYSTEMS LLC

Address:2135 W MAPLE RD

Box:City:TROY

State:MI

ZIP:48084

Country:US

Phone:248-435-8207

CAGE:78500

=====
Composition/Information on Ingredients
=====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

=====
Hazards Identification
=====

Routes of En

try: Inhalation: YES Skin: NO Ingestion: NO
Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: YES
Health Hazards Acute and Chronic: ACUTE: MINOR EYS/SKIN IRRITATION.
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &
MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE
LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER
OF THE BOWEL.

Explanation of Carcinogenicity: ASBESTOS IS A KNOW
N HUMAN CARCINOGEN.

Effects of Overexposure: INHALATION: FATIGUE AND SHORTNESS OF BREATH
THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.
DIARRHEA, VOMITING, AND NA USEA.

Medical Cond Aggravated by Exposure: ASTHMA, EMPHYSEMA, AND TUBERCULOSIS
ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

=====
===== First Aid Measures =====

First Aid: INHALATION: REMOVE
TO FRESH AIR. SEE DOCTOR. EYES: RINSE
THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH
THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.
INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING. SEE DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point: NOT REQUIRED

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL F
ACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures: VACUUM THE MATERIAL WITH A HEPA FILTERED
VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE
RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE
MATERIAL WITH WATER & SURFACTAN T AND THEN SHOVEL OR MOP UP
C

CONTAMINATION.

===== Handling and Storage =====

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves:COTTON OR LEATHER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING ITEM. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN. MSDS NOT AVAILABLE FROM MANUFACTURER. WHEN HMIS IS ABLE TO OBTAIN AN MSDS FROM MANUFACTURER, THIS RECORD WILL BE UPDATED. INGREDIENTS ARE FROM DLSC TIR PART M OR PARTMASTER TECHNICAL CHARACTERISTICS.

===== Physical/Chemical Properties =====

HCC:T6

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BRAKE SHOE

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid:ACCUMULATIONS OF DUST

Hazardous Decomposition Products:ASBESTOS DUST

===== Disposal Considerations =====

Waste Disposal Methods:WET THE MATERIAL WITH

H WATER AND SURFACTANT.

PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informatio

n to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.