View NSN Online: https://aerobasegroup.com/nsn/1260-01-073-5886

UNION CARBIDE CHEMICALS & PLASTICS CO., INC. -- 11507453 NEODYMIUM DOPED YTRIUM ALUMINUM GA -- 1260-01-073-5886

Product ID:11507453 NEODYMIUM DOPED YTRIUM ALUMINUM GA

MSDS Date:05/01/1991

FSC:1260

NIIN:01-073-5886

MSDS Number: BPWYY === Responsible Party ===

Company Name: UNION CARBIDE CHEMICALS & PLASTICS CO., INC.

Address:750 S 32ND STREET

City:WASHOUGAL

State: WA

ZIP:98671 Country:US

Info Phone Num: 206-835-8566

Emergency Phone Num:800-822-4357

CAGE:DO713

=== Contractor Identification ===

Company Name: UNION CARBIDE CHEM & PLASTICS CO INC

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Phone:203-794-6753/304-744-3487

CAGE:DO713

======= Composition/Information on Ingredients ========

Ingred Name: NEODYMIUM OXIDE

CAS:1313-97-9

Fraction by Wt: 0.85%

Other REC Limits: NONE RECOMMENDED

Ingred Name:YTRIUM OXIDE

CAS:1314-36-9

RTE

CS #:ZG3850000 Fraction by Wt: 56.88% Other REC Limits: NONE RECOMMENDED Ingred Name: ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS FORMS) (SARA III) CAS:1344-28-1 RTECS #:BD1200000 Fraction by Wt: 42.83% Other REC Limits: NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST: 9293 ========== Hazards Identification ================ Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: NO EVIDENCE OF ADVERSE EFFECTS. Effects of Overexposure: NO EVIDENCE OF ADVERSE EFFECTS. Medical Cond Aggravated by Exposure: NONE First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: NO HARMFUL EFFECTS. Extinguishing Media: NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPIATE SURROUNDING FIRE. ======== Accidental Release Measures ============ Spill Release Procedures: BROKEN CRYSTALS HAVE SHARP EDGES. GLOVES SHOULD BE WORN WHEN CLEANING UP A BROKEN CRYSTAL.

========== Handling and Storage ============

Handling and Storage Precautions: NORMAL PRECAUTIONS COMMON TO SAFE MANUFACTURING PRACTICES SHOULD BE FOLLOWED IN HANDLING AND STORAGE. ALWAYS MACHINE A CRYSTAL USING WET METHODS.

Other Precautions: USE OF THIS CRYS

TAL IN LASER OPERATIONS SHOULD BE SUPERVISED BY QUALIFIED, KNOWLEDGEABLE PERSONNEL, IN ACCORDANCE WITH ANSI Z 136.1, THE AMERICAN NATIONAL STANDARD FOR THE SAFE USE OF LASERS. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: IF EXCESSIVE DUSTING OCCURS WHEN MACHINING, WEAR NIOSH OR MSHA APPROVED DUST RESPIRATOR. Ventilation:LOCAL DUST PICK UP RECOMMENDED WHEN MACHINING. Protective Gloves:RECOMMENDED. Eve Protection: SAFETY GLASSES. Other Protective Equipment:NONE Work Hygienic Practices: STANDARD PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health PROLONGED CONTACT WITH DUST OR POWDER FROM MACHINING MAY CAUSE DRYING OF SKIN. \*\*\* NOTE: THIS IS AN ARTICLE. MANUFACTURER SUPPLIED MSDS FOR MANUFACTURING OPERATIONS \*\*\* ========= Physical/Chemical Properties =========== HCC:N1 Melt/Freeze Pt:M.P/F.P Text:3578F,1970C Spec Gravity:4.55 Solubility in Water: NEGLIGIBLE Appearance and Odor:TRANSPA RENT, PURPLE. NO ODOR. ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES ETHYLENE OXIDE, CHROMIUM TRIFLUORIDE. Stability Condition to Avoid:NONE Hazardous Decomposition Products:NONE ======= Disposal Considerations ============

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.