

=====
Product Identification
=====

Product ID:PETROLATUM

MSDS Date:05/10/1991

FSC:6505

NIIN:00-133-8025

MSDS Number: BPYCS

=== Responsible Party ===

Company Name:SPECTRUM CHEMICAL MANUFACTURING CORP.

Address:14422 SOUTH SAN PEDRO STREET

City:GARDENA

State:CA

ZIP:90248-2027

Country:US

Info Phone Num:213-516-8000

Emergency Phone Num:213-516-8000

CAGE:63415

=== Contractor Identification ===

C

Company Name:SPECTRUM LABORATORY PRODUCTS INC

Address:14422 S SAN PEDRO ST

Box:City:GARDENA

State:CA

ZIP:90248-2027

Country:US

Phone:310-516-8000/FAX: 310-516-9843

CAGE:63415

=====
Composition/Information on Ingredients
=====

Ingred Name:GREASE, PETROLEUM

CAS:8009-03-8

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP

:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION OF MIST MAY CAUSE RESPIRATORY IRRITATION, LIPID PNEUMONIA/GRANULOMA OF LUNG. CONTACT WITH SKIN MAY CAUSE HYSENSITIVITY REACTIONS IN SOME. CONTACT WITH EYES MAY CAUSE IRRITATION. SWAL LOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE SYSTEM IRRITATION. CHRONIC: SKIN CONTACT MAY CAUSE FOLLICULITIS.

Explanation of Carcinogenicity:IARC LIST MINERAL OILS AS IARC GROUP 3-INADEQUATE EVIDENCE.

Effects of Overexpos

ure:INHALATION: COUGHING, SHORTNESS OF BREATH.

EYES: REDNESS, TEARING, BLURRED VISION, DISCOMFORT. SKIN: RASH, REDNESS, DISCOMFORT. INGESTED: NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALED: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF BREATHING STOPPED. GIVE OXYGEN IF BREATHING DIFFICULT. GET MEDICAL ATTENTION. EYES: FLUSH WITH LOTS OF WAT

ER FOR 15 MINUTES, HOLD LIDS

OPEN. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP AND WATER. INGESTED: TREAT SYMTOMATICALLY AND SUPPORTIVLY. GET MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>360F,>182C

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR REGULAR FOAM

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. MOVE

CONTAINER FROM FIRE IF CAN BE DONE AT NO RISK. DO NOT SCATTER SPILLED MATERIAL WITH HIGH PRESSURE WATER.

Unusual Fire/Explosion Hazard:DIKE FIRE CONTROL WATER FOR LATER DISPOSAL.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP AND PLACE IN CONTAINERS FOR LATER DISPOSAL. DO NOT FLUSH TO SEWER OR WATERWAYS. KEEP UNECESSARY PEOPLE AWAY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling

and Storage =====

Handling and Storage Precautions:STORE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF CONDITIONS WARRANT; USE NIOSH/MSHA APPROVED RESPIRATOR, OR SUPPLIED AIR RESPIRATOR, OR SCBA, AS SITUATION REQUIRES. USE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW REGULATORY LIMITS IF VAPORS OR MISTS GENERATED.

Protective Gloves:RUBBER IF PROLONGED OR REPEATED CONTACT

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>500F,>260C

Melt/Freeze Pt:M.P/F.P Text:>10

0F,>38C

Vapor Pres: