

SPECTRUM CHEMICAL MANUFACTURING CORP. -- PETROLATUM -- 6505-00-133-8025

=====  
Product Identification  
=====

Product ID:PETROLATUM

MSDS Date:05/10/1991

FSC:6505

NIIN:00-133-8025

MSDS Number: BPYCS

=== Responsible Party ===

Company Name:SPECTRUM CHEMICAL MANUFACTURING CORP.

Address:14422 SOUTH SAN PEDRO STREET

City:GARDENA

State:CA

ZIP:90248-2027

Country:US

Info Phone Num:213-516-8000

Emergency Phon

e Num:213-516-8000

CAGE:63415

=== Contractor Identification ===

Company Name:SPECTRUM LABORATORY PRODUCTS INC

Address:14422 S SAN PEDRO ST

Box:City:GARDENA

State:CA

ZIP:90248-2027

Country:US

Phone:310-516-8000/FAX: 310-516-9843

CAGE:63415

=====  
Composition/Information on Ingredients  
=====

Ingred Name:GREASE, PETROLEUM

CAS:8009-03-8

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

Routes of Entry: Inh

alation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: INHALATION OF MIST MAY CAUSE  
RESPIRATORY IRRITATION, LIPID PNEUMONIA/GRANULOMA OF LUNG. CONTACT  
WITH SKIN MAY CAUSE HYSENSITIVITY REACTIONS IN SOME. CONTACT WITH  
EYES MAY CAUSE IRRITATION. SWAL LOWING LARGE AMOUNTS MAY CAUSE  
DIGESTIVE SYSTEM IRRITATION. CHRONIC: SKIN CONTACT MAY CAUSE  
FOLLICULITIS.

Explanation of Carcinogenicity:IARC LIST MINERAL O  
ILS AS IARC GROUP  
3-INADEQUATE EVIDENCE.

Effects of Overexposure:INHALATION: COUGHING, SHORTNESS OF BREATH.  
EYES: REDNESS, TEARING, BLURRED VISION, DISCOMFORT. SKIN: RASH,  
REDNESS, DISCOMFORT. INGESTED: NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALED: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF  
BREATHING STOPPED. GIVE OXYGEN IF BREATHING D  
IFFICULT. GET MEDICAL  
ATTENTION. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS  
OPEN. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHES. WASH WITH  
SOAP AND WATER. INGESTED: TREAT SYMTOMATICALLY AND SUPPORTIVLY. GET  
MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:>360F,>182C  
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR  
REGULAR FOAM

F  
ire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. MOVE  
CONTAINER FROM FIRE IF CAN BE DONE AT NO RISK. DO NOT SCATTER  
SPILLED MATERIAL WITH HIGH PRESSURE WATER.

Unusual Fire/Explosion Hazard:DIKE FIRE CONTROL WATER FOR LATER  
DISPOSAL.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP AND PLACE IN CONTAINERS FOR LATER  
DISPOSAL. DO NOT FLUSH TO SEWER OR WATERWAYS. KEEP UNECESSARY  
PEOPLE AWAY.

Neutralizing Agent

:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF CONDITIONS WARRANT; USE NIOSH/MSHA APPROVED RESPIRATOR, OR SUPPLIED AIR RESPIRATOR, OR SCBA, AS SITUATION REQUIRES. USE IN ACCORDANCE WITH 29 CFR

1910.134.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW REGULATORY LIMITS IF VAPORS OR MISTS GENERATED.

Protective Gloves:RUBBER IF PROLONGED OR REPEATED CONTACT

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>500F,>260C

Melt/Freeze Pt:M.P/F.P Text:>100F,>38C

Vapor Pres: