View NSN Online: https://aerobasegroup.com/nsn/9150-00-185-0629 FRANKLIN OIL CORP -- RUST FOIL 2675 -- 9150-00-185-0629 ============ Product Identification ========================= Product ID:RUST FOIL 2675 MSDS Date:08/03/1990 FSC:9150 NIIN:00-185-0629 MSDS Number: BPYDT === Responsible Party === Company Name: FRANKLIN OIL CORP Address:FRANKLIN PARK Box:30 City:BEDFORD State:OH ZIP:44146 Country:US Info Phone Num:216-232-3000 Emergency Phone Num:216-232-3000 CAGE:84591 === Contractor Identification === Company Name: FRANKLIN OIL CORP Address:FRANKLIN PARK Box:30 City:BEDFORD State:OH ZIP:44146 Country:US Phone:216-232-3000 CAGE:84591 ======= Composition/Information on Ingredients ======== Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT **NAPHTHENIC** CAS:64742-53-6 RTECS #:PY8036000

Other REC Limits: NONE RECOMMENDED

ACGIH TLV:5 MG/M3 (OIL MIST)

============= Hazards Identification ========================

Routes of Entry: Inhalation:

YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-INGESTION:LOW TOXICITY. MAY CAUSE GI TRACT IRRITATION. INHALATION:INHALATION OF MIST/VAPORS/FUMES MAY CAUSE RESPIRATORY TRACT IRRITATION. SMALL AMOUNT ASPIRATED INTO LUNGS MAY CAUSE CHEMICAL PNE UMONITIS. EYE:IRRITATION. SKIN:REPEATEDCONTACT MAY CAUSE IRRITATION. CHRONIC:DERMATITIS. Effects of Overexposure:EYE:IRRITATION. SKIN:DRYNESS. INHALATION OF MIS T:COUGHING, DIFFICULTY IN BREATHING. INGESTION:DIARRHEA. Medical Cond Aggravated by Exposure:SKIN DISEASES.
======================================
First Aid:SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION:REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE:I MMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION:GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.
======================================
Flash Point Method:COC Flash Point:>275F,>135C Lower Limits:1.0% Upper Limits:6.0% Extinguishing Media:CO2,FOAM,DRY CHEMICAL,WATER SPRAY OR FOG Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:HOT VAPORS FORM EXPLOSIVE MIXTUR E WITH AIR.
========= Accidental Release Measures ==========
Spill Release Procedures:SMALL SPILL: WIPE UP WITH RAGS OR TOWELS. LARGE SPILLS: EVACUATE AREA. VENTILATE AREA. DIKE TO RETAIN FLUID. PUMP UP FREE LIQUID OR ABSORB IN INERT MATERIAL, COLLECT INTO DRUMS FOR DISPOSAL. DO NOT FL USH TO SEWER OR WATERWAY.
========== Handling and Storage ============
Handling and Storage Precautions:STORE IN A CLOSED CONTAINER AWAY FROM EXTRE

ME HEAT & OPEN FLAMES.

Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE. DO NOT PRESSURIZE, CUT, WELD OR EXPOSE TO HEAT, FLAME, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE NORMALLY REQUIRED. USE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN SPRAYING OR USING IN CONFINED SPACES.

Ventilation:MFR RECM LOCAL EXHAUST

: CONTROL TO TLV

Protective Gloves: RUBBER

Eye Protection: SAFETY GLASSES

Other Protective Equipment: USE EYE PROTECTION IAW STANDARD SAFE SHOP PRACTICES

Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH THIS PRODUCT.

Supplemental Safety and Health

======== Physical/Chemical Properties ===========

HCC:V6

Boiling Pt:B.P. Text:>500F,>260C

Vapor Pres:1 Spec Gravity:0.89

Evaporation Rate & Deference: