

DAY-GLO COLOR CORP -- 202 ACRYLIC PAINT GENERIC MSDS -- 8010-00-082-2421

=====
Product Identification
=====

Product ID:202 ACRYLIC PAINT GENERIC MSDS

MSDS Date:01/14/1986

FSC:8010

NIIN:00-082-2421

MSDS Number: BQCNF

=== Responsible Party ===

Company Name:DAY-GLO COLOR CORP

Address:4515 ST CLAIR

City:CLEVELAND

State:OH

ZIP:44103

Country:US

Info Phone Num:216-391-7070

Emergency Phone Num:216-391-70

70

Preparer's Name:J IRSAK

CAGE:58825

=== Contractor Identification ===

Company Name:DAY-GLO COLOR CORP

Address:4515 ST CLAIR AVE

Box:City:CLEVELAND

State:OH

ZIP:44103-1203

Country:US

Phone:216-391-7070

CAGE:58825

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICON DIOXIDE (VAPOR PRESSURE 0.0 MM HG @ 0 C)

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 107F,>42C

Lower Limits:1.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:CLEAR AR

EA. APPROACH FROM UPWIND. WEAR SELF-CONTAINED BREATHING APPARATUS. USE EMERGENCY RESPONSE GUIDE BOOK (DOT P 5800.3) GUIDE 26.

Unusual Fire/Explosion Hazard:KEEP FROM HEAT, ELEC EQUIP, SPARKS, OPEN FLAME. CLOSED CONTAINER MAY EXPLODE WHEN SUBJECTED TO HIGH HEAT. DENSE SMOKE MAY RESULT DURING COMBUSTION-HEALTH HAZARD

===== Accidental Release Measures =====

Spill Release Procedures:DIKE TO PREVENT SPREAD OR ENTRY TO SEWER. REMOVE IGNITION SOURCES. ABSORB ON INERT MATERIAL AND SCOOP INTO AN APPROPRIATE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT OR FIRE IN WELL VENTED AREA. STORE IN ACCORDANCE WITH OSHA 1910.106. KEEP CONTAINER CLOSED WHEN NOT IN USE. FOR INDUST USE ONLY.

Other Precautions:CONTAINS ONLY HYDROCARBONS REPORTED TO BE NONCARCINOGENIC. DO NOT WELD OR CUT ON/NEAR EMPTY DRUM, SINCE THIS PRODUCT OR ITS FUMES MAY IGNITE EXPLOSIVELY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED PEL - 5 MG/M3. IF EXCEEDED, USE NIOSH APPROVED RESPIRATOR OR AIR SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION SHOULD BE SUFFICIENT TO MAINTAIN VAPOR CONCENTRATIONS BELOW TLV.

Protective Gloves:NEOPRENE OR OTHER IMPERVIOUS MATERIAL

Eye Protection:GOGGLES OR GLASSES WITH SPLASH GUARDS

Other Protective Equipment:NONE REQUIRED

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING. RELAUDE
CONTAMINATED CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Vapor Density:> AIR

Spec Gravity:8.76 LBS/GAL

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:54.95

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

PEROXIDES AND STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, SPARKS, FLAMES, OR EXCESSI

VE

TEMPERATURE

Hazardous Decomposition Products:FUMES CONTAINING OXIDES OF CARBON,
NITROGEN, SULFUR RESULT UPON DECOMPOSITION.

Conditions to Avoid Polymerization:HEAT, SPARKS, FLAMES, OR EXCESSIVE
TEMPERATURE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION PREFERRED. COMPLY WITH APPLICABLE
LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is for
mulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.