

UNITED STATES WELDING CORP -- 4130 LOW ALLOY STEEL WELD WIRE -- 3439-00-606-5425

=====
Product Identification
=====

Product ID:4130 LOW ALLOY STEEL WELD WIRE

MSDS Date:01/06/1987

FSC:3439

NIIN:00-606-5425

MSDS Number: BQCSS

=== Responsible Party ===

Company Name:UNITED STATES WELDING CORP

Address:20700 DEARBORN ST

City:CHATSWORTH

State:CA

ZIP:91311-5912

Country:US

Info Phone Num:213-341-2021

Emer

gency Phone Num:213-341-2021

Preparer's Name:JORGE JACOBS

CAGE:58401

=== Contractor Identification ===

Company Name:ASTROLITE ALLOYS DIV OF ASTRO METALLUGICAL

Address:709 VIA ALONDRA

Box:City:CAMARILLO

State:CA

ZIP:93010-8714

Country:US

Phone:805-484-3621

CAGE:2R602

Company Name:UNITED STATES WELDING CORP

Address:3579 HWY 50 E SUITE 104

Box:City:CARSON CITY

State:NV

ZIP:89701-2807

Country:US

Phone:775-883-7878

CAGE:58401

=====
Composition/Information on Ingredients
=====

Ingr

ed Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Other REC Limits:NONE SPECIFIED.
OSHA PEL:10 MG/M3 FE2O3 FUME
ACGIH TLV:5 MG/M3 AS FE FUME

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 0.95%
Other REC Limits:NONE SPECIFIED.
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MOLYBDENUM
CAS:7439-98-7
RTECS #:QA4680000
Fraction by Wt: 0.20%
Other REC Limits:NONE SPECIFIED.
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9293

Ingred Name:GRAPHITE, SYNTHETIC
CAS:7440-44-0
RTECS #:FF5250100
Fraction by Wt: 0.3%
Other REC Limits:NONE SPECIFIED.
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:HEALTH HAZARDS ARE BASED ON HAZARDS
INVOLVED WHEN METAL RODS A

RE USED IN WELDING. FUMES MAY CAUSE

DIZZINESS, NAUSEA, IRRITATION OF NOSE AND THROAT, WATERY EYES, HEADACHE, BREATHING DIFFICULTY, COUGHING, CHEST PAINS, PULMONARY EDEMA, ASPHYXIATION, DEATH, NEUROLOGICAL DAMAGE, LUNG FIBROSIS, PNEUMOCONIOSIS, LUNG DISEASES.

Explanation of Carcinogenicity: THIS PRODUCT CONTAINS 2-A [53-96-3], AN OSHA REGULATED CARCINOGEN.

Effects of Overexposure: OVEREXPOSURE RESULTS IN DIZZINESS, NAUSEA, IRRITATION OF NOSE AND THROAT, WATERY EYES

, HEADACHE, BREATHING

DIFFICULTY, FREQUENT COUGHING, CHEST PAINS, PULMONARY EDEMA, NEUROLOGICAL DAMAGE, LUNG FIBROSIS, PNEUMOCONIOSIS, AND OTHER LUNG DISEASES.

Medical Cond Aggravated by Exposure: PERSONS WITH IMPAIRED PULMONARY FUNCTION, AIRWAY DISEASES AND CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, CHRONIC BRONCHITIS, ETC MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid: EYES: FLUSH WITH LARGE AMOUNTS OF WATER.

IF IRRITATION

PERSISTS GET MEDICAL ATTENTION. SKIN: IF IRRITATION DEVELOPS REMOVE CLOTHING AND WASH AREA OF SKIN WITH SOAP OR MILD DETERGENT. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING GIVE CPR. IF BREATHING DIFFICULT GIVE OXYGEN. GET MEDICAL ATTENTION. INGESTION: GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point: NONFLAMMABLE

Extinguishing Media: NONFLAMMABLE. USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures: SOLID FORM IS NOT COMBUSTIBLE UNDER NORMAL CONDITIONS. USE FIRE FIGHTING METHODS THAT ARE APPROPRIATE FOR THE SURROUNDING FIRE.

Unusual Fire/Explosion Hazard: MOLTEN METAL ALLOYS MAY EXPLODE ON CONTACT WITH WATER. MAY ALSO REACT VIOLENTLY WITH WATER, RUST, AND CERTAIN METAL OXIDES (E.G. OXIDES OF COPPER, IRON, LEAD).

===== Accidental Release Measures =====

Spill Release Procedures: IN SOLID

FORM THIS MATERIAL POSES NO SPECIAL
CLEAN-UP PROBLEMS.

Neutralizing Agent:NOT RELEVANT.

===== Handling and Storage =====

Handling and Storage Precautions:ACTUAL EXPOSURE SHOULD BE DETERMINED
BY MONITORING THE FUME IN THE OPERATOR'S BREATHING ZONE. TRAIN THE
EMPLOYEE TO KEEP HIS HEAD OUT OF THE FUMES.

Other Precautions:PREVENT WASTE FROM CONTAMINATING SURROUNDING
ENVIRONMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR WHEN WELDING,
BRAZING OR SOLDERING IN A CONFINED SPACE, IF TLV IS EXCEEDED.

Ventilation:LOCAL EXHAUST VENTILATION SHOULD BE USED TO CONTROL
EXPOSURE TO AIRBORNE FUMES WHENEVER POSSIBLE.

Protective Gloves:WEAR FLAMEPROOF WELDING GLOVES.

Eye Protection:USE SAFETY GLASSES,UNDER WELDING HELMET.

Other Protective Equipment:ARM PROTECTORS, APRONS, HATS, SHOULDER
PROTECTION. PROVIDE PROTECTION SCREENS AND FLASH GOGGLES, IF
NECESSARY.

Work Hygienic Practices:PREVENT WASTE FROM CONTAMINATING SURROUNDING
ENVIRONMENT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:ODORLESS FILLER METAL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:METAL FUMES (WHEN PRODUCT IS IN USE).

Conditions to Avoid Polymerization:WIL

L NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:PRIOR TO DISPOSAL, CONSIDER IF MATERIAL HAS RECOVERY VALUE. DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.