View NSN Online: https://aerobasegroup.com/nsn/8010-01-132-2976

CAAP CO INC -- POLYURETHANE ACCELERATOR -- 8010-01-132-2976

=========== Product Identification =============

Product ID:POLYURETHANE ACCELERATOR

MSDS Date:08/01/1992

FSC:8010

NIIN:01-132-2976

Kit Part:Y

MSDS Number: BQCWV
=== Responsible Party ===
Company Name: CAAP CO INC
Address: 152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-877-0375

Emergency Phone Num:203-877-0375

Prepa

rer's Name: CHRISTINE L. SLEDGE

CAGE:60922

=== Contractor Identification === Company Name:CAAP CO INC Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT ZIP:06460 Country:US

Phone:203-877-0375

CAGE:60922

======= Composition/Information on Ingredients ========

Ingred Name: METHYLISOBUTYLKETONE; MIBK (SARA 313)

CAS:108-10-1

RTECS #:SA9275000 Fraction by Wt: 38.4%


Other REC Limits: NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:



Flash Point Method:TCC Flash Point:23.0F,-5.0C

Lower Limits: 1.0 Upper Limits:11.5

Extinguishing Media: WATER FOG, DRY CHEMICAL, FOAM, OR CO2. DO NOT USE DIRECT WATER STREAM.

Fire Fighting Procedures: SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL NEARBY CONTA

INERS AND STRUCTURES EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:PROD-FLAMM LIQ. AVOID ACCUMULTN-MAY FLOAT ON WTR-REIGNIT ON WTR SURFACE. EXTING ALL SRCS OF IGNIT-VAPOR HEAVIER THAN AIR-TRVL DISTANCE TO IGNIT SOURCE/FLASHBACK ======== Accidental Release Measures ============ Spill Release Procedures: RMV IGNIT SRCS-DONT SMOKE IN AREA. WEAR PROTECT EQUIP W/SOLVENT RESIST GLOVES/APRON/BOOTS/SCBA IN PRESS DEMAND MODE/POSITIVE PRESS AIR-SUPPLIED RESP. DIKE & SOA K UP W/ABSORB, CLEANUP ABSORB/CONTAIN, S WEEP/WET MOP W/SOAP & WATER. VENT AREA. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: IF VAPOR/MIST, WEAR NIOSH RESP FOR EMISSION LEVELS AT POINT OF USE. RESP W/FULL FACEPIECE/PURIFY CARTRIDGE RESP FOR ORGANIC VAPOR/MIST, SCBA IN PRESS DEMAND MODE/POSITIVE PRESS AIR-SUPPLD RESP. SPRAY APPLIC, SPRAY BOOTH Ventilation: EXHST VENT TO KEEP CONC BELOW PEL. VENT AIR PAST OPRATR, VAPOR SRC, T HEN EXHST. FOLLOW GUIDELINES-"INDUSTRIAL VENT". Protective Gloves: SOLVENT RESISTANT GLOVES. Eye Protection: SAFETY GOGGLES OR SAFETY GLASSES. Other Protective Equipment: SOLVENT RESISTANT APRON AND BOOTS FOR SPILLS. Work Hygienic Practices: EYEWASH/SAFETY SHOWER SHOULD BE NEARBY/READY TO USE. WASH WELL WITH SOAP AND WATER AFTER HANDLING THE PRODUCT. Supplemental Safety and Health KEY1:F3. CAN WEAR FULL FACE PIECE RESPIRATOR IN PLACE OF GOGGLES OR GLASSES. DO NOT WEAR CONTACT LENSES WHEN USING THIS PRODUCT BECAUSE CONTACT LENSES CONTRIBUTE TO THE SEVERITY OF AN EYE INJURY.

======== Physical/Chemical Properties ==========

HCC:F2
Boiling Pt:B.P. Text:175-241F
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres:48
Vapor Density:2.9
Spec Gravity:(H20=1): 0.80
pH:6.0
Viscosity: