

TABCO PRODUCTS, INC -- EPOXY THINNER, TYPE II -- 8010-01-200-2637
===== Product Identification =====

Product ID:EPOXY THINNER, TYPE II
MSDS Date:01/01/1987
FSC:8010
NIIN:01-200-2637
MSDS Number: BQCXY
=== Responsible Party ===
Company Name:TABCO PRODUCTS, INC
Address:940 WEST 100 SOUTH
City:SALT LAKE CITY
State:UT
ZIP:84107
Country:US
Info Phone Num:801-595-0119
Emergency Phone Num:801-595-0119

C
AGE:0SYZ3
=== Contractor Identification ===
Company Name:TABCO PRODUCTS, INC
Address:940 WEST 100 SOUTH
Box:City:SALT LAKE CITY
State:UT
ZIP:84107
Country:US
Phone:801-595-0119
CAGE:0SYZ3

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 55%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA927

5000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPYLENE GLYCOL METHYL ETHER
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 35%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INGESTION: MODERATELY TOXIC; MAY CAUSE
NAUSEA, VOMITIN
G, DIARRHEA. INHALATION: CONCENTRATION OF 100-300
PPM CAUSE NOSE & THROAT IRRITATION. SKIN: PROLONGED EXPOSURE TO
CONCENTRATION ABOVE TLV CAUSE MO DERATE IRRITATION. EYES: LIQUID
CAUSES SEVERE IRRITATION. VAPORS CAUSE SLIGHT TO MODERATE
IRRITATION.

=====
===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN. SKIN:
REMOVE CLOTHING & FLUSH SKIN WITH WATER. INHALATION: REMOVE TO
FRESH AIR. IF BREATHING HA
S STOPPED, GIVE ARTIFICIAL RESPIRATION.
IF BREATHING I S DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. EYES:
IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL
ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:25.0F,-3.9C
Lower Limits:1.8
Upper Limits:10.1
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL OR
ALCOHOL TYPE FOAM APPLIED BY MANUFACTURER'S RECOMMENDED TECHNIQUES.
Fire Fighting P

rocedures:USE SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. COOL ADJACENT CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:VAPOR FORM FROM THIS PRODUCT AND MAY TRAVEL OR MOVE BY AIR CURRENTS & IGNITED BY PILOT LIGHTS, FLAMES, SMOKING, SPARKS, HEATERS, ELEC EQUIP, STATIC, ETC.

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH AND DO NOT TURN ON ANY IGNITION SOURCES UNTIL AREA IS DETERMINED TO BE FREE FROM EXPLOSION OR FIRE HAZARDS. COLLECT LARGE SPILLS FOR DISPOSAL. FLUSH SMALL SPILLS WITH WATER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND FLAME. AVOID BREATHING VAPOR. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. KEEP CONTAINER CLOSED.
Other Precautions:USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS IN HIGH CONCENTRATIONS.
Ventilation:LOCAL EXHAUST:WHERE VAPOR CAN ESCAPE INTO WORKPLACE. MECHANICAL (GENERAL):IF PRODUCT IS CONFINED W/IN CLOSED EQUIPMENT.
Protective Gloves:BUTYL
Eye Protection:MONOGOGGLES
Other Protective Equipment:EYE BATH, SAFETY SHOWER
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3
Spec Gravity:0.845+/-0.005
Evaporation Rate & Reference:5 (BU AC=1)
Solubility in Water:APPROXIMATELY 30%
Appearance and Odor:CLEAR, COLORLESS LIQUID WITH KETONE/ACETATE ODOR
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID ALKALINE MATERIALS, MINERAL ACIDS, AND HALOGENS.
Stability Condition to Avoid:HEAT, FIRE, IGNITION SOURCES
Hazardous Decomposition Products:BURNING CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

===== Disposal C

onsiderations =====

Waste Disposal Methods:INCINERATE IN A FURNACE WHERE PERMITTED UNDER
APPROPRIATE FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing thi

s

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.