View NSN Online: https://aerobasegroup.com/nsn/8040-01-296-1793

Product ID:FM (R) 410 CORE SPLICE ADHESIVE FOAM MSDS Date:01/12/1989 FSC:8040 NIIN:01-296-1793 **MSDS Number: BQDBR** === Responsible Party === Company Name: AMERICAN CYANAMID Address:1 CYANAMID PLAZA **City:WAYNE** State:NJ ZIP:07470 Country:US Info Phone Num:201-835-3100 **Emergency Phone Num:2** 01-835-3100 Preparer's Name: DR MARVIN A FRIEDMAN CAGE:07542 === Contractor Identification === Company Name: AMERICAN CYANAMID CO, INDUST CHEM & PLATICS DIV. Address:OLD POST RD Box:City:HAVRE DE GRACE State:MD ZIP:21078 Country:US Phone:201-835-3100 CAGE:07542

Ingred Name:GLASS Fraction by Wt: 4.4% Other REC Limits:NONE SPECIFIED ACGIH TLV:10 MG/M3 CEILING

Ingred Name:SILICA, AMORPHOUS CAS:112945-52-5 RTECS #:VV7310000 Fracti on by Wt: 28.5% Other REC Limits:NONE SPECIFIED OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:EPOXY RESIN Fraction by Wt: 60-100% Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture:ORAL LD50 RAT>7.5G/KG.LC50 RAT>250MG/M3.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:BASED ON PHYSICAL FORM, OVEREXPOSURE BY INGESTION OR INHALATION WILL NOT OCCUR. ALLERGIC SKIN REACTION OR PRIM

ARY SKIN IRRITATION MAY BE PRODUCED BY PROLONGED OR REPEATED DERMAL CONTACT WITH EPOXY RES INS. OVEREXPOSURE TO VAPOR DURING HEAT CURING MAY CAUSE IRRITATION OR INJURY TO RESPIRATORY TRACT & EYE IRRITATION. *

Effects of Overexposure:* OVEREXPOSURE TO SYNTHETIC AMORPHOUS SILICA DUST BY INHAL, SKIN, ORAL, DERMAL ROUTE NOT EXPECTED TO CAUSE ADVERSE EFFECTS. PRODUCT CONTAINS NONE OF CRYSTALLINE VARIETIES OF SILICA KNOWN TO CAUSE LUNG DISEASE. OVEREXPOSURE TO GLASS FIBERS

CAUSES SKIN & EYE IRRIT. INHAL OF GLASS FIBERS MAY CAUSE RESP CONGESTION/IRRIT.

First Aid:IN CASE OF SKIN CONTACT, IMMEDIATLEY WASH AFFECTED AREA WITH SOAP AND PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES. OBTAIN MEDICAL ATTENTION. DESTROY OR THOROUGHLY CLEAN SHOES BEFORE REUSE. DO NOT REUSE CONTAMINATED CLOTHING WITHOUT LAUNDERING. IN CASE OF EYE CONTACT, IMMEDIATELY IRRIGATE WITH PLENTY OF WA TER FOR

15 MINUTES.

Extinguishing Media:USE WATER, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS, POSITIVE PRESSURE BREATHING APPARATUS AND FULL FIREFIGHTING PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:MATERIAL MUST BE PREHEATED BEFORE IGNITION CAN OCCUR.

Spill

Release Procedures: EXPOSURE LEVEL UNKNOWN; WEAR NIOSH POSITIVE PRESSURE, SELF-CONTAINED RESPIRATOR; KNOWN, WEAR NIOSH APPRVD RESPIRATOR APPROP FOR LEVEL OF EXPOSURE. SWEEP UP SPILL & PLACE IN WASTE DISPOSAL CNTNR. FLUSH AREA W/WATER.

Handling and Storage Precautions:CUTTING, GRINDING, OR SANDING OF PARTS
FABRICATED AFTER CURING OF THIS MATERIAL MAY CREATE RESPIRABLE DUST
PARTICLES.
Other Precautions:AVOID
SKIN CONTACT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:BELOW PEL, RESPIRATORY PROTECTION NOT REQ'D. ABOVE PEL, USE NIOSH RESPIRATOR FOR MAT'L & LEVEL OF EXPOSURE. RESPIRATORY PROTECTION FOR DUST MAY BE REQ'D (CUTTING,GRINDING,SANDING). SEE "GUIDE TO INDUS TRIAL RESPIRATORY PROTECTION" (NIOSH).

Ventilation: WHEN NOT USED IN A CLOSED SYSTEM, PROVIDE GOOD ENCLOSURE & LOCAL EXHAUST VENT WHEN SPRAYING OR CURING AT ELEVATED TEMPS.

Protective Gloves:BARRIER CREAM IN CONJUNCTION W/GLOVES Eye Protection:IF CONTACT, CHEM SPLASH GOGGLES,FACESHLD Other Protective Equipment:EYE WASH,SAFETY SHOWER IF EXPOSURE POTENTIAL.PROTECT CLOTH(APRO,WRK PANTS,LONG SLEEVE WRK SHIRT,DISPOSABLE COVERALLS).

Work Hygienic Practices:DONT CARRY/STORE FOOD,BEVERAGES,TOBACCO WHERE MAT'L IN USE.BEFORE EATING,DRINKING,SMOKING,WASH FACE/HANDS W/SOAP & WATER

Supplemental Safety and Health

======== Physical/Chemical Properties

Spec Gravity:1.08-1.10 Solubility in Water:NEGLIGIBLE Appearance and Odor:BLUE FILM, NO ODOR Percent Volatiles by Volume:NEGLIG

Stability Indicator/Materials to Avoid:YES NO SPECIFIC INCOMPATIBILITY Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:THERMAL DECOMPOSITION OR COMBUSTION MAY PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE. Conditions to Avoid Polymerization:POLYMERIZA

TION MAY OCCUR SLOWLY AT ROOM TEMPERATURE. STORE AT OR BELOW 0 F.

Waste Disposal Methods:DISPOSAL MUST BE MADE IN ACCORDANCE WITH APPLICABLE GOVERNMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informa tion to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.