

DEFT INC CHEMICAL COATING DIV -- TT-P-2756, 36118, 1-COAT PC03GY381 -- 8010-01-354-0969  
===== Product Identification =====

Product ID:TT-P-2756, 36118, 1-COAT PC03GY381  
MSDS Date:06/07/1991  
FSC:8010  
NIIN:01-354-0969  
Kit Part:Y  
MSDS Number: BQDVX  
=== Responsible Party ===  
Company Name:DEFT INC CHEMICAL COATING DIV  
Address:17451 VON KARMAN AVE  
City:IRVINE  
State:CA  
ZIP:92714-6205  
Country:US  
Info Phone Num:714-474-0400  
Emergency Phone Num:800-424-9300 CHEMTREC  
Preparer's Name:NORM GAUL  
CAGE:33461  
=== Contractor Identification ===  
Company Name:DEFT, INC.  
Address:17451 VON KARMAN AVE  
City:IRVINE  
State:CA  
ZIP:92614  
Country:US  
Phone:949-474-0400  
CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC ISOCYANATE, HEXAMETHYLENE DIISOCYANATE (HDI) CAS  
NO. 822-06-0, FREE MONOMER CONTENT LESS THAN 0.5%.  
CAS:28182-81-2  
RTECS #:NQ9170000  
Fraction by

Wt: 60%  
Other REC Limits:MOBAY-0.02 CEILING  
ACGIH TLV:0.005 PPM

Ingred Name:ETHYL-3-ETHOXYPROPIONATE (VP: .7 MMGH @ 68F)  
CAS:763-69-9  
RTECS #:UF3325000  
Fraction by Wt: 25%  
Other REC Limits:50 PPM-TWA/STEL 100

Ingred Name:N-BUTYL ACETATE (VP: 13 MMGH @ 68F)  
CAS:123-86-4  
RTECS #:AF7350000  
Fraction by Wt: 15%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:150 PPM/STEL 200  
ACGIH TLV:150 PPM/STEL 200  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: VAPORS IRRIT TO  
EYES-NOSE-THROAT. INHAL MAY CAUSE HEADACHES-DIFFICULT BREATH-LOSS  
OF CONSCIOUSNESS. CHRONIC: AS A RESULT OF PREVIOUS REPEAT  
OVEREXPOS/SINGLE LG DOSE, SOME INDIVIDUALS WILL DEVEL OP ISOCYANATE  
SENSITIZATION CAUSING A REACTION TO LATER EXPOS OF ISOCYANATE  
LEVELS WELL BELOW TLV VALUE OF ISOCYANATES

Effects o

f Overexposure:INHAL: RESP TRACT IRRIT, NERV SYS DEPRESS  
W/HEADACHE-DIZZI-STAG GAIT-CONFUSION-UNCONSCIOUS-COMA. EYE: IRRIT,  
POSS TEARING-REDNESS-SWELLING W/STING SENSATION. SKIN: IRRIT  
W/SWELLING-REDNESS-RASH-DRY-DE FAT. INGEST: IRRIT, POSS CORROSIVE  
ACTION IN MOUTH-STOMACH TISSUE-DIGEST TRACT. POSS ASPIR  
W/VOMITING-CHEM PNEUMONITIS

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY  
DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS. ISOCYANATE  
SENSIT

IZATION.

=====  
===== First Aid Measures =====

First Aid:INHAL: MOVE TO FRESH AIR. RESTORE BREATHING. ASTHMATIC TYPE SYMPTOMS-MAY BE IMMEDIATE OR DELAYED BY SEVERAL HOURS-GET MED AID. SKIN: REMOVE CONTAMINATED CLOTHING-WASH BEFORE REUSE. WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER (LOW PRESSURE) 15 MINUTES, LIFTING LIDS-GET MED AID. INGEST: DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON-GET MED AID.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:76.0F,24.4C  
Lower Limits:1.05%  
Upper Limits:7.60%  
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG  
Fire Fighting Procedures:FULL FIRE FIGHT EQUIP W/SCBA AND FULL PROTECT CLOTHING. MAY USE WATER TO COOL CLSD CNTNRS-PREVENT PRESSURE BUILD-UP/AUTO IGNIT/EXPLOS. IRRIT VAPORS W/COMBUSTN  
Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD TIGHT-MAY EXPLODE W/HEAT. ISOLATE FROM HEAT/IGNI  
T SOURCES. SPECIAL PRECAUTION W/APPLIC TO HOT SURFACES. OVEREXPOSURE-HEALTH HAZ-SYMPTOMS DELAYED

=====  
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BLDG THAT COMPLY W/OSHA 1910.106. AVOID STOR NEAR HIGH TEMP/FIRE/OPEN FLAMES/SPARK SOURCES. STORE IN TIGHTLY CLSD CNTNRS IN WELL VENT AREAS  
Other Precautions:KEEP CONTAINERS TIGHT AND UPRIGHT TO PREVENT LEAKAGE. PREVENT BREATHING OF VAPORS/SPRAY MIST. POSSIBLE ALLERGIC REACTION. AVOID CONTACT WITH EYES AND SKIN. DO NOT INGEST. DO NOT HANDLE UNTIL MFR SAFETY PRECAUTIONS ARE READ AND UNDERSTOOD.

=====  
===== Exposure Controls/Personal Protection =====

Respi

ratory Protection:RESP FOR ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING-FRESH AIR SUPPLIED). OBSERVE OSHA REG. PROVIDE VENT-KEEP EXPOS LEVELS BELOW PEL. VAPOR PARTIC RESP (TC23C NIOSH/MSHA) WHERE DEMONSTRATED THAT VAPOR LEVELS BELOW TEN TIMES APPLIC EXPOS LIMITS

Ventilation:UTILIZE EXHST VENT TO KEEP AIRBORNE CONC OF SOLVENT/HDI/POLYISOCYANATES BELOW RESPECTIVE TLV'S. RMV ALL IGNIT SOURCES

Protective Gloves:COTTON-NEOPRENE-RUBBER POLYETHYLENE

Eye Protection:SPLSH GUARD/SIDE-FACE SHIELD/CHEM GOGGLE

Other Protective Equipment:THE USE OF LONG SLEEVE AND LONG LEG CLOTHING IS RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM. SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:260-460F

Vapor Density:> THAN AIR

Spec Gravity:1.02521

Evaporation Rate & Reference:0.44 X N

-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:45.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid:CONTACT WITH MOISTURE, MATERIAL WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPER

ATURE: CARBON

MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND HDI

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL-STATE-LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED W/CARE-DUE TO PRODUCT RESIDUE AND FLAMMABLE VAPOR. DO NOT INCINERATE CLOSED CONTAINERS. EPA HAZARDOUS WASTE NUMBER/CODE: D001-F003-F005

Disclaimer (provided with this information)

by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.